

ISO/IEC JTC 1/SC 22/WG 14 N1757

Date: yyyy-mm-dd

Reference number of document: **ISO/IEC TS 18661**

Committee identification: ISO/IEC JTC 1/SC 22/WG 14

Secretariat: ANSI

5

Information Technology — Programming languages, their environments, and system software interfaces — Floating-point extensions for C — Part 2: Decimal floating-point arithmetic

10 *Technologies de l'information — Langages de programmation, leurs environnements et interfaces du logiciel système — Extensions à virgule flottante pour C — Partie 2: décimal arithmétique flottante*

Warning

15

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Copyright notice

5 This ISO document is a working draft or committee draft and is copyright-protected by ISO. While the reproduction of working drafts or committee drafts in any form for use by participants in the ISO standards development process is permitted without prior permission from ISO, neither this document nor any extract from it may be reproduced, stored or transmitted in any form for any other purpose without prior written permission from ISO.

Requests for permission to reproduce this document for the purpose of selling it should be addressed as shown below or to ISO's member body in the country of the requester:

10 *ISO copyright office*
Case postale 56 CH-1211 Geneva 20
Tel. +41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

15 Reproduction for sales purposes may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

	Page
Introduction	v
Background	v
IEC 60559 floating-point standard	v
5 C support for IEC 60559.....	vi
Purpose	vii
Additional background on decimal floating-point arithmetic	vii
1 Scope	1
2 Conformance	1
10 3 Normative references	2
4 Terms and definitions	2
5 C standard conformance.....	2
5.1 Freestanding implementations.....	2
5.2 Predefined macros.....	2
15 5.3 Standard headers.....	3
6 Decimal floating types	7
7 Characteristics of decimal floating types <code><float.h></code>	9
8 Operation binding	14
9 Conversions	14
20 9.1 Conversions between decimal floating and integer types.....	14
9.2 Conversions among decimal floating types, and between decimal floating and standard floating types	15
9.3 Conversions between decimal floating and complex types	16
9.4 Usual arithmetic conversions	16
25 9.5 Default argument promotion.....	16
10 Constants	16
11 Arithmetic operations	17
11.1 Operators	17
11.2 Functions	18
30 11.3 Conversions	19
11.4 Expression transformations	19
12 Library	20
12.1 Standard headers.....	20
12.2 Decimal floating-point environment in <code><fenv.h></code>	20
35 12.3 Decimal mathematics in <code><math.h></code>	23
12.4 Decimal-only functions in <code><math.h></code>	32
12.4.1 Quantum and quantum exponent functions	32
12.4.2 Decimal re-encoding functions.....	34
12.5 Formatted input/output specifiers.....	36
40 12.6 <code>strtodN</code> functions in <code><stdlib.h></code>	38
12.7 <code>wcstodN</code> functions in <code><wchar.h></code>	41
12.8 <code>strfromdN</code> functions in <code><stdlib.h></code>	42
12.9 Type-generic math for decimal in <code><tgmath.h></code>	43
45 Bibliography	48

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TS 18661 was prepared by Technical Committee ISO JTC 1, *Information Technology*, Subcommittee SC 22, *Programming languages, their environments, and system software interfaces*.

ISO/IEC TS 18661 consists of the following parts, under the general title *Floating-point extensions for C*:

- *Part 1: Binary floating-point arithmetic*
- *Part 2: Decimal floating-point arithmetic*
- *Part 3: Interchange and extended types*
- *Part 4: Supplemental functions*
- *Part 5: Supplemental attributes*

Part 1 updates ISO/IEC 9899:2011 (*Information technology — Programming languages, their environments and system software interfaces — Programming Language C*), Annex F in particular, to support all required features of ISO/IEC/IEEE 60559:2011 (*Information technology — Microprocessor Systems — Floating-point arithmetic*).

Part 2 supersedes ISO/IEC TR 24732:2009 (*Information technology – Programming languages, their environments and system software interfaces – Extension for the programming language C to support decimal floating-point arithmetic*).

Parts 3-5 specify extensions to ISO/IEC 9899:2011 for features recommended in ISO/IEC/IEEE 60559:2011.

Introduction

Background

IEC 60559 floating-point standard

5 The IEEE 754-1985 standard for binary floating-point arithmetic was motivated by an expanding diversity in floating-point data representation and arithmetic, which made writing robust programs, debugging, and moving programs between systems exceedingly difficult. Now the great majority of systems provide data formats and arithmetic operations according to this standard. The IEC 60559:1989 international standard was equivalent to the IEEE 754-1985 standard. Its stated goals were:

- 10 1 Facilitate movement of existing programs from diverse computers to those that adhere to this standard.
- 2 Enhance the capabilities and safety available to programmers who, though not expert in numerical methods, may well be attempting to produce numerically sophisticated programs. However, we recognize that utility and safety are sometimes antagonists.
- 15 3 Encourage experts to develop and distribute robust and efficient numerical programs that are portable, by way of minor editing and recompilation, onto any computer that conforms to this standard and possesses adequate capacity. When restricted to a declared subset of the standard, these programs should produce identical results on all conforming systems.
- 4 Provide direct support for
 - a. Execution-time diagnosis of anomalies
 - 20 b. Smoother handling of exceptions
 - c. Interval arithmetic at a reasonable cost
- 5 Provide for development of
 - a. Standard elementary functions such as exp and cos
 - b. Very high precision (multiword) arithmetic
 - 25 c. Coupling of numerical and symbolic algebraic computation
- 6 Enable rather than preclude further refinements and extensions.

To these ends, the standard specified a floating-point model comprising:

formats – for binary floating-point data, including representations for Not-a-Number (NaN) and signed infinities and zeros

30 *operations* – basic arithmetic operations (addition, multiplication, etc.) on the format data to compose a well-defined, closed arithmetic system; also specified conversions between floating-point formats and decimal character sequences, and a few auxiliary operations

context – status flags for detecting exceptional conditions (invalid operation, division by zero, overflow, underflow, and inexact) and controls for choosing different rounding methods

35 The IEC 60559:2011 international standard is equivalent to the IEEE 754-2008 standard for floating-point arithmetic, which is a major revision to IEEE 754-1985.

The revised standard specifies more formats, including decimal as well as binary. It adds a 128-bit binary format to its basic formats. It defines extended formats for all of its basic formats. It specifies data interchange

formats (which may or may not be arithmetic), including a 16-bit binary format and an unbounded tower of wider formats. To conform to the floating-point standard, an implementation must provide at least one of the basic formats, along with the required operations.

5 | The revised standard specifies more operations. New requirements include – among others – arithmetic operations that round their result to a narrower format than the operands (with just one rounding), more conversions with integer types, more **classifications** and comparisons, and more operations for managing flags and modes. New recommendations include an extensive set of mathematical functions and seven reduction functions for sums and scaled products.

10 | The revised standard places more emphasis on reproducible results, which is reflected in its standardization of more operations. For the most part, behaviors are completely specified. The standard requires conversions between floating-point formats and decimal character sequences to be correctly rounded for at least three more decimal digits than is required to distinguish all numbers in the widest supported binary format; it fully specifies conversions involving any number of decimal digits. It recommends that transcendental functions be correctly rounded.

15 | The revised standard requires a way to specify a constant rounding direction for a static portion of code, with details left to programming language standards. This feature potentially allows rounding control without incurring the overhead of runtime access to a global (or thread) rounding mode.

20 | Other features recommended by the revised standard include alternate methods for exception handling, controls for expression evaluation (allowing or disallowing various optimizations), support for fully reproducible results, and support for program debugging.

25 | The revised standard, like its predecessor, defines **its** model of floating-point arithmetic in the abstract. It neither defines the way in which operations are expressed (which might vary depending on the computer language or other interface being used), nor does it define the concrete representation (specific layout in storage, or in a processor's register, for example) of data or context, except that it does define specific encodings that are to be used for data that may be exchanged between different implementations that conform to the specification.

30 | IEC 60559 does not include bindings of its floating-point model for particular programming languages. However, the revised standard does include guidance for programming language standards, in recognition of the fact that features of the floating-point standard, even if well supported in the hardware, are not available to users unless the programming language provides a commensurate level of support. The implementation's combination of both hardware and software determines conformance to the floating-point standard.

C support for IEC 60559

35 | The C standard specifies floating-point arithmetic using an abstract model. The representation of a floating-point number is specified in an abstract form where the constituent components (sign, exponent, significand) of the representation are defined but not the internals of these components. In particular, the exponent range, significand size, and the base (or radix) are implementation-defined. This allows flexibility for an implementation to take advantage of its underlying hardware architecture. Furthermore, certain behaviors of operations are also implementation-defined, for example in the area of handling of special numbers and in exceptions.

40 | The reason for this approach is historical. At the time when C was first standardized, before the floating-point standard was established, there were various hardware implementations of floating-point arithmetic in common use. Specifying the exact details of a representation would have made most of the existing implementations at the time not conforming.

45 | Beginning with ISO/IEC 9899:1999 (C99), C has included an optional second level of specification for implementations supporting the floating-point standard. C99, in conditionally normative Annex F, introduced nearly complete support for the IEC 60559:1989 standard for binary floating-point arithmetic. Also, C99's informative Annex G offered a specification of complex arithmetic that is compatible with IEC 60559:1989.

ISO/IEC 9899:2011 (C11) includes refinements to the C99 floating-point specification, though is still based on IEC 60559:1989. C11 upgrades Annex G from “informative” to “conditionally normative”.

5 ISO/IEC Technical Report 24732:2009 introduced partial C support for the decimal floating-point arithmetic in IEC 60559:2011. TR 24732, for which technical content was completed while IEEE 754-2008 was still in the later stages of development, specifies decimal types based on IEC 60559:2011 decimal formats, though it does not include all of the operations required by IEC 60559:2011.

Purpose

10 The purpose of this Technical Specification is to provide a C language binding for IEC 60559:2011, based on the C11 standard, that delivers the goals of IEC 60559 to users and is feasible to implement. It is organized into five Parts.

Part 1 provides changes to C11 that cover all the requirements, plus some basic recommendations, of IEC 60559:2011 for binary floating-point arithmetic. C implementations intending to support IEC 60559:2011 are expected to conform to conditionally normative Annex F as enhanced by the changes in Part 1.

15 Part 2, this document, enhances TR 24732 to cover all the requirements, plus some basic recommendations, of IEC 60559:2011 for decimal floating-point arithmetic. C implementations intending to provide an extension for decimal floating-point arithmetic supporting IEC 60559-2011 are expected to conform to Part 2.

Part 3 (Interchange and extended types), Part 4 (Supplementary functions), and Part 5 (Supplementary attributes) cover recommended features of IEC 60559-2011. C implementations intending to provide extensions for these features are expected to conform to the corresponding Parts.

20 Additional background on decimal floating-point arithmetic

25 Most of today's general-purpose computing architectures provide binary floating-point arithmetic in hardware. Binary floating point is an efficient representation that minimizes memory use, and is simpler to implement than floating-point arithmetic using other bases. It has therefore become the norm for scientific computations, with almost all implementations following the IEEE 754 standard for binary floating-point arithmetic (and the equivalent international ISO/IEC 60559 standard).

30 However, human computation and communication of numeric values almost always uses decimal arithmetic and decimal notations. Laboratory notes, scientific papers, legal documents, business reports and financial statements all record numeric values in decimal form. When numeric data are given to a program or are displayed to a user, conversion between binary and decimal is required. There are inherent rounding errors involved in such conversions; decimal fractions cannot, in general, be represented exactly by binary floating-point values. These errors often cause usability and efficiency problems, depending on the application.

35 These problems are minor when the application domain accepts, or requires results to have, associated error estimates (as is the case with scientific applications). However, in business and financial applications, computations are either required to be exact (with no rounding errors) unless explicitly rounded, or be supported by detailed analyses that are auditable to be correct. Such applications therefore have to take special care in handling any rounding errors introduced by the computations.

40 The most efficient way to avoid conversion error is to use decimal arithmetic. Currently, the IBM z/Architecture (and its predecessors since System/360) is a widely used system that supports built-in decimal arithmetic. Prior to the IBM System z10 processor, however, this provided integer arithmetic only, meaning that every number and computation has to have separate scale information preserved and computed in order to maintain the required precision and value range. Such scaling is difficult to code and is error-prone; it affects execution time significantly, and the resulting program is often difficult to maintain and enhance.

45 Even though the hardware may not provide decimal arithmetic operations, the support can still be emulated by software. Programming languages used for business applications either have native decimal types (such as PL/I, COBOL, REXX, C#, or Visual Basic) or provide decimal arithmetic libraries (such as the BigDecimal class in Java). The arithmetic used in business applications, nowadays, is almost invariably decimal floating-

point; the COBOL 2002 ISO standard, for example, requires that all standard decimal arithmetic calculations use 32-digit decimal floating-point.

The IEEE has recognized the importance of this. Decimal floating-point formats and arithmetic are major new features in the IEEE 754:2008 standard and its international equivalent IEC 60559:2011.

Information Technology — Programming languages, their environments, and system software interfaces — Floating-point extensions for C — Part 2: Decimal floating-point arithmetic

5 1 Scope

This document, Part 2 of ISO/IEC Technical Specification 18661, extends programming language C, as specified in IEC 9899:2011 (C11) with changes specified in Part 1 of ISO/IEC Technical Specification 18661, to support decimal floating-point arithmetic conforming to ISO/IEC/IEEE 60559:2011. It covers all requirements of IEC 60559 as they pertain to C decimal floating types.

10 This document supersedes ISO/IEC TR 24732:2009 (Information technology – Programming languages, their environments and system software interfaces – Extension for the programming language C to support decimal floating-point arithmetic).

This document does not cover binary floating-point arithmetic (which is covered in Part 1 of ISO/IEC TS 18661), nor does it cover most optional features of IEC 60559.

15 2 Conformance

An implementation conforms to Part 2 of Technical Specification 18661 if all the following are true:

- a) It meets the requirements for a conforming implementation of C11 with all the changes to C11 specified in Parts 1 and 2 of Technical Specification 18661.
- 20 b) It meets the requirements of the following clauses of C11 Annex F with all the changes specified in Parts 1 and 2 of Technical Specification 18661:
 - F.2.1 Infinities and NaNs
 - F.3 Operations (see clause 8 below)
 - 25 — F.4 Floating to integer conversions
 - F.6 The return statement
 - F.7 Contracted expressions
 - F.8 Floating-point environment
 - F.9 Optimization
 - 30 — F.10 Mathematics `<math.h>` (see clause 8 below)

For the purpose of specifying these conformance requirements, the macros, functions, and values mentioned in the clauses listed above are understood to refer to the corresponding macros, functions, and values defined in this document for decimal floating types. Likewise, the “rounding direction mode” is understood to refer to the rounding direction mode for decimal floating-point arithmetic.

- c) It defines `__STDC_IEC_60559_DFP__` to 201ymmL.

40 NOTE Conformance to Part 2 of Technical Specification 18661 does not include all the requirements of Part 1. An implementation may conform to either or both of Parts 1 and 2.

3 Normative references

The following referenced documents are indispensable for the application of this document. Only the editions cited apply.

ISO/IEC 9899:2011, *Information technology — Programming languages, their environments and system software interfaces — Programming Language C*

ISO/IEC 9899:2011/Cor.1:2012, *Technical Corrigendum 1*

ISO/IEC/IEEE 60559:2011, *Information technology — Microprocessor Systems — Floating-point arithmetic* (with identical content to IEEE 754-2008, *IEEE Standard for Floating-Point Arithmetic*. The Institute of Electrical and Electronic Engineers, Inc., New York, 2008)

ISO/IEC TS 18661-1:yyyy, *Information technology – Programming languages, their environments and system software interfaces – Floating-point extension for C – Part 1: Binary floating-point arithmetic*

4 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 9899:2011 and ISO/IEC/IEEE 60559:2011 and the following apply.

4.1 C11

standard ISO/IEC 9899:2011, *Information technology — Programming languages, their environments and system software interfaces — Programming Language C, including Technical Corrigendum 1 (ISO/IEC 9899:2011/Cor. 1:2012)*

5 C standard conformance

5.1 Freestanding implementations

The following change to C11 + TS18661-1 expands the conformance requirements for freestanding implementations so that they might conform to this Part of Technical Specification 18661.

Change to C11 + TS18661-1:

Replace the fourth sentence of 4#6:

The strictly conforming programs that shall be accepted by a conforming freestanding implementation that defines `__STDC_IEC_60559_BFP__` may also use features in the contents of the standard headers `<fenv.h>` and `<math.h>` and the numeric conversion functions (7.22.1) of the standard header `<stdlib.h>`.

with:

The strictly conforming programs that shall be accepted by a conforming freestanding implementation that defines `__STDC_IEC_60559_BFP__` or `__STDC_IEC_60559_DFP__` may also use features in the contents of the standard headers `<fenv.h>` and `<math.h>` and the numeric conversion functions (7.22.1) of the standard header `<stdlib.h>`.

5.2 Predefined macros

The following change to C11 + TS18661-1 replaces `__STDC_DEC_FP__`, the conformance macro for decimal floating-point arithmetic specified in TR 24732, with `__STDC_IEC_60559_DFP__`, for consistency with the conformance macro for Part 1 of Technical Specification 18661. Note that an implementation may continue to define `__STDC_DEC_FP__`, so that programs that use `__STDC_DEC_FP__` may remain valid under the changes in Part 2 of Technical Specification 18661.

Change to C11 + TS18661-1:

In 6.10.8.3#1, add:

`__STDC_IEC_60559_DFP__` The integer constant `201yymmL`, intended to indicate support of decimal floating types, with decimal floating-point arithmetic according to IEC 60559.

5 5.3 Standard headers

The new identifiers added to C11 library headers by this Part of Technical Specification 18661 are defined or declared by their respective headers only if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where the appropriate header is first included. The following changes to C11 + TS18661-1 list these identifiers in each applicable library subclause.

10 Changes to C11 + TS18661-1:

In 5.2.4.2.1#1a, change:

[1a] The following identifiers are defined only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<limits.h>` is first included:

to:

15 [1a] The following identifiers are defined only if `__STDC_WANT_IEC_60559_BFP_EXT__` or `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<limits.h>` is first included:

After 5.2.4.2.2#6a, insert the paragraph:

20 [6b] The following identifiers are defined if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<float.h>` is first included:

for $N = 32, 64,$ and 128 :

<code>DECN_MANT_DIG</code>	<code>DECN_MAX</code>	<code>DECN_TRUE_MIN</code>
<code>DECN_MIN_EXP</code>	<code>DECN_EPSILON</code>	
<code>DECN_MAX_EXP</code>	<code>DECN_MIN</code>	

25 After 7.6#3a, insert the paragraph:

[3b] The following identifiers are defined or declared only if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<fenv.h>` is first included:

<code>fe_dec_getround</code>	<code>fe_dec_setround</code>
------------------------------	------------------------------

30 Change 7.12#1a from:

[1a] The following identifiers are defined or declared only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<math.h>` is first included:

```

FP_INT_UPWARD          FP_FAST_FSUB
FP_INT_DOWNWARD        FP_FAST_FSUBL
FP_INT_TOWARDZERO      FP_FAST_DSUBL
FP_INT_TONEARESTFROMZERO  FP_FAST_FMUL
FP_INT_TONEAREST      FP_FAST_FMULL
FP_LLOGB0              FP_FAST_DMULL
FP_LLOGBNAN            FP_FAST_FDIV
SNANF                  FP_FAST_FDIVL
SNAN                    FP_FAST_DDIVL
SNANL                  FP_FAST_FSQRT
FP_FAST_FADD           FP_FAST_FSQRTL
FP_FAST_FADDL          FP_FAST_DSQRTL
FP_FAST_DADDL

```

```

iseqsig                fmaxmagf          fpmal
iscanonical            fmaxmagl          dfmal
issignaling            fminmag           fsqrt
issubnormal            fminmagf          fsqrtl
iszero                 fminmagl          dsqrtl
fromfp                 nextup            totalorder
fromfpf                nextupf           totalorderf
fromfppl               nextupl           totalorderl
ufromfp                nextdown          totalordermag
ufromfpf               nextdownf         totalordermagf
ufromfppl              nextdownl         totalordermagl
fromfpfx               fadd              canonicalize
fromfpxf               faddl             canonicalizef
fromfppl               daddl             canonicalizel
ufromfpfx              fsub              getpayload
ufromfpxf              fsubl             getpayloadf
ufromfppl              dsubl             getpayloadl
roundeven              fmul              setpayload
roundevenf             fnull             setpayloadf
roundevenl             dmull             setpayloadl
llogb                  fdiv              setpayloadsig
llogbf                 fdivl             setpayloadsigf
llogbl                 ddivl             setpayloadsigl
fmaxmag                fma

```

to:

[1a] The following identifiers are defined only if `__STDC_WANT_IEC_60559_BFP_EXT__` or `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<math.h>` is first included:

```

FP_INT_UPWARD          FP_LLOGBNAN
FP_INT_DOWNWARD        iseqsig
FP_INT_TOWARDZERO      iscanonical
FP_INT_TONEARESTFROMZERO  issignaling
FP_INT_TONEAREST      issubnormal
FP_LLOGB0              iszero

```

[1b] The following identifiers are defined or declared only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<math.h>` is first included:

	SNANF	ufromp \times f	dmull
	SNAN	ufromp \times l	fdiv
	SNANL	roundeven	fdivl
5	FP_FAST_FADD	roundevenf	ddivl
	FP_FAST_FADDL	roundevenl	ffma
	FP_FAST_DADDL	llogb	ffmal
	FP_FAST_FSUB	llogbf	dfmal
	FP_FAST_FSUBL	llogbl	fsqrt
10	FP_FAST_DSUBL	fmaxmag	fsqrtl
	FP_FAST_FMUL	fmaxmagf	dsqrtl
	FP_FAST_FMULL	fmaxmagl	totalorder
	FP_FAST_DMULL	fminmag	totalorderf
	FP_FAST_FDIV	fminmagf	totalorderl
15	FP_FAST_FDIVL	fminmagl	totalordermag
	FP_FAST_DDIVL	nextup	totalordermagf
	FP_FAST_FSQRT	nextupf	totalordermagl
	FP_FAST_FSQRTL	nextupl	canonicalize
	FP_FAST_DSQRTL	nextdown	canonicalizef
20	fromfp	nextdownf	canonicalizel
	fromfpf	nextdownl	getpayload
	fromfpl	fadd	getpayloadf
	ufromfp	faddl	getpayloadl
	ufromfpf	daddl	setpayload
25	ufromfpl	fsub	setpayloadf
	fromfp \times	fsubl	setpayloadl
	fromfp \times f	dsubl	setpayloadsig
	fromfp \times l	fmul	setpayloadsigf
	ufromfp \times	fmull	setpayloadsigl

30 [1c] The following identifiers are defined or declared only if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<math.h>` is first included:

<code>_Decimal32_t</code>	<code>DEC_INFINITY</code>
<code>_Decimal64_t</code>	<code>DEC_NAN</code>

and for $N = 32, 64, 128$:

HUGE_VAL_DN	modfdN	remainderdN
SNANDN	scalbndN	copysigndN
FP_FAST_FMADN	scalblndN	nandN
acosdN	cbrtdN	nextafterdN
asindN	fabsdN	nexttowarddN
atandN	hypotdN	nexttupdN
atan2dN	powdN	nextdowndN
cosdN	sqrtdN	canonicalizedN
sindN	erfdN	fdimdN
tandN	erfcdN	fmaxdN
acoshdN	lgammadN	fmindN
asinhdN	tgammadN	fmaxmagdN
atanhdN	ceildN	fminmagdN
coshdN	floordN	fmadN
sinhdN	nearbyintdN	totalorderdN
tanhdN	rintdN	totalordermagdN
expdN	lrintdN	getpayloaddN
exp2dN	llrintdN	setpayloaddN
expm1dN	rounddN	setpayloadsigdN
frexpdN	lrounddN	quantizedN
ilogbdN	llrounddN	samequantumdN
llogbdN	truncdN	quantumdN
ldexpdN	roundevendN	llquantexpdN
logdN	fromfpdN	encodedecdN
log10dN	ufromfpdN	decodedecdN
log1pdN	fromfpxdN	encodebindN
log2dN	ufromfpxdN	decodebindN
logbdN	fmoddN	

and for $(M,N) = (32,64), (32,128), (64,128)$:

FP_FAST_DMADDDN	FP_FAST_DMFMADN	dMmuldN
FP_FAST_DMSUBDN	FP_FAST_DMSQRDND	dMdivdN
FP_FAST_DMMULDND	dMadddN	dMfmadN
FP_FAST_DMDIVDND	dMsubdN	dMsqrtdN

In 7.20#4a, change:

[4a] The following identifiers are defined only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<stdint.h>` is first included:

to:

[4a] The following identifiers are defined only if `__STDC_WANT_IEC_60559_BFP_EXT__` or `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<stdint.h>` is first included:

After 7.22#1a, insert the paragraph:

[1b] The following identifiers are declared only if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<stdlib.h>` is first included:

<code>strfromd32</code>	<code>strfromd64</code>	<code>strfromd128</code>
-------------------------	-------------------------	--------------------------

Change 7.25#1a from:

[1a] The following identifiers are defined as type-generic macros only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<tgmath.h>` is first included:

5	<code>roundeven</code>	<code>fromfpx</code>	<code>fmul</code>
	<code>llogb</code>	<code>ufromfpx</code>	<code>dmul</code>
	<code>fmaxmag</code>	<code>totalorder</code>	<code>fdiv</code>
	<code>fminmag</code>	<code>totalordermag</code>	<code>ddiv</code>
	<code>nextup</code>	<code>fadd</code>	<code>ffma</code>
10	<code>nextdown</code>	<code>dadd</code>	<code>dfma</code>
	<code>fromfp</code>	<code>fsub</code>	<code>fsqrt</code>
	<code>ufromfp</code>	<code>dsub</code>	<code>dsqrt</code>

to:

[1a] The following identifiers are defined as type-generic macros only if `__STDC_WANT_IEC_60559_BFP_EXT__` or `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<tgmath.h>` is first included:

	<code>roundeven</code>	<code>nextup</code>	<code>fromfpx</code>
	<code>llogb</code>	<code>nextdown</code>	<code>ufromfpx</code>
20	<code>fmaxmag</code>	<code>fromfp</code>	<code>totalorder</code>
	<code>fminmag</code>	<code>ufromfp</code>	<code>totalordermag</code>

[1b] The following identifiers are defined as type-generic macros only if `__STDC_WANT_IEC_60559_BFP_EXT__` is defined as a macro at the point in the source file where `<tgmath.h>` is first included:

	<code>fadd</code>	<code>fmul</code>	<code>ffma</code>
	<code>dadd</code>	<code>dmul</code>	<code>dfma</code>
	<code>fsub</code>	<code>fdiv</code>	<code>fsqrt</code>
30	<code>dsub</code>	<code>ddiv</code>	<code>dsqrt</code>

[1c] The following identifiers are defined as type-generic macros only if `__STDC_WANT_IEC_60559_DFP_EXT__` is defined as a macro at the point in the source file where `<tgmath.h>` is first included:

35	<code>d32add</code>	<code>d64add</code>	<code>quantize</code>
	<code>d32sub</code>	<code>d64sub</code>	<code>samequantum</code>
	<code>d32mul</code>	<code>d64mul</code>	<code>quantum</code>
	<code>d32div</code>	<code>d64div</code>	<code>llquantexp</code>
	<code>d32fma</code>	<code>d64fma</code>	
	<code>d32sqrt</code>	<code>d64sqrt</code>	

40 6 Decimal floating types

This Part of Technical Specification 18661 introduces three decimal floating types, designated as `_Decimal32`, `_Decimal64` and `_Decimal128`. These types support the IEC 60559 decimal formats: `decimal32`, `decimal64`, and `decimal128`.

Within the type hierarchy, decimal floating types are basic types, real types and arithmetic types.

45 This part of Technical Specification 18661 introduces the term *standard floating types* to refer to the types `float`, `double`, and `long double`, which are the floating types the C Standard requires unconditionally.

NOTE C does not specify a radix for `float`, `double`, and `long double`. An implementation can choose the representation of `float`, `double`, and `long double` to be the same as the decimal floating types. In

any case, the decimal floating types are distinct from `float`, `double`, and `long double` regardless of the representation.

NOTE This Part of Technical Specification 18661 does not define decimal complex types or decimal imaginary types. The three complex types remain as `float _Complex`, `double _Complex`, and `long double _Complex`, and the three imaginary types remain as `float _Imaginary`, `double _Imaginary`, and `long double _Imaginary`.

Changes to C11 + TS18661-1:

Change the first sentence of 6.2.5#10 from:

[10] There are three *real floating types*, designated as `float`, `double`, and `long double`.

to:

[10] There are three *standard floating types*, designated as `float`, `double`, and `long double`.

Add the following paragraphs after 6.2.5#10:

[10a] There are three *decimal floating types*, designated as `_Decimal32`, `_Decimal64`, and `_Decimal128`. *Respectively, they have the IEC 60559 formats: decimal32, decimal64, and decimal128.* Decimal floating types are real floating types.

[10b] Together, the *standard* floating types and the decimal floating types comprise the *real floating types*.

In 6.2.5#10a, attach a footnote to the wording:

they have the IEC 60559 formats: decimal32

where the footnote is:

**) IEC 60559 specifies decimal32 as a data-interchange format that does not require arithmetic support; however, `_Decimal132` is a fully supported arithmetic type.*

Add the following to 6.4.1 Keywords:

keyword:

`_Decimal32`
`_Decimal64`
`_Decimal128`

Add the following to 6.7.2 Type specifiers:

type-specifier:

`_Decimal32`
`_Decimal64`
`_Decimal128`

Add the following bullets in 6.7.2#2 Constraints:

- `_Decimal32`
- `_Decimal64`
- `_Decimal128`

Add the following after 6.7.2#3:

[3a] The type specifiers `_Decimal32`, `_Decimal64`, and `_Decimal128` shall not be used if the implementation does not support decimal floating types (see 6.10.8.3).

Add the following after 6.5#8:

- 5 [8a] Expressions involving decimal floating types are evaluated according to the semantics of IEC 60559, including production of results with the preferred quantum exponent as specified in IEC 60559.

7 Characteristics of decimal floating types <float.h>

10 IEC 60559 defines a general model for floating-point data, specifies formats (both binary and decimal) for the data, and defines encodings for the formats.

The three decimal floating types correspond to decimal formats defined in IEC 60559 as follows:

- `_Decimal32` is a *decimal32* format, which is encoded in 32 bits
- `_Decimal64` is a *decimal64* format, which is encoded in 64 bits
- `_Decimal128` is a *decimal128* format, which is encoded in 128 bits

- 15 The value of a finite number is given by $(-1)^{\text{sign}} \times \text{significand} \times 10^{\text{exponent}}$. Refer to IEC 60559 for details of the format.

These formats are characterized by the length of the *significand* and the maximum exponent. Note that, for decimal IEC 60559 decimal formats, trailing zeros in the *significand* are significant; i.e., 1.0 is equal to but can be distinguished from 1.00. Table 1 below shows these characteristics by type:

20 **Table 1 – Format characteristics**

Type	<code>_Decimal32</code>	<code>_Decimal64</code>	<code>_Decimal128</code>
<i>Significand</i> length in digits	7	16	34
Maximum Exponent (E_{max})	97	385	6145
Minimum Exponent (E_{min})	-94	-382	-6142

25 The maximum and minimum exponents in Table 1 are for floating-point numbers expressed with significands less than 1, as in the C11 model (5.2.4.2.2). They differ (by 1) from the maximum and minimum exponents in the IEC 60559 standard, where normalized floating-point numbers are expressed with one significant digit to the left of the radix point.

If the macro `__STDC_WANT_IEC_60559_DFP_EXT__` is defined at the point in the source file where the header `<float.h>` is first included, the header `<float.h>` shall define several macros that expand to various limits and parameters of the decimal floating types. The names and meaning of these macros are similar to the corresponding macros for *standard* floating types.

30 **Changes to C11 + TS18661-1:**

In 5.2.4.2.2#6, append the sentence:

Decimal floating-point operations have stricter requirements.

In 5.2.4.2.2#7, change:

All except `CR_DECIMAL_DIG` (F.5), `DECIMAL_DIG`, `FLT_EVAL_METHOD`, `FLT_RADIX`, and `FLT_ROUNDS` have separate names for all three floating-point types. The floating-point model representation is provided for all values except `FLT_EVAL_METHOD` and `FLT_ROUNDS`.

to:

All except `DECIMAL_DIG`, `CR_DECIMAL_DIG` (F.5), `DEC_EVAL_METHOD`, `FLT_EVAL_METHOD`, `FLT_RADIX`, and `FLT_ROUNDS` have separate names for all real floating types. The floating-point model representation is provided for all values except `DEC_EVAL_METHOD`, `FLT_EVAL_METHOD`, and `FLT_ROUNDS`.

After 5.2.4.2.2#7, insert the paragraph:

[7a] The remainder of this subclause specifies characteristics of standard floating types.

Add the following after 5.2.4.2.2:

5.2.4.2.2a Characteristics of decimal floating types in `<float.h>`

[1] This subclause specifies macros in `<float.h>` that provide characteristics of decimal floating types in terms of the model presented in 5.2.4.2.2. The prefixes `DEC32_`, `DEC64_`, and `DEC128_` denote the types `_Decimal32`, `_Decimal64`, and `_Decimal128` respectively.

[2] Except for assignment and cast (which remove all extra range and precision), the values of the decimal floating operands and results of expressions that are subject to the usual arithmetic conversions, and the values of floating constants of decimal floating type, are evaluated to a format whose range and precision may be greater than required by the type. The use of evaluation formats is characterized by the implementation-defined value of `DEC_EVAL_METHOD`: [ISSUE: wording here is a clarification of the analogous specification in 5.2.4.2.2#9 – how to fix 5.2.4.2.2?]

–1 indeterminate;

0 evaluate all operations and constants just to the range and precision of the type;

1 evaluate operations and constants of type `_Decimal32` and `_Decimal64` to the range and precision of the `_Decimal64` type, evaluate `_Decimal128` operations and constants to the range and precision of the `_Decimal128` type;

2 evaluate all operations and constants to the range and precision of the `_Decimal128` type.

[3] The integer values given in the following lists shall be replaced by constant expressions suitable for use in `#if` preprocessing directives:

— radix of exponent representation, $b(=10)$

For the standard floating types, this value is implementation-defined and is specified by the macro `FLT_RADIX`. For the decimal floating types there is no corresponding macro, since the value 10 is an inherent property of the types. Wherever `FLT_RADIX` appears in a description of a function that has versions that operate on decimal floating types, it is noted that for the decimal floating-point versions the value used is implicitly 10, rather than `FLT_RADIX`.

— number of digits in the coefficient

<code>DEC32_MANT_DIG</code>	7
<code>DEC64_MANT_DIG</code>	16
<code>DEC128_MANT_DIG</code>	34

[6] For binary floating-point **arithmetic** following IEC 60559, representations in the model described in 5.2.4.2.2 that have the same numerical value are indistinguishable in the arithmetic. However, for decimal floating-point **arithmetic**, representations that have the same numerical value but different quantum exponents, e.g., (1, 10, -1) representing 1.0 and (1, 100, -2) representing 1.00 are distinguishable. To facilitate exact fixed-point calculation, **operation results that are of decimal floating type** have a *preferred quantum exponent*, as specified in IEC 60559, which is determined by the quantum exponents of the operands if they have decimal floating types (or by specific rules for conversions from other types). Table 3 below gives rules for determining preferred quantum exponents for results of IEC 60559 operations, and for other operations specified in this document. When exact, these operations produce a result with their preferred quantum exponent, or as close to it as possible within the limitations of the type. When inexact, these operations produce a result with the least possible quantum exponent. For example, the preferred quantum exponent for addition is the minimum of the quantum exponents of the operands. Hence (1, 123, -2) + (1, 4000, -3) = (1, 5230, -3) or $1.23 + 4.000 = 5.230$.

[7] Table 3 shows, for each operation, how the preferred quantum exponents of the operands, $Q(\mathbf{x})$, $Q(\mathbf{y})$, etc., determine the preferred quantum exponent of the operation result.

Table 3 – Preferred quantum exponents

Decimal operation (shown without suffixes)	Preferred quantum exponent of result
roundeven, round, trunc, ceil, floor, rint, nearbyint	$\max(Q(\mathbf{x}), 0)$
nextup, nextdown, nextafter, nexttoward remainder	least possible
fmin, fmax, fminmag, fmaxmag	$Q(\mathbf{x})$ if \mathbf{x} gives the result, $Q(\mathbf{y})$ if \mathbf{y} gives the result
scalbn, scalbln	$Q(\mathbf{x}) + n$
ldexp	$Q(\mathbf{x}) + \text{exp}$
logb	0
+, d32add, d64add	$\min(Q(\mathbf{x}), Q(\mathbf{y}))$
-, d32sub, d64sub	$\min(Q(\mathbf{x}), Q(\mathbf{y}))$
*, d32mul, d64mul	$Q(\mathbf{x}) + Q(\mathbf{y})$
/, d32div, d64div	$Q(\mathbf{x}) - Q(\mathbf{y})$
sqrt, d32sqrt, d64sqrt	$\text{floor}(Q(\mathbf{x})/2)$
fma, d32fma, d64fma	$\min(Q(\mathbf{x}) + Q(\mathbf{y}), Q(\mathbf{z}))$
conversion from integer type	0
exact conversion from non-decimal floating type	0
inexact conversion from non-decimal floating type	least possible
conversion between decimal floating types	$Q(\mathbf{x})$
cx returned by canonicalize	$Q(\mathbf{x})$
strtod, wcstod, scanf, floating constants of decimal floating type	see 7.22.1.3a
-(x)	$Q(\mathbf{x})$
fabs	$Q(\mathbf{x})$
copysign	$Q(\mathbf{x})$
quantize	$Q(\mathbf{y})$
quantum	$Q(\mathbf{x})$
encptr returned by encodedec, encodebin	$Q(\mathbf{xptr})$
xptr returned by decodedec, decodebin	$Q(\mathbf{encptr})$
fmod	$\min(Q(\mathbf{x}), Q(\mathbf{y}))$
fdim	$\min(Q(\mathbf{x}), Q(\mathbf{y}))$ if $\mathbf{x} > \mathbf{y}$, 0 if $\mathbf{x} \leq \mathbf{y}$
cbrt	$\text{floor}(Q(\mathbf{x})/3)$
hypot	$\min(Q(\mathbf{x}), Q(\mathbf{y}))$
pow	$\text{floor}(\mathbf{y} \times Q(\mathbf{x}))$
modf	$Q(\text{value})$
*iptr returned by modf	$\max(Q(\text{value}), 0)$
frexp	$Q(\text{value})$ if $\text{value} = 0$, - (length of coefficient of value) otherwise
*res returned by setpayload, setpayloadsig	0 if $\mathbf{p1}$ does not represent a valid payload, not applicable otherwise (NaN returned)
getpayload	0 if $*\mathbf{x}$ is a NaN, unspecified otherwise
transcendental functions	0

8 Operation binding

Table 1 and subsequent text in F.3 as specified in Part 1 of Technical Specification 18661, with the further change below, show how the C decimal operations specified in this document, Part 2 of Technical Specification 18661, provide the operations required by IEC 60559 for decimal floating-point arithmetic.

Change to C11 + TS18661-1:

After F.3#10 (see Part 1 of Technical Specification 18661), append the following:

[11] Decimal versions of the C `remquo` function are not provided. (The C decimal `remainder` functions provide the remainder operation defined by IEC 60559.)

[12] The C `quantizedN` functions (7.12.11a.1) provide the quantize operation defined in IEC 60559 for decimal floating-point arithmetic.

[13] The binding for the `convertFormat` operation applies to all conversions among IEC 60559 formats. Therefore, for implementations that conform to Annex F, conversions between decimal floating types and standard floating types with IEC 60559 formats are correctly rounded and raise floating-point exceptions as specified in IEC 60559.

[14] IEC 60559 specifies the `convertFromHexCharacter` and `convertToHexCharacter` operations only for binary floating-point arithmetic.

[15] The C integer constant `10` provides the radix operation defined in IEC 60559 for decimal floating-point arithmetic.

[16] The C `samequantumdN` functions (7.12.11a.2) provide the `sameQuantum` operation defined in IEC 60559 for decimal floating-point arithmetic.

[17] The C `fe_dec_getround` (7.6.3.3) and `fe_dec_setround` (7.6.3.4) functions provide the `getDecimalRoundingDirection` and `setDecimalRoundingDirection` operations defined in IEC 60559 for decimal floating-point arithmetic. The macros (7.6) `FE_DEC_DOWNWARD`, `FE_DEC_TONEAREST`, `FE_DEC_TONEARESTFROMZERO`, `FE_DEC_TOWARDZERO`, and `FE_DEC_UPWARD`, which are used in conjunction with the `fe_dec_getround` and `fe_dec_setround` functions, represent the IEC 60559 rounding-direction attributes `roundTowardNegative`, `roundTiesToEven`, `roundTiesToAway`, `roundTowardZero`, and `roundTowardPositive`, respectively.

[18] The C `quantumdN` (7.12.11a.3) and `llquantexpdN` (7.12.11a.4) functions compute the `quantum` and the (quantum) exponent q defined in IEC 60559 for decimal numbers viewed as having integer significands.

[19] The C `encodedecdN` (7.12.11b.1) and `decodedecdN` (7.12.11b.2) functions provide the `encodeDecimal` and `decodeDecimal` operations defined in IEC 60559 for decimal floating-point arithmetic.

[20] The C `encodebindN` (7.12.11b.3) and `decodebindN` (7.12.11b.4) functions provide the `encodeBinary` and `decodeBinary` operations defined in IEC 60559 for decimal floating-point arithmetic.

9 Conversions

9.1 Conversions between decimal floating and integer types

For conversions between real floating and integer types, C11 6.3.1.4 leaves the behavior undefined if the conversion result cannot be represented (Annex F.3 and F.4 define the behavior). To help writing portable code, this Part of Technical Specification 18661 provides defined behavior for decimal floating types.

Changes to C11 + TS18661-1:

Change the first sentence of 6.3.1.4#1 from:

[1] When a finite value of real floating type is converted to an integer type ...

to:

5 [1] When a finite value of **standard** floating type is converted to an integer type ...

Add the following paragraph after 6.3.1.4#1:

10 [1a] When a finite value of decimal floating type is converted to an integer type other than `_Bool`, the fractional part is discarded (i.e., the value is truncated toward zero). If the value of the integral part cannot be represented by the integer type, the “invalid” floating-point exception shall be raised and the result of the conversion is unspecified.

Change the first sentence of 6.3.1.4#2 from:

[2] When a value of integer type is converted to a real floating type, ...

to:

[2] When a value of integer type is converted to a **standard** floating type, ...

15 Add the following paragraph after 6.3.1.4#2:

[2a] When a value of integer type is converted to a decimal floating type, if the value being converted can be represented exactly in the new type, it is unchanged. If the value being converted cannot be represented exactly, the result shall be correctly rounded with exceptions raised as specified in IEC 60559.

20 **9.2 Conversions among decimal floating types, and between decimal floating and **standard** floating types**

25 In the following change to C11 + TS18661-1, the specification of conversions among decimal floating types is similar to the existing one for `float`, `double`, and `long double`, except that when the result cannot be represented exactly, the **specification requires** correct rounding. It also **requires correct rounding** for conversions from **standard** to decimal floating types. **The specification in Annex F requires** correct rounding for conversions from decimal to **the standard** floating types **that conform** to IEC 60559.

Change to C11 + TS18661-1:

Replace 6.3.1.5#1:

30 [1] When a value of real floating type is converted to a real floating type, if the value being converted can be represented exactly in the new type, it is unchanged. If the value being converted is in the range of values that can be represented but cannot be represented exactly, the result is either the nearest higher or nearest lower representable value, chosen in an implementation-defined manner. If the value being converted is outside the range of values that can be represented, the behavior is undefined. Results of some implicit conversions (6.3.1.8, 6.8.6.4) may be represented in greater
35 range and precision than that required by the new type.

with:

[1] When a value of real floating type is converted to a real floating type, if the value being converted can be represented exactly in the new type, it is unchanged.

[2] When a value of real floating type is converted to a **standard** floating type, if the value being converted is in the range of values that can be represented but cannot be represented exactly, the result is either the nearest higher or nearest lower representable value, chosen in an implementation-defined manner. If the value being converted is outside the range of values that can be represented, the behavior is undefined.

[3] When a value of real floating type is converted to a decimal floating type, if the value being converted cannot be represented exactly, the result is correctly rounded with exceptions raised as specified in IEC 60559

[4] Results of some implicit conversions (6.3.1.8, 6.8.6.4) may be represented in greater range and precision than that required by the new type.

9.3 Conversions between decimal floating and complex types

This is covered by C11 6.3.1.7.

9.4 Usual arithmetic conversions

In an application that is written using decimal **floating-point** arithmetic, mixed operations between decimal and other real types are likely to occur only when interfacing with other languages, calling existing libraries written for binary floating-point arithmetic, or accessing existing data. Determining the common type for mixed operations is difficult because ranges overlap; therefore, mixed mode operations are not allowed and the programmer must use explicit casts. Implicit conversions are allowed only for simple assignment, **return** statement, and in argument passing involving prototyped functions.

Change to C11 + TS18661-1:

Insert the following in 6.3.1.8#1, after "This pattern is called the *usual arithmetic conversions*:"

If one operand **has** decimal floating type, all other operands shall not **have standard** floating, complex, or imaginary type.

First, if **the type of** either operand is `_Decimal128`, the other operand is converted to `_Decimal128`.

Otherwise, if **the type of** either operand is `_Decimal64`, the other operand is converted to `_Decimal64`.

Otherwise, if **the type of** either operand is `_Decimal32`, the other operand is converted to `_Decimal32`.

If there are no decimal floating types in the operands:

First, if the corresponding real type of either operand is `long double`, the other operand is converted, without ... <the rest of 6.3.1.8#1 remains the same>

9.5 Default argument promotion

There is no default argument promotion specified for the decimal floating types. Default argument promotion covered in C11 6.5.2.2 [6] and [7] remains unchanged, and applies to **standard** floating types only.

10 Constants

New suffixes are added to denote decimal floating constants: **df** and **DF** for `_Decimal32`, **dd** and **DD** for `_Decimal64`, and **d1** and **DL** for `_Decimal128`.

This specification does not carry forward two features introduced in TR 24732: the `FLOAT_CONST_DECIMAL64` pragma and the **d** and **D** suffixes for floating constants. The pragma changed the

interpretation of unsuffixed floating constants between `double` and `_Decimal64`. The suffixes provided a way to designate `double` floating constants so that the pragma would not affect them. The pragma is not included because of its potential for inadvertently reinterpreting constants. Without the pragma, the suffixes are no longer needed. Also, significant implementations use the `d` and `D` suffixes for other purposes.

5 Changes to C11 + TS18661-1:

Change *floating-suffix* in 6.4.4.2 from:

floating-suffix: one of
`f l F L`

to:

10 *floating-suffix*: one of
`f l F L df dd dl DF DD DL`

Add the following after 6.4.4.2#2:

Constraints

[2a] A *floating-suffix* `df`, `dd`, `dl`, `DF`, `DD`, or `DL` shall not be used in a *hexadecimal-floating-constant*.

15 Add the following paragraph after 6.4.4.2#4:

[4a] If a floating constant is suffixed by `df` or `DF`, it has type `_Decimal32`. If suffixed by `dd` or `DD`, it has type `_Decimal64`. If suffixed by `dl` or `DL`, it has type `_Decimal128`.

Add the following paragraph after 6.4.4.2#5:

20 [5a] *Floating constants* of decimal floating *type* that have the same numerical value but different quantum exponents have distinguishable internal representations. The quantum exponent is specified to be the same as for the corresponding `strtod32`, `strtod64`, or `strtod128` function for the same numeric string.

11 Arithmetic operations

11.1 Operators

25 The operators *Add* (C11 6.5.6), *Subtract* (C11 6.5.6), *Multiply* (C11 6.5.5), *Divide* (C11 6.5.5), *Relational operators* (C11 6.5.8), *Equality operators* (C11 6.5.9), *Unary Arithmetic operators* (C11 6.5.3.3), and *Compound Assignment operators* (C11 6.5.16.2) when applied to decimal floating type operands shall follow the semantics as defined in IEC 60559.

Changes to C11 + TS18661-1:

30 Add the following after 6.5.5#2:

[2a] If either operand has decimal floating type, the other operand shall not have *standard* floating type, complex type, nor imaginary type.

Add the following after 6.5.6#3:

35 [3a] If either operand has decimal floating type, the other operand shall not have *standard* floating type, complex type, nor imaginary type.

Add the following after 6.5.8#2:

[2a] If either operand has decimal floating type, the other operand shall not have **standard** floating type.

Add the following after 6.5.9#2:

[2a] If either operand has decimal floating type, the other operand shall not have **standard** floating type, complex type, nor imaginary type.

Add the following bullet to 6.5.15#3:

- one operand has decimal floating type, and the other has arithmetic type other than **standard** floating type, complex type, **and** imaginary type;

Add the following after 6.5.16.2#2:

[2a] If either operand has decimal floating type, the other operand shall not have **standard** floating type, complex type, nor imaginary type.

11.2 Functions

The headers and library supply a number of functions and **function-like** macros that support decimal floating-point **arithmetic** with the semantics specified in IEC 60559, including producing results with the preferred quantum exponent where appropriate. That support is provided by the following:

From C11 `<math.h>`, with changes in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

`sqrt`, `fma`, `fabs`, `fmax`, `fmin`, `ceil`, `floor`, `trunc`, `round`, `rint`, `lround`, `llround`, `ldexp`, `frexp`, `ilogb`, `logb`, `scalbn`, `scalbln`, `copysign`, `remainder`, `isnan`, `isinf`, `isfinite`, `isnormal`, `signbit`, `fpclassify`, `isunordered`, `isgreater`, `isgreaterequal`, `isless`, `islessequal` and `islessgreater`.

From the `<math.h>` extensions specified in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

`roundeven`, `nextup`, `nextdown`, `fminmag`, `fmaxmag`, `llogb`, `fadd`, `faddl`, `daddl`, `fsub`, `fsubl`, `dsubl`, `fmul`, `fmull`, `dmull`, `fdiv`, `fdivl`, `ddivl`, `fsqrt`, `fsqrtl`, `dsqrtl`, `ffma`, `ffmal`, `dfmal`, `fromfp`, `ufromfp`, `fromfpx`, `ufromfpx`, `canonicalize`, `iseqsig`, `issignaling`, `issubnormal`, `iscanonical`, `iszero`, `totalorder`, `totalordermag`, `getpayload`, `setpayload`, and `setpayloadsig`.

The `<math.h>` extensions specified below in 12.4 for the decimal-specific functions:

`quantizedN`, `samequantumdN`, `quantumdN`, `llquantexpdN`, `encodedecdN`, `decodedecdN`, `encodebindN`, and `decodebindN`.

From C11 `<fenv.h>`, facilities dealing with decimal context:

`feraiseexcept`, `feclearexcept`, `fetestexcept`, `fesetexceptflag`, `fegetexceptflag`, `fesetenv`, `fegetenv`, `feupdateenv`, and `feholdexcept`.

From the `<fenv.h>` extensions specified in Part 1 of Technical Specification 18661, facilities dealing with decimal context:

`fetestexceptflag`, `fesetexcept`, `fegetmode`, and `fesetmode`.

From the `<fenv.h>` extensions specified in this Part of Technical Specification 18661, facilities dealing with decimal context:

`fe_dec_getround` and `fe_dec_setround`.

From `<stdio.h>`, decimal floating-point modified format specifiers for:

- 5 The `printf/scanf` family of functions.

From `<stdlib.h>` and `<wchar.h>`, with changes in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

`strtod` and `wctod`.

- 10 From the `<stdlib.h>` extensions specified in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

`strfromd`.

From `<wchar.h>`, decimal floating-point modified format specifiers for:

The `wprintf/wscanf` family of functions.

11.3 Conversions

- 15 Conversions between different floating types and conversions to and from integer types are covered in clause 9.

11.4 Expression transformations

The following changes to C11 + TS18661-1 alert implementors that some expression transformations must be avoided in order to preserve the quantum exponent (7) of decimal floating-point numbers.

- 20 **Changes to C11 + TS18661-1:**

In F.9.2, insert before paragraph #1:

[0] Valid expression transformations must preserve numerical values.

In F.9.2, insert at the beginning of paragraph #1:

[1] The equivalences noted below apply to expressions of standard floating types.

- 25 In F.9.2, append:

[2] For expressions of decimal floating types, transformations must preserve quantum exponents, as well as numerical values (5.2.4.2.2a).

[3] EXAMPLE $1. \times x \rightarrow x$ is valid for decimal floating-point expressions x , but $1.0 \times x \rightarrow x$ is not:

$$1. \times 12.34 = (1, 1, 0) \times (1, 1234, -2) = (1, 1234, -2) = 12.34$$

- 30 $1.0 \times 12.34 = (1, 10, -1) \times (1, 1234, -2) = (1, 12340, -3) = 12.340$

The results are numerically equal, but have different quantum exponents, hence have different values.

12 Library

12.1 Standard headers

The functions, macros, and types declared or defined in Clause 12 and its subclauses are only declared or defined by their respective headers if the macro `__STDC_WANT_IEC_60559_DFP_EXT__` is defined at the point in the source file where the appropriate header is first included.

12.2 Decimal floating-point environment in `<fenv.h>`

The floating-point environment specified in C11 7.6 applies to operations for both standard floating types and decimal floating types. This is to implement the *context* defined in IEC 60559. The existing general C11 specification gives flexibility to an implementation on which part of the environment is accessible to programs. Annex F requires support for all the (binary) rounding directions and exception flags (for operations for standard floating types). This document requires support for all the rounding directions and exceptions flags for operations for decimal floating types.

IEC 60559 requires separate rounding modes for binary and decimal floating-point operations. This document requires a separate rounding mode for decimal floating-point operations if the standard floating types are not decimal, and it allows the implementation to define whether the rounding modes are separate or the same if the standard floating types are decimal.

Table 4 – Rounding mode macros

For decimal floating types	For standard floating types	IEC 60559
<code>FE_DEC_TOWARDZERO</code>	<code>FE_TOWARDZERO</code>	Toward zero
<code>FE_DEC_TONEAREST</code>	<code>FE_TONEAREST</code>	To nearest, ties to even
<code>FE_DEC_UPWARD</code>	<code>FE_UPWARD</code>	Toward plus infinity
<code>FE_DEC_DOWNWARD</code>	<code>FE_DOWNWARD</code>	Toward minus infinity
<code>FE_DEC_TONEARESTFROMZERO</code>	n/a	To nearest, ties away from zero

Changes to C11 + TS18661-1:

Add the following after 7.6#6:

[6a] Decimal floating-point operations and IEC 60559 binary floating-point operations (Annex F) access the same floating-point exception status flags.

In 7.6#8, delete the sentence (and retain footnote 211 at the end of the paragraph):

The defined macros expand to integer constant expressions whose values are distinct nonnegative values.

Add the following after 7.6#8:

[8a] Each of the macros

```
FE_DEC_DOWNWARD
FE_DEC_TONEAREST
FE_DEC_TONEARESTFROMZERO
FE_DEC_TOWARDZERO
FE_DEC_UPWARD
```

7 is defined for use with the `fe_dec_getround` and `fe_dec_setround` functions for getting and setting the dynamic rounding direction mode, and with the `FENV_DEC_ROUND` rounding control pragma (7.6.1b) for specifying a constant rounding direction, for decimal floating-point operations. The decimal rounding direction affects all (inexact) operations that produce a result of decimal floating

type and all operations that produce an integer or character sequence result and have an operand of decimal floating type, unless stated otherwise. The macros expand to integer constant expressions whose values are distinct nonnegative values.

5 [8b] During translation, constant rounding direction modes for decimal floating-point arithmetic are in effect where specified. Elsewhere, during translation the decimal rounding direction mode is **FE_DEC_TONEAREST**.

[8c] At program startup the dynamic rounding direction mode for decimal floating-point arithmetic is initialized to **FE_DEC_TONEAREST**.

In 7.6.1a#2, change the first sentence from:

10 The **FENV_ROUND** pragma provides a means to specify a constant rounding direction for floating-point operations within a translation unit or compound statement.

to:

The **FENV_ROUND** pragma provides a means to specify a constant rounding direction for floating-point operations for standard floating types within a translation unit or compound statement.

15 In 7.6.1a#3, change the first sentence from:

direction shall be one of the rounding direction macro names defined in 7.6, or **FE_DYNAMIC**.

to:

direction shall be one of the names of the supported rounding direction macros for operations for standard floating types (7.6), or **FE_DYNAMIC**.

20 In 7.6.1a#4, replace the first sentence:

Within the scope of an **FENV_ROUND** directive establishing a mode other than **FE_DYNAMIC**, all floating-point operators, ...

with:

25 The **FENV_ROUND** directive affects operations for standard floating types. Within the scope of an **FENV_ROUND** directive establishing a mode other than **FE_DYNAMIC**, floating-point operators, ...

In 7.6.1a#4, change the last sentence from:

Floating constants (6.4.4.2) that occur in the scope of a constant rounding mode shall be interpreted according to that mode.

to:

30 Floating constants (6.4.4.2) of a standard floating type that occur in the scope of a constant rounding mode shall be interpreted according to that mode.

After 7.6.1a, insert:

7.6.1b Decimal rounding control pragma

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <fenv.h>
#pragma STDC FENV_DEC_ROUND dec-direction
```

Description

[2] The `FENV_DEC_ROUND` pragma is a decimal floating-point analogue of the `FENV_ROUND` pragma. It affects operations only for decimal floating types. If `FLT_RADIX` is not 10, the `FENV_DEC_ROUND` pragma affects operations only for decimal floating types; otherwise, if `FLT_RADIX` is 10, whether the `FENV_ROUND` and `FENV_DEC_ROUND` pragmas alter the rounding direction of both standard and decimal floating-point operations is implementation-defined. *dec-direction* shall be one of the decimal rounding direction macro names (`FE_DEC_DOWNWARD`, `FE_DEC_TONEAREST`, `FE_DEC_TONEARESTFROMZERO`, `FE_DEC_TOWARDZERO`, and `FE_DEC_UPWARD`) defined in 7.6, to specify a constant rounding mode, or `FE_DEC_DYNAMIC`, to specify dynamic rounding. The corresponding dynamic rounding mode can be established by a call to `fe_dec_setround`.

Add the following after 7.6.3.2:

7.6.3.3 The `fe_dec_getround` function

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <fenv.h>
int fe_dec_getround(void);
```

Description

[2] The `fe_dec_getround` function gets the current value of the dynamic rounding direction mode for decimal floating-point operations.

Returns

[3] The `fe_dec_getround` function returns the value of the rounding direction macro representing the current dynamic rounding direction for decimal floating-point operations, or a negative value if there is no such rounding macro or the current rounding direction is not determinable.

7.6.3.4 The `fe_dec_setround` function

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <fenv.h>
int fe_dec_setround(int round);
```

Description

[2] The `fe_dec_setround` function sets the dynamic rounding direction mode for decimal floating-point operations to be the rounding direction represented by its argument `round`. If the argument is not equal to the value of a decimal rounding direction macro, the rounding direction is not changed.

[3] If `FLT_RADIX` is not 10, the rounding direction altered by the `fesetround` function is independent of the rounding direction altered by the `fe_dec_setround` function; otherwise if `FLT_RADIX` is 10, whether the `fesetround` and `fe_dec_setround` functions alter the rounding direction of both standard and decimal floating-point operations is implementation-defined.

5 Returns

[4] The `fe_dec_setround` function returns a zero value if and only if the argument is equal to a decimal rounding direction macro (that is, if and only if the dynamic rounding direction mode for decimal floating-point operations was set to the requested rounding direction).

12.3 Decimal mathematics in `<math.h>`

10 The list of types, macros, and functions specified in the mathematics library is extended to handle decimal floating types. These include functions specified in C11 (7.12.4, 7.12.5, 7.12.6, 7.12.7, 7.12.8, 7.12.9, 7.12.10, 7.12.11, 7.12.12, and 7.12.13) and in Part 1 of Technical Specification 18661 (14.1, 14.2, 14.3, 14.4, 14.5, 14.8, 14.9, and 14.0). With the exception of the decimal floating-point functions listed in 11.2, which have accuracy as specified in IEC 60559, the accuracy of decimal floating-point results is implementation-defined.

15 The implementation may state that the accuracy is unknown. All classification macros specified in C11 (7.12.3) and in Part 1 of Technical Specification 18661 (14.7) are also extended to handle decimal floating types. The same applies to all comparison macros specified in C11 (7.12.14) and in Part 1 of Technical Specification 18661 (14.6).

20 The names of the functions are derived by adding suffixes `d32`, `d64`, and `d128` to the `double` version of the function name, except for the functions that round result to narrower type (7.12.13a).

Changes to C11 + TS18661-1:

Add after 7.12#2:

[2a] The types

```
25     _Decimal32_t
       _Decimal64_t
```

are decimal floating types at least as wide as `_Decimal32` and `_Decimal64`, respectively, and such that `_Decimal64_t` is at least as wide as `_Decimal32_t`. If `DEC_EVAL_METHOD` equals 0, `_Decimal32_t` and `_Decimal64_t` are `_Decimal32` and `_Decimal64`, respectively;

30 if `DEC_EVAL_METHOD` equals 1, they are both `_Decimal64`; if `DEC_EVAL_METHOD` equals 2, they are both `_Decimal128`; and for other values of `DEC_EVAL_METHOD`, they are otherwise implementation-defined.

Add after 7.12#3:

[3a] The macro

```
35     HUGE_VAL_D64
```

expands to a constant expression of type `_Decimal64` representing positive infinity. The macros

```
     HUGE_VAL_D32
     HUGE_VAL_D128
```

40 are respectively `_Decimal32` and `_Decimal128` analogues of `HUGE_VAL_D64`.

Add after 7.12#4:

[4a] The macro

```
DEC_INFINITY
```

expands to a constant expression of type `_Decimal32` representing positive infinity.

5 Add after 7.12#5, before 7.12#5a (see Part 1 of Technical Specification 18661):

[5a-] The macro

```
DEC_NAN
```

expands to a constant expression of type `_Decimal32` representing a quiet NaN.

Add after 7.12#5a:

10 [5b] The **decimal** signaling NaN macros

```
SNAND32
SNAND64
SNAND128
```

15 each expands to a constant expression of the respective decimal floating type representing a signaling NaN. If a signaling NaN macro is used for initializing an object of the same type that has static or thread-local storage duration, the object is initialized with a signaling NaN value.

Add after 7.12#7a:

[7b] The macros

```
FP_FAST_FMAD32
FP_FAST_FMAD64
FP_FAST_FMAD128
```

are, respectively, `_Decimal32`, `_Decimal64`, and `_Decimal128` analogues of `FP_FAST_FMA`.

25 [7c] The macros

```
FP_FAST_D32ADDD64
FP_FAST_D32ADDD128
FP_FAST_D64ADDD128
FP_FAST_D32SUBD64
FP_FAST_D32SUBD128
FP_FAST_D64SUBD128
FP_FAST_D32MULD64
FP_FAST_D32MULD128
FP_FAST_D64MULD128
FP_FAST_D32DIVD64
FP_FAST_D32DIVD128
FP_FAST_D64DIVD128
FP_FAST_D32FMAD64
FP_FAST_D32FMAD128
FP_FAST_D64FMAD128
FP_FAST_D32SQRTD64
FP_FAST_D32SQRTD128
FP_FAST_D64SQRTD128
```

are decimal analogues of `FP_FAST_FADD`, `FP_FAST_FADDL`, `FP_FAST_DADDL`, etc.

Add the following list of function prototypes to the synopsis of the respective subclauses:

7.12.4 Trigonometric functions

```

5      _Decimal64 acosd64(_Decimal64 x);
      _Decimal32 acosd32(_Decimal32 x);
      _Decimal128 acosd128(_Decimal128 x);

      _Decimal64 asind64(_Decimal64 x);
10     _Decimal32 asind32(_Decimal32 x);
      _Decimal128 asind128(_Decimal128 x);

      _Decimal64 atand64(_Decimal64 x);
      _Decimal32 atand32(_Decimal32 x);
15     _Decimal128 atand128(_Decimal128 x);

      _Decimal64 atan2d64(_Decimal64 y, _Decimal64 x);
      _Decimal32 atan2d32(_Decimal32 y, _Decimal32 x);
20     _Decimal128 atan2d128(_Decimal128 y, _Decimal128 x);

      _Decimal64 cosd64(_Decimal64 x);
      _Decimal32 cosd32(_Decimal32 x);
      _Decimal128 cosd128(_Decimal128 x);

25     _Decimal64 sind64(_Decimal64 x);
      _Decimal32 sind32(_Decimal32 x);
      _Decimal128 sind128(_Decimal128 x);

      _Decimal64 tand64(_Decimal64 x);
30     _Decimal32 tand32(_Decimal32 x);
      _Decimal128 tand128(_Decimal128 x);

```

7.12.5 Hyperbolic functions

```

      _Decimal64 acoshd64(_Decimal64 x);
      _Decimal32 acoshd32(_Decimal32 x);
35     _Decimal128 acoshd128(_Decimal128 x);

      _Decimal64 asinhd64(_Decimal64 x);
      _Decimal32 asinhd32(_Decimal32 x);
40     _Decimal128 asinhd128(_Decimal128 x);

      _Decimal64 atanh64(_Decimal64 x);
      _Decimal32 atanh32(_Decimal32 x);
      _Decimal128 atanh128(_Decimal128 x);

45     _Decimal64 coshd64(_Decimal64 x);
      _Decimal32 coshd32(_Decimal32 x);
      _Decimal128 coshd128(_Decimal128 x);

      _Decimal64 sinhd64(_Decimal64 x);
50     _Decimal32 sinhd32(_Decimal32 x);
      _Decimal128 sinhd128(_Decimal128 x);

      _Decimal64 tanhd64(_Decimal64 x);
      _Decimal32 tanhd32(_Decimal32 x);
55     _Decimal128 tanhd128(_Decimal128 x);

```

7.12.6 Exponential and logarithmic functions

```

    _Decimal64 expd64(_Decimal64 x);
    _Decimal32 expd32(_Decimal32 x);
    _Decimal128 expd128(_Decimal128 x);
5
    _Decimal64 exp2d64(_Decimal64 x);
    _Decimal32 exp2d32(_Decimal32 x);
    _Decimal128 exp2d128(_Decimal128 x);

    _Decimal64 expm1d64(_Decimal64 x);
    _Decimal32 expm1d32(_Decimal32 x);
    _Decimal128 expm1d128(_Decimal128 x);

    _Decimal64 frexp64(_Decimal64 value, int *exp);
    _Decimal32 frexp32(_Decimal32 value, int *exp);
    _Decimal128 frexp128(_Decimal128 value, int *exp);
15

    int ilogbd64(_Decimal64 x);
    int ilogbd32(_Decimal32 x);
    int ilogbd128(_Decimal128 x);
20

    _Decimal64 ldexpd64(_Decimal64 x, int exp);
    _Decimal32 ldexpd32(_Decimal32 x, int exp);
    _Decimal128 ldexpd128(_Decimal128 x, int exp);
25

    long int llogbd64(_Decimal64 x);
    long int llogbd32(_Decimal32 x);
    long int llogbd128(_Decimal128 x);

    _Decimal64 logd64(_Decimal64 x);
    _Decimal32 logd32(_Decimal32 x);
    _Decimal128 logd128(_Decimal128 x);
30

    _Decimal64 log10d64(_Decimal64 x);
    _Decimal32 log10d32(_Decimal32 x);
    _Decimal128 log10d128(_Decimal128 x);
35

    _Decimal64 log1pd64(_Decimal64 x);
    _Decimal32 log1pd32(_Decimal32 x);
    _Decimal128 log1pd128(_Decimal128 x);
40

    _Decimal64 log2d64(_Decimal64 x);
    _Decimal32 log2d32(_Decimal32 x);
    _Decimal128 log2d128(_Decimal128 x);
45

    _Decimal64 logbd64(_Decimal64 x);
    _Decimal32 logbd32(_Decimal32 x);
    _Decimal128 logbd128(_Decimal128 x);

    _Decimal64 modfd64(_Decimal64 value, _Decimal64 *iptr);
    _Decimal32 modfd32(_Decimal32 value, _Decimal32 *iptr);
    _Decimal128 modfd128(_Decimal128 value, _Decimal128 *iptr);
50

    _Decimal64 scalbnd64(_Decimal64 x, int n);
    _Decimal32 scalbnd32(_Decimal32 x, int n);
    _Decimal128 scalbnd128(_Decimal128 x, int n);
55

```

```

    _Decimal64 scalblnd64(_Decimal64 x, long int n);
    _Decimal32 scalblnd32(_Decimal32 x, long int n);
    _Decimal128 scalblnd128(_Decimal128 x, long int n);

```

7.12.7 Power and absolute-value functions

```

5      _Decimal64 cbrtd64(_Decimal64 x);
      _Decimal32 cbrtd32(_Decimal32 x);
      _Decimal128 cbrtd128(_Decimal128 x);

      _Decimal64 fabsd64(_Decimal64 x);
10     _Decimal32 fabsd32(_Decimal32 x);
      _Decimal128 fabsd128(_Decimal128 x);

      _Decimal64 hypotd64(_Decimal64 x, _Decimal64 y);
      _Decimal32 hypotd32(_Decimal32 x, _Decimal32 y);
15     _Decimal128 hypotd128(_Decimal128 x, _Decimal128 y);

      _Decimal64 powd64(_Decimal64 x, _Decimal64 y);
      _Decimal32 powd32(_Decimal32 x, _Decimal32 y);
      _Decimal128 powd128(_Decimal128 x, _Decimal128 y);
20     _Decimal64 sqrt64(_Decimal64 x);
      _Decimal32 sqrt32(_Decimal32 x);
      _Decimal128 sqrt128(_Decimal128 x);

```

7.12.8 Error and gamma functions

```

25     _Decimal64 erfd64(_Decimal64 x);
      _Decimal32 erfd32(_Decimal32 x);
      _Decimal128 erfd128(_Decimal128 x);

      _Decimal64 erfcd64(_Decimal64 x);
30     _Decimal32 erfcd32(_Decimal32 x);
      _Decimal128 erfcd128(_Decimal128 x);

      _Decimal64 lgammad64(_Decimal64 x);
      _Decimal32 lgammad32(_Decimal32 x);
35     _Decimal128 lgammad128(_Decimal128 x);

      _Decimal64 tgamma64(_Decimal64 x);
      _Decimal32 tgamma32(_Decimal32 x);
      _Decimal128 tgamma128(_Decimal128 x);

```

40 7.12.9 Nearest integer functions

```

      _Decimal64 ceild64(_Decimal64 x);
      _Decimal32 ceild32(_Decimal32 x);
      _Decimal128 ceild128(_Decimal128 x);

45     _Decimal64 floord64(_Decimal64 x);
      _Decimal32 floord32(_Decimal32 x);
      _Decimal128 floord128(_Decimal128 x);

      _Decimal64 nearbyintd64(_Decimal64 x);
50     _Decimal32 nearbyintd32(_Decimal32 x);
      _Decimal128 nearbyintd128(_Decimal128 x);

```

```

    _Decimal64 rintd64(_Decimal64 x);
    _Decimal32 rintd32(_Decimal32 x);
    _Decimal128 rintd128(_Decimal128 x);

5     long int lrintd64(_Decimal64 x);
    long int lrintd32(_Decimal32 x);
    long int lrintd128(_Decimal128 x);

    long long int llrintd64(_Decimal64 x);
10    long long int llrintd32(_Decimal32 x);
    long long int llrintd128(_Decimal128 x);

    _Decimal64 roundd64(_Decimal64 x);
    _Decimal32 roundd32(_Decimal32 x);
15    _Decimal128 roundd128(_Decimal128 x);

    long int lroundd64(_Decimal64 x);
    long int lroundd32(_Decimal32 x);
    long int lroundd128(_Decimal128 x);

20    long long int llroundd64(_Decimal64 x);
    long long int llroundd32(_Decimal32 x);
    long long int llroundd128(_Decimal128 x);

25    _Decimal64 roundevend64(_Decimal64 x);
    _Decimal32 roundevend32(_Decimal32 x);
    _Decimal128 roundevend128(_Decimal128 x);

    _Decimal64 truncd64(_Decimal64 x);
30    _Decimal32 truncd32(_Decimal32 x);
    _Decimal128 truncd128(_Decimal128 x);

    intmax_t fromfpd64(_Decimal64 x, int round, unsigned int width);
    intmax_t fromfpd32(_Decimal32 x, int round, unsigned int width);
35    intmax_t fromfpd128(_Decimal128 x, int round, unsigned int width);
    uintmax_t ufromfpd64(_Decimal64 x, int round, unsigned int width);
    uintmax_t ufromfpd32(_Decimal32 x, int round, unsigned int width);
    uintmax_t ufromfpd128(_Decimal128 x, int round, unsigned int width);

40    intmax_t fromfpxd64(_Decimal64 x, int round, unsigned int width);
    intmax_t fromfpxd32(_Decimal32 x, int round, unsigned int width);
    intmax_t fromfpxd128(_Decimal128 x, int round, unsigned int width);
    uintmax_t ufromfpxd64(_Decimal64 x, int round, unsigned int width);
    uintmax_t ufromfpxd32(_Decimal32 x, int round, unsigned int width);
45    uintmax_t ufromfpxd128(_Decimal128 x, int round, unsigned int width);

```

7.12.10 Remainder functions

```

    _Decimal64 fmodd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fmodd32(_Decimal32 x, _Decimal32 y);
50    _Decimal128 fmodd128(_Decimal128 x, _Decimal128 y);

    _Decimal64 remainderd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 remainderd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 remainderd128(_Decimal128 x, _Decimal128 y);

```

7.12.11 Manipulation functions

```

    _Decimal64 copysignd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 copysignd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 copysignd128(_Decimal128 x, _Decimal128 y);
5
    _Decimal64 nand64(const char *tagp);
    _Decimal32 nand32(const char *tagp);
    _Decimal128 nand128(const char *tagp);

10
    _Decimal64 nextafterd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 nextafterd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 nextafterd128(_Decimal128 x, _Decimal128 y);

15
    _Decimal64 nexttowardd64(_Decimal64 x, _Decimal128 y);
    _Decimal32 nexttowardd32(_Decimal32 x, _Decimal128 y);
    _Decimal128 nexttowardd128(_Decimal128 x, _Decimal128 y);

20
    _Decimal64 nextupd64(_Decimal64 x);
    _Decimal32 nextupd32(_Decimal32 x);
    _Decimal128 nextupd128(_Decimal128 x);

    _Decimal64 nextdownd64(_Decimal64 x);
    _Decimal32 nextdownd32(_Decimal32 x);
    _Decimal128 nextdownd128(_Decimal128 x);
25
    int canonicalized64(_Decimal64 * cx, const _Decimal64 * x);
    int canonicalized32(_Decimal32 * cx, const _Decimal32 * x);
    int canonicalized128(_Decimal128 * cx, const _Decimal128 * x);

```

7.12.12 Maximum, minimum, and positive difference functions

```

30
    _Decimal64 fdimd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fdimd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 fdimd128(_Decimal128 x, _Decimal128 y);

35
    _Decimal64 fmaxd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fmaxd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 fmaxd128(_Decimal128 x, _Decimal128 y);

40
    _Decimal64 fmind64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fmind32(_Decimal32 x, _Decimal32 y);
    _Decimal128 fmind128(_Decimal128 x, _Decimal128 y);

45
    _Decimal64 fmaxmagd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fmaxmagd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 fmaxmagd128(_Decimal128 x, _Decimal128 y);

    _Decimal64 fminmagd64(_Decimal64 x, _Decimal64 y);
    _Decimal32 fminmagd32(_Decimal32 x, _Decimal32 y);
    _Decimal128 fminmagd128(_Decimal128 x, _Decimal128 y);

```

7.12.13 Floating multiply-add

```

50
    _Decimal64 fmad64(_Decimal64 x, _Decimal64 y, _Decimal64 z);
    _Decimal32 fmad32(_Decimal32 x, _Decimal32 y, _Decimal32 z);
    _Decimal128 fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);

```

7.12.13a Functions that round result to narrower format

```

5  _Decimal32 d32addd64(_Decimal64 x, _Decimal64 y);
   _Decimal32 d32addd128(_Decimal128 x, _Decimal128 y);
   _Decimal64 d64addd128(_Decimal128 x, _Decimal128 y);

   _Decimal32 d32subd64(_Decimal64 x, _Decimal64 y);
   _Decimal32 d32subd128(_Decimal128 x, _Decimal128 y);
   _Decimal64 d64addd128(_Decimal128 x, _Decimal128 y);

10  _Decimal32 d32muld64(_Decimal64 x, _Decimal64 y);
   _Decimal32 d32muld128(_Decimal128 x, _Decimal128 y);
   _Decimal64 d64muld128(_Decimal128 x, _Decimal128 y);

   _Decimal32 d32divd64(_Decimal64 x, _Decimal64 y);
   _Decimal32 d32divd128(_Decimal128 x, _Decimal128 y);
   _Decimal64 d64divd128(_Decimal128 x, _Decimal128 y);

15  _Decimal32 d32fmad64(_Decimal64 x, _Decimal64 y, _Decimal64 z);
   _Decimal32 d32fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);
   _Decimal64 d64fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);

20  _Decimal32 d32sqrtd64(_Decimal64 x);
   _Decimal32 d32sqrtd128(_Decimal128 x);
   _Decimal64 d64sqrtd128(_Decimal128 x);

```

F.10.12 Total order functions

```

25  int totalorderd64(_Decimal64 x, _Decimal64 y);
   int totalorderd32(_Decimal32 x, _Decimal32 y);
   int totalorderd128(_Decimal128 x, _Decimal128 y);

30  int totalordermagd64(_Decimal64 x, _Decimal64 y);
   int totalordermagd32(_Decimal32 x, _Decimal32 y);
   int totalordermagd128(_Decimal128 x, _Decimal128 y);

```

F.10.13 Payload functions

```

35  _Decimal64 getpayloadd64(const _Decimal64 *x);
   _Decimal32 getpayloadd32(const _Decimal32 *x);
   _Decimal128 getpayloadd128(const _Decimal128 *x);

   int setpayloadd64(_Decimal64 *res, _Decimal64 pl);
   int setpayloadd32(_Decimal32 *res, _Decimal32 pl);
   int setpayloadd128(_Decimal128 *res, _Decimal128 pl);

40  int setpayloadsigd64(_Decimal64 *res, _Decimal64 pl);
   int setpayloadsigd32(_Decimal32 *res, _Decimal32 pl);
   int setpayloadsigd128(_Decimal128 *res, _Decimal128 pl);

```

In 7.12.10.3, attach a footnote to the heading:

7.12.10.3 The `remquo` functions

where the footnote is:

*) There are no decimal floating-point versions of the `remquo` functions.

Add to the end of 7.12.14#1:

[1] ... If either argument has decimal floating type, the other argument shall have decimal floating type as well.

Replace 7.12.6.4 paragraphs 2 and 3:

5 [2] The **frexp** functions break a floating-point number into a normalized fraction and an integral power of 2. They store the integer in the **int** object pointed to by **exp**.

[3] If **value** is not a floating-point number or if the integral power of 2 is outside the range of **int**, the results are unspecified. Otherwise, the **frexp** functions return the value **x**, such that **x** has a magnitude in the interval $[1/2, 1)$ or zero, and **value** equals $x \times 2^{\text{exp}}$. If **value** is zero, both parts of
10 the result are zero.

with the following:

[2] The **frexp** functions break a floating-point number into a normalized fraction and an integer exponent. They store the integer in the **int** object pointed to by **exp**. If the type of the function is a **standard** floating type, the exponent is an integral power of 2. If the type of the function is a decimal
15 floating type, the exponent is an integral power of 10.

[3] If **value** is not a floating-point number or the integral power is outside the range of **int**, the results are unspecified. Otherwise, the **frexp** functions return the value **x**, such that: **x** has a magnitude in the interval $[1/2, 1)$ or zero, and **value** equals $x \times 2^{\text{exp}}$, when the type of the function is a **standard** floating type; or **x** has a magnitude in the interval $[1/10, 1)$ or zero, and **value** equals $x \times$
20 10^{exp} , when the type of the function is a decimal floating type. If **value** is zero, both parts of the result are zero.

Replace 7.12.6.6 paragraphs 2 and 3:

[2] The **ldexp** functions multiply a floating-point number by an integral power of 2. A range error may occur.

25 [3] The **ldexp** functions return $x \times 2^{\text{exp}}$.

with the following:

[2] The **ldexp** functions multiply a floating-point number by an integral power of 2 when the type of the function is a **standard** floating type, or by an integral power of 10 when the type of the function is a decimal floating type. A range error may occur.

30 [3] The **ldexp** functions return $x \times 2^{\text{exp}}$ when the type of the function is a **standard** floating type, or return $x \times 10^{\text{exp}}$ when the type of the function is a decimal floating type.

Replace 7.12.6.11#2:

[2] The **logb** functions extract the exponent of **x**, as a signed integer value in floating-point format. If **x** is subnormal it is treated as though it were normalized; thus, for positive finite **x**,

35
$$1 \leq x \times \text{FLT_RADIX}^{-\text{logb}(x)} < \text{FLT_RADIX}$$

A domain error or pole error may occur if the argument is zero.

with the following:

[2] The `logb` functions extract the exponent of `x`, as a signed integer value in floating-point format. If `x` is subnormal it is treated as though it were normalized; thus, for positive finite `x`,

$$1 \leq x \times b^{-\text{logb}(x)} < b$$

5 | where `b = FLT_RADIX` if the type of the function is a **standard** floating type, or `b = 10` if the type of the function is a decimal floating type. A domain error or range error may occur if the argument is zero.

Replace 7.12.6.13 paragraphs 2 and 3:

[2] The `scalbn` and `scalbln` functions compute `x × FLT_RADIXn` efficiently, not normally by computing `FLT_RADIXn` explicitly. A range error may occur.

10 | [3] The `scalbn` and `scalbln` functions return `x × FLT_RADIXn`.

with the following:

[2] The `scalbn` and `scalbln` functions compute `x × bn`, where `b = FLT_RADIX` if the type of the function is a **standard** floating type, or `b = 10` if the type of the function is a decimal floating type. A range error may occur.

15 | [3] The `scalbn` and `scalbln` functions return `x × bn`.

12.4 Decimal-only functions in `<math.h>`

This clause **adds** new functions to `<math.h>`.

12.4.1 Quantum and quantum exponent functions

20 | This specification does not carry forward the `quantexpdN` functions from TR 24732, which return the quantum exponent of their argument as an `int`. Instead it introduces the `quantumdN` functions, which return the quantum rather than the quantum exponent, and the `llquantexpdN` functions, which return the quantum exponent as a `long long int`, instead of `int`. The new interfaces offer natural extensions for support of wider IEC 60559 decimal formats in Part 3 of Technical Specification 18661.

Change to C11 + TS18661-1:

25 | After subclause 7.12.11, add a new subclause:

7.12.11a Quantum and quantum exponent functions

7.12.11a.1 The `quantizedN` functions

Synopsis

30 | [1]

```
#define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
_Decimal32 quantized32(_Decimal32 x, _Decimal32 y);
_Decimal64 quantized64(_Decimal64 x, _Decimal64 y);
_Decimal128 quantized128(_Decimal128 x, _Decimal128 y);
```

Description

[2] The `quantizedN` functions **compute, if possible, a value with the numerical value of `x` and the quantum exponent of `y`**. If the quantum exponent is being increased, the value shall be correctly rounded; if the result does not have the same value as `x`, the “inexact” floating-point exception shall

be raised. If the quantum exponent is being decreased and the significand of the result has more digits than the type would allow, the result is NaN and a domain error occurs. If one or both operands are NaN the result is NaN. Otherwise if only one operand is infinite, the result is NaN and a domain error occurs. If both operands are infinite, the result is DEC_INFINITY with the sign of x , converted to the type of the function. The `quantize` functions do not raise the “underflow” floating-point exception.

Returns

[3] The `quantizedN` functions return a value with the numerical value of x (except for any rounding) and the quantum exponent of y .

7.12.11a.2 The `samequantumdN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
   _Bool samequantumd32(_Decimal32 x, _Decimal32 y);
   _Bool samequantumd64(_Decimal64 x, _Decimal64 y);
   _Bool samequantumd128(_Decimal128 x, _Decimal128 y);
```

Description

[2] The `samequantumdN` functions determine if the quantum exponents of x and y are the same. If both x and y are NaN, or both infinite, they have the same quantum exponents; if exactly one operand is infinite or exactly one operand is NaN, they do not have the same quantum exponents. The `samequantumdN` functions raise no floating-point exception.

Returns

[3] The `samequantumdN` functions return nonzero (true) when x and y have the same quantum exponents, zero (false) otherwise.

7.12.11a.3 The `quantumdN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
   _Decimal32 quantumd32(_Decimal32 x);
   _Decimal64 quantumd64(_Decimal64 x);
   _Decimal128 quantumd128(_Decimal128 x);
```

Description

[2] The `quantumdN` functions compute the quantum (5.2.4.2.2a) of a finite argument. If x is infinite, the result is $+\infty$. If x is NaN, the result is NaN.

Returns

[3] The `quantumdN` functions return the quantum of x .

7.12.11a.4 The `llquantexpdN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
long long int llquantexpd32(_Decimal32 x);
long long int llquantexpd64(_Decimal64 x);
long long int llquantexpd128(_Decimal128 x);
```

Description

[2] The `llquantexpdN` functions compute the quantum exponent (5.2.4.2.2a) of a finite argument. If `x` is infinite or NaN, they compute `LLONG_MIN` and a domain error occurs.

Returns

[3] The `llquantexpdN` functions return the quantum exponent of `x`.

12.4.2 Decimal re-encoding functions

IEC 60559 defines two alternative encoding schemes for its decimal interchange formats: one based on decimal encoding of the significand, the other based on binary encoding of the significand. (See IEC 60559 for details.) The two encoding schemes encode the same values. The re-encoding functions in this subclause allow the user to convert data, in either of the encoding schemes, to and from values of the corresponding decimal floating type.

Change to C11 + TS18661-1:

After subclause 7.12.11a, add a new subclause:

7.12.11b Decimal re-encoding functions

7.12.11b.1 The `encodedecdN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
void encodedecd32(unsigned char * restrict encptr, const _Decimal32 *
    restrict xptr);
void encodedecd64(unsigned char * restrict encptr, const _Decimal64 *
    restrict xptr);
void encodedecd128(unsigned char * restrict encptr, const _Decimal128 *
    restrict xptr);
```

Description

[2] The `encodedecdN` functions convert `*xptr` into an IEC 60559 decimal N encoding in the encoding scheme based on decimal encoding of the significand and store the resulting encoding as an $N/8$ element array, with 8 bits per array element, in the object pointed to by `encptr`. The order of bytes in the array is implementation-defined. These functions preserve the value of `*xptr` and raise no floating-point exceptions. If `*xptr` is non-canonical, these functions may or may not produce a canonical encoding.

Returns

[3] The `encodedecdN` functions return no value.

7.12.11b.2 The `decodedecdN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
5 void decodedecd32(_Decimal32 * restrict xptr, const unsigned char *
    restrict encptr);
void decodedecd64(_Decimal64 * restrict xptr, const unsigned char *
    restrict encptr);
10 void decodedecd128(_Decimal128 * restrict xptr, const unsigned char *
    restrict encptr);
```

Description

[2] The `decodedecdN` functions interpret the $N/8$ element array pointed to by `encptr` as an IEC 60559 decimal N encoding, with 8 bits per array element, in the encoding scheme based on decimal encoding of the significand. The order of bytes in the array is implementation-defined. These functions convert the given encoding into a value of type `_DecimalN`, and store the result in the object pointed to by `xptr`. These functions preserve the encoded value and raise no floating-point exceptions. If the encoding is non-canonical, these functions may or may not produce a canonical representation.

Returns

[3] The `decodedecdN` functions return no value.

7.12.11b.3 The `encodebindN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
25 void encodebind32(unsigned char * restrict encptr, const _Decimal32 *
    restrict xptr);
void encodebind64(unsigned char * restrict encptr, const _Decimal64 *
    restrict xptr);
30 void encodebind128(unsigned char * restrict encptr, const _Decimal128 *
    restrict xptr);
```

Description

[2] The `encodebindN` functions convert `*xptr` into an IEC 60559 decimal N encoding in the encoding scheme based on binary encoding of the significand and store the resulting encoding as an $N/8$ element array, with 8 bits per array element, in the object pointed to by `encptr`. The order of bytes in the array is implementation-defined. These functions preserve the value of `*xptr` and raise no floating-point exceptions. If `*xptr` is non-canonical, these functions may or may not produce a canonical encoding.

Returns

[3] The `encodebindN` functions return no value.

7.12.11b.4 The `decodebindN` functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
void decodebind32(_Decimal32 * restrict xptr, const unsigned char *
    restrict encptr);
void decodebind64(_Decimal64 * restrict xptr, const unsigned char *
    restrict encptr);
void decodebind128(_Decimal128 * restrict xptr, const unsigned char *
    restrict encptr);
```

Description

[2] The `decodebindN` functions interpret the $N/8$ element array pointed to by `encptr` as an IEC 60559 decimal N encoding, with 8 bits per array element, in the encoding scheme based on binary encoding of the significand. The order of bytes in the array is implementation-defined. These functions convert the given encoding into a value of type `_DecimalN`, and store the result in the object pointed to by `xptr`. These functions preserve the encoded value and raise no floating-point exceptions. If the encoding is non-canonical, these functions may or may not produce a canonical representation.

Returns

[3] The `decodebindN` functions return no value.

12.5 Formatted input/output specifiers

With the following decimal forms of the `a` (or `A`), format specifiers, the `printf` family of functions provide conversions to decimal character sequences that preserve quantum exponents, as required by IEC 60559.

Changes to C11 + TS18661-1:

Add the following to 7.21.6.1#7, 7.21.6.2#11, 7.29.2.1#7, and 7.29.2.2#11:

- H** Specifies that a following `a`, `A`, `e`, `E`, `f`, `F`, `g`, or `G` conversion specifier applies to a `_Decimal32` argument.
- D** Specifies that a following `a`, `A`, `e`, `E`, `f`, `F`, `g`, or `G` conversion specifier applies to a `_Decimal64` argument.
- DD** Specifies that a following `a`, `A`, `e`, `E`, `f`, `F`, `g`, or `G` conversion specifier applies to a `_Decimal128` argument.

Add the following to 7.21.6.1#8 and 7.29.2.1#8, under `a,A` conversion specifiers:

If an **H**, **D**, or **DD** modifier is present and the precision is missing, then for a decimal floating type argument represented by a triple of integers (s , c , q), where n is the number of digits in the coefficient c ,

- if $-(n+5) \leq q \leq 0$, use style `f` formatting with formatting precision equal to $-q$,
- otherwise, use style `e` formatting with formatting precision equal to $n - 1$, with the exceptions that if $c = 0$ then the *digit-sequence* in the *exponent-part* shall have the value q (rather than 0), and that the exponent is always expressed with the minimum number of digits required to represent its value (the exponent never contains a leading zero).

If the precision is present (in the conversion specification) and is zero or at least as large as the precision p (5.2.4.2.2) of the decimal floating type, the conversion is as if the precision were missing.

If the precision is present (and nonzero) and less than the precision p of the decimal floating type, the conversion first obtains an intermediate result by rounding the input in the type, according to the current rounding direction for decimal floating-point operations, to the number of digits specified by the precision, then converts the intermediate result as if the precision were missing. The length of the coefficient of the intermediate result is the smallest number, at least as large as the formatting precision, for which the quantum exponent is within the quantum exponent range of the type (see 5.2.4.2.2 Table 2). The intermediate rounding may overflow.

EXAMPLE 1 Following are representations of `_Decimal164` arguments as triples (s, c, q) and the corresponding character sequences `printf` produces with `%Da`:

```

10      ( 1, 123, 0)      123
        (-1, 123, 0)     -123
        ( 1, 123, -2)    1.23
        ( 1, 123, 1)     1.23e+3
        (-1, 123, 1)    -1.23e+3
15      ( 1, 123, -8)    0.00000123
        ( 1, 123, -9)    1.23e-7
        ( 1, 120, -8)    0.00000120
        ( 1, 120, -9)    1.20e-7
        ( 1, 1234567890123456, 0) 1234567890123456
20      ( 1, 1234567890123456, 1) 1.234567890123456e+16
        ( 1, 1234567890123456, -1) 123456789012345.6
        ( 1, 1234567890123456, -21) 0.000001234567890123456
        ( 1, 1234567890123456, -22) 1.234567890123456e-7
        ( 1, 0, 0)       0
25      (-1, 0, 0)       -0
        ( 1, 0, -6)      0.000000
        ( 1, 0, -7)      0e-7
        ( 1, 0, 2)       0e+2
        ( 1, 5, -6)       0.000005
30      ( 1, 50, -7)      0.0000050
        ( 1, 5, -7)       5e-7

```

EXAMPLE 2 To illustrate the effects of a precision specification, the sequence:

```

35      _Decimal32 x = 6543.00DF; // represented by the triple (1, 654300, -2)
        printf("%Ha\n", x);
        printf("%.6Ha\n", x);
        printf("%.5Ha\n", x);
        printf("%.4Ha\n", x);
        printf("%.3Ha\n", x);
40      printf("%.2Ha\n", x);
        printf("%.1Ha\n", x);
        printf("%.0Ha\n", x);

```

assuming default rounding, results in:

```

45      6543.00
        6543.00
        6543.0
        6543
        6.54e+3
50      6.5e+3
        7e+3
        6543.00

```

EXAMPLE 3 To illustrate the effects of the exponent range, the sequence:

```

    _Decimal32 x = 9543210e87DF; // represented by the triple (1, 9543210, 87)
    _Decimal32 y = 9500000e90DF; // represented by the triple (1, 9500000, 90)
    printf("%.6Ha\n", x);
    printf("%.5Ha\n", x);
    printf("%.4Ha\n", x);
    printf("%.3Ha\n", x);
    printf("%.2Ha\n", x);
    printf("%.1Ha\n", x);
    printf("%.1Ha\n", y);

```

assuming default rounding, results in:

```

    9.54321e+93
    9.5432e+93
    9.543e+93
    9.540e+93
    9.500e+93
    1.0000e+94
    inf

```

12.6 strtodN functions in <stdlib.h>

The specifications of these functions are similar to those of `strtod`, `strtof`, and `strtold` as defined in C11 7.22.1.3. These functions are declared in <stdlib.h>.

Changes to C11 + TS18661-1:

After 7.22.1.3, add:

7.22.1.3a The strtodN functions

Synopsis

```

[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
    #include <stdlib.h>
    _Decimal32 strtod32(const char * restrict nptr, char ** restrict
        endptr);
    _Decimal64 strtod64(const char * restrict nptr, char ** restrict
        endptr);
    _Decimal128 strtod128(const char * restrict nptr, char ** restrict
        endptr);

```

Description

[2] The `strtodN` functions convert the initial portion of the string pointed to by `nptr` to `_DecimaldN` representation. First, they decompose the input string into three parts: an initial, possibly empty, sequence of white-space characters (as specified by the `isspace` function), a subject sequence resembling a floating constant or representing an infinity or NaN; and a final string of one or more unrecognized characters, including the terminating null character of the input string. Then, they attempt to convert the subject sequence to a floating-point number, and return the result.

[3] The expected form of the subject sequence is an optional plus or minus sign, then one of the following:

- a nonempty sequence of decimal digits optionally containing a decimal-point character, then an optional exponent part as defined in 6.4.4.2;
- **INF** or **INFINITY**, ignoring case
- **NAN** or **NAN(*d-char-sequence*_{opt})**, ignoring case in the **NAN** part, where:

d-char-sequence:

digit

nondigit

d-char-sequence digit

d-char-sequence nondigit

The subject sequence is defined as the longest initial subsequence of the input string, starting with the first non-white-space character, that is of the expected form. The subject sequence contains no characters if the input string is not of the expected form.

[4] If the subject sequence has the expected form for a floating-point number, the sequence of characters starting with the first digit or the decimal-point character (whichever occurs first) is interpreted as a floating constant according to the rules of 6.4.4.2, except that it is not a hexadecimal floating number, that the decimal-point character is used in place of a period, and that if neither an exponent part nor a decimal-point character appears in a decimal floating-point number, an exponent part of the appropriate type with value zero is assumed to follow the last digit in the string. If the subject sequence begins with a minus sign, the sequence is interpreted as negated (before rounding). A character sequence **INF** or **INFINITY** is interpreted as an infinity. A character sequence **NAN** or **NAN(*d-char-sequence*_{opt})**, is interpreted as a quiet NaN; the meaning of the *d-char sequence* is implementation-defined. A pointer to the final string is stored in the object pointed to by **endptr**, provided that **endptr** is not a null pointer.

[5] If the sequence is negated, the sign *s* is set to -1 , else *s* is set to 1 .

[6] If the subject sequence has the expected form for a floating-point number, then the result shall be correctly rounded as specified in IEC 60559.

[7] The coefficient *c* and the quantum exponent *q* of a finite converted floating-point number are determined from the subject sequence as follows:

- The *fractional-constant* or *digit-sequence* and the *exponent-part* (if any) are extracted from the subject sequence. If there is an *exponent-part*, then *q* is set to the value of *sign*_{opt} *digit-sequence* in the *exponent-part*. If there is no *exponent-part*, *q* is set to 0 .
- If there is a *fractional-constant*, *q* is decreased by the number of digits to the right of the decimal point and the decimal point is removed to form a *digit-sequence*.
- *c* is set to the value of the *digit-sequence* (after any decimal point has been removed).
- Rounding required because of insufficient precision or range in the type of the result will round *c* to the full precision available in the type, and will adjust *q* accordingly within the limits of the type, provided the rounding does not yield an infinity (in which case an appropriately signed internal representation of infinity is returned). If the full precision of the type would require *q* to be smaller than the minimum for the type, then *q* is pinned at the minimum and *c* is adjusted through the subnormal range accordingly, perhaps to zero.

EXAMPLE Following are subject sequences of the decimal form and the resulting triples (*s*, *c*, *q*) produced by **strtod64**. Note that for **_Decima164**, the precision (maximum coefficient length) is 16 and the quantum exponent range is $-398 \leq q \leq 369$.

"0"	(1,0,0)
"0.00"	(1,0,-2)
"123"	(1,123,0)
"-123"	(-1,123,0)

	"1.23E3"	(1,123,1)
	"1.23E+3"	(1,123,1)
	"12.3E+7"	(1,123,6)
5	"12.0"	(1,120,-1)
	"12.3"	(1,123,-1)
	"0.00123"	(1,123,-5)
	"-1.23E-12"	(-1,123,-14)
	"1234.5E-4"	(1,12345,-5)
10	"-0"	(-1,0,0)
	"-0.00"	(-1,0,-2)
	"0E+7"	(1,0,7)
	"-0E-7"	(-1,0,-7)
	"12345678901234567890"	(1, 1234567890123457, 4) or (1, 1234567890123456, 4) depending on rounding mode
15	"1234E-400"	(1, 12, -398) or (1, 13, -398) depending on rounding mode
	"1234E-402"	(1, 0, -398) or (1, 1, -398) depending on rounding mode
	"1000."	(1,1000,0)
	".0001"	(1,1,-4)
20	"1000.e0"	(1,1000,0)
	".0001e0"	(1,1,-4)
	"1000.0"	(1,10000,-1)
	"0.0001"	(1,1,-4)
	"1000.00"	(1,100000,-2)
25	"00.0001"	(1,1,-4)
	"001000."	(1,1000,0)
	"001000.0"	(1,10000,-1)
	"001000.00"	(1,100000,-2)
	"00.00"	(1,0,-2)
	"00."	(1,0,0)
30	".00"	(1,0,-2)
	"00.00e-5"	(1,0,-7)
	"00.e-5"	(1,0,-5)
	".00e-5"	(1,0,-7)
35	"0x1.8p+4"	(1,0,0), and a pointer to "x1.8p+4" is stored in the object pointed to by <code>endptr</code> , provided <code>endptr</code> is not a null pointer
	"infinite"	infinity, and a pointer to "inite" is stored in the object pointed to by <code>endptr</code> , provided <code>endptr</code> is not a null pointer

[8] In other than the "C" locale, additional locale-specific subject sequence forms may be accepted.

[9] If the subject sequence is empty or does not have the expected form, no conversion is performed; the value of `nptr` is stored in the object pointed to by `endptr`, provided that `endptr` is not a null pointer.

Returns

[10] The functions return the **correctly rounded** converted value, if any. If no conversion could be performed, **the value** of the **triple (1,0,0)** is returned. If the correct value overflows, the value of the macro **ERANGE** is stored in `errno`. If the result underflows (7.12.1), whether `errno` acquires the value **ERANGE** is implementation-defined.

In 7.22.1.3a#4, attach a footnote to the wording:

the meaning of the d-char **sequence** is implementation-defined.

where the footnote is:

*) An implementation may use the d-char sequence to determine extra information to be represented in the NaN's significand.

12.7 `wcstodN` functions in `<wchar.h>`

The specifications of these functions are similar to those of `wcstod`, `wcstof`, and `wcstold` as defined in C11 7.29.4.1.1. They are declared in `<wchar.h>`.

Change to C11 + TS18661-1:

5 After 7.29.4.1.1, add:

7.29.4.1.1a The `wcstodN` functions

Synopsis

```

[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
    #include <wchar.h>
10  _Decimal32 wcstod32(const wchar_t * restrict nptr, wchar_t ** restrict
        endptr);
    _Decimal64 wcstod64(const wchar_t * restrict nptr, wchar_t ** restrict
        endptr);
15  _Decimal128 wcstod128(const wchar_t * restrict nptr, wchar_t **
        restrict endptr);

```

Description

[2] The `wcstodN` functions convert the initial portion of the wide string pointed to by `nptr` to `_DecimalN` representation. First, they decompose the input string into three parts: an initial, possibly empty, sequence of white-space wide characters (as specified by the `iswspace` function), a subject sequence resembling a floating constant or representing an infinity or NaN; and a final wide string of one or more unrecognized wide characters, including the terminating null wide character of the input wide string. Then, they attempt to convert the subject sequence to a floating-point number, and return the result.

[3] The expected form of the subject sequence is an optional plus or minus sign, then one of the following:

- a nonempty sequence of decimal digits optionally containing a decimal-point wide character, then an optional exponent part as defined in 6.4.4.2;
- **INF** or **INFINITY**, ignoring case
- 30 • **NAN** or **NAN(*d-wchar-sequence*_{opt})**, ignoring case in the **NAN** part, where:

```

d-wchar-sequence:
    digit
    nondigit
35  d-wchar-sequence digit
    d-wchar-sequence nondigit

```

The subject sequence is defined as the longest initial subsequence of the input wide string, starting with the first non-white-space wide character, that is of the expected form. The subject sequence contains no wide characters if the input wide string is not of the expected form.

[4] If the subject sequence has the expected form for a floating-point number, the sequence of wide characters starting with the first digit or the decimal-point wide character (whichever occurs first) is interpreted as a floating constant according to the rules of 6.4.4.2, except that it is not a hexadecimal floating number, that the decimal-point wide character is used in place of a period, and that if neither an exponent part nor a decimal-point wide character appears in a decimal floating-point number, an exponent part of the appropriate type with value zero is assumed to follow the last digit in the string. If the subject sequence begins with a minus sign, the sequence is interpreted as negated (before rounding). A wide character sequence **INF** or **INFINITY** is interpreted as an infinity. A wide

character sequence **NAN** or **NAN**(*d-wchar-sequence_{opt}*), is interpreted as a quiet NaN; the meaning of the d-wchar **sequence** is implementation-defined. A pointer to the final wide string is stored in the object pointed to by **endptr**, provided that **endptr** is not a null pointer.

[5] If the sequence is negated, the sign *s* is set to -1 , else *s* is set to 1.

[6] If the subject sequence has the expected form for a floating-point number, then the result shall be correctly rounded as specified in IEC 60559.

[7] The coefficient *c* and the quantum exponent *q* of a finite converted floating-point number are determined from the subject sequence as follows:

- The *fractional-constant* or *digit-sequence* and the *exponent-part* (if any) are extracted from the subject sequence. If there is an *exponent-part*, then *q* is set to the value of *sign_{opt} digit-sequence* in the *exponent-part*. If there is no *exponent-part*, *q* is set to 0.
- If there is a *fractional-constant*, *q* is decreased by the number of digits to the right of the decimal point and the decimal point is removed to form a *digit-sequence*.
- *c* is set to the value of the *digit-sequence* (after any decimal point has been removed).
- Rounding required because of insufficient precision or range in the type of the result will round *c* to the full precision available in the type, and will adjust *q* accordingly within the limits of the type, provided the rounding does not yield an infinity (in which case an appropriately signed internal representation of infinity is returned). If the full precision of the type would require *q* to be smaller than the minimum for the type, then *q* is pinned at the minimum and *c* is adjusted through the subnormal range accordingly, perhaps to zero.

[8] In other than the "C" locale, additional locale-specific subject sequence forms may be accepted.

[9] If the subject sequence is empty or does not have the expected form, no conversion is performed; the value of **nptr** is stored in the object pointed to by **endptr**, provided that **endptr** is not a null pointer.

Returns

[10] The functions return the converted value, if any. If no conversion could be performed, the **value** of the **triple** (1,0,0) is returned. If the correct value overflows and default rounding is in effect (7.12.1), plus or minus **HUGE_VAL_D64**, **HUGE_VAL_D32**, or **HUGE_VAL_D128** is returned (according to the return type and sign of the value), and the value of the macro **ERANGE** is stored in **errno**. If the result underflows (7.12.1), the functions return a value whose magnitude is no greater than the smallest normalized positive number in the return type; whether **errno** acquires the value **ERANGE** is implementation-defined.

In 7.29.4.1.3#4, attach a footnote to the wording:

the meaning of the d-wchar **sequence** is implementation-defined.

where the footnote is:

*) An implementation may use the d-wchar sequence to determine extra information to be represented in the NaN's significand.

12.8 **strfromdN** functions in **<stdlib.h>**

The specifications of these functions are similar to those of **strfromd**, **strfromf**, and **strfromld** (7.22.1.2a) as defined in Part 1 (10.2) of Technical Specification 18661. These functions are declared in **<stdlib.h>**.

Change to C11 + TS18661-1:

After 7.22.1.2a, add:

7.22.1.2b The `strfromdN` functions**Synopsis**

```

5  [1] #define __STDC_WANT_IEC_60559_DFP_EXT__
      #include <stdlib.h>
      int strfromd32(char * restrict s, size_t n, const char * restrict
          format, _Decimal32 fp);
10  int strfromd64(char * restrict s, size_t n, const char * restrict
          format, _Decimal64 fp);
      int strfromd128(char * restrict s, size_t n, const char * restrict
          format, _Decimal128 fp);

```

Description

15 [2] The `strfromdN` functions are equivalent to `snprintf(s, n, format, fp)` (7.21.6.5), except the `format` string contains only the character `%`, an optional precision that does not contain an asterisk `*`, and one of the conversion specifiers `a`, `A`, `e`, `E`, `f`, `F`, `g`, or `G`, which applies to the type (`_Decimal32`, `_Decimal64`, or `_Decimal128`) indicated by the function suffix (rather than by a length modifier). Use of these functions with any other `format` string results in undefined behavior.

Returns

20 [3] The `strfromdN` functions return the number of characters that would have been written had `n` been sufficiently large, not counting the terminating null character. Thus, the null-terminated output has been completely written if and only if the returned value is less than `n`.

12.9 Type-generic math for decimal in `<tgmath.h>`

25 The following changes to C11 + TS18661-1 enhance the specification of type-generic macros in `<tgmath.h>` to apply to decimal floating types, as well as standard floating types.

Changes to C11 + TS18661-1:

In 7.25, replace paragraphs 2 and 3:

30 [2] Of the `<math.h>` and `<complex.h>` functions without an `f` (`float`) or `l` (`long double`) suffix, several have one or more parameters whose corresponding real type is `double`. For each such function, except `modf`, `setpayload`, and `setpayloadsig`, there is a corresponding *type-generic macro*.³¹³ The parameters whose corresponding real type is `double` in the function synopsis are *generic parameters*. Use of the macro invokes a function whose corresponding real type and type domain are determined by the arguments for the generic parameters.³¹⁴

35 [3] Except for the macros for functions that round result to a narrower type (7.12.13a), use of the macro invokes a function whose generic parameters have the corresponding real type determined as follows:

- First, if any argument for generic parameters has type `long double`, the type determined is `long double`.
- Otherwise, if any argument for generic parameters has type `double` or is of integer type, the type determined is `double`.
- Otherwise, the type determined is `float`.

with:

[2] This clause specifies a many-to-one correspondence of functions in `<math.h>` and `<complex.h>` with *type-generic macros*.³¹³⁾ Use of a type-generic macro invokes a corresponding function whose type is determined by the types of the arguments for particular parameters called the *generic parameters*.³¹⁴⁾

[3] Of the `<math.h>` and `<complex.h>` functions without an `f` (`float`) or `l` (`long double`) suffix, several have one or more parameters whose corresponding real type is `double`. For each such function, except `modf`, `setpayload`, and `setpayloadsig`, there is a corresponding type-generic macro.³¹³⁾ The parameters whose corresponding real type is `double` in the function synopsis are generic parameters.

[3a] Some of the `<math.h>` functions for decimal floating types have no unsuffixed counterpart. Of these functions with a `d64` suffix, some have one or more parameters whose type is `_Decimal64`. For each such function, except `decodedecd64`, `encodedecd64`, `decodebind64`, and `encodebind64`, there is a corresponding type-generic macro. The parameters whose real type is `_Decimal64` in the function synopsis are generic parameters.

[3b] If arguments for generic parameters of a type-generic macro are such that some argument has a corresponding real type that is of *standard* floating type and another argument is of decimal floating type, the behavior is undefined.

[3c] Except for the macros for functions that round result to a narrower type (7.12.13a), use of a type-generic macro invokes a function whose generic parameters have the corresponding real type determined by the corresponding real types of the arguments as follows:

- First, if any argument for generic parameters has type `_Decimal128`, the type determined is `_Decimal128`.
- Otherwise, if any argument for generic parameters has type `_Decimal64`, or if any argument for generic parameters is of integer type and another argument for generic parameters has type `_Decimal32`, the type determined is `_Decimal64`.
- Otherwise, if any argument for generic parameters has type `_Decimal32`, the type determined is `_Decimal32`.
- Otherwise, if the corresponding real type of any argument for generic parameters is `long double`, the type determined is `long double`.
- Otherwise, if the corresponding real type of any argument for generic parameters is `double` or is of integer type, the type determined is `double`.
- Otherwise, if any argument for generic parameters is of integer type, the type determined is `double`.
- Otherwise, the type determined is `float`.

If neither `<math.h>` nor `<complex.h>` define a function whose generic parameters have the determined corresponding real type, the behavior is undefined.

In 7.25#5, replace the last sentence:

If all arguments for generic parameters are real, then use of the macro invokes a real function; otherwise, use of the macro results in undefined behavior.

with:

If all arguments for generic parameters are real, then use of the macro invokes a real function (provided `<math.h>` defines a function of the determined type); otherwise, use of the macro results in undefined behavior.

5 In 7.25#6, replace the last sentence:

Use of the macro with any real or complex argument invokes a complex function.

with:

Use of the macro with any **argument of standard** floating or complex **type** invokes a complex function. Use of the macro with an argument of decimal floating type results in undefined behavior.

10 Change 7.25.6a from:

[7.25.6a] The functions that round result to a narrower type have type-generic macros whose names are obtained by omitting any **f** or **l** suffix from the function names. Thus, the macros are:

	fadd	fmul	ffma
	dadd	dmul	dfma
15	fsub	fdiv	fsqrt
	dsub	ddiv	dsqrt

All arguments are generic. If any argument is not real, use of the macro results in undefined behavior. If any argument has type **long double**, or if the macro prefix is **d**, the function invoked has the name of the macro with an **l** suffix. Otherwise, the function invoked has the name of the macro (with no suffix).

to:

[7.25.6a] The functions that round result to a narrower type have type-generic macros whose names are obtained by omitting any suffix from the function names. Thus, the macros are:

25	fadd	fmul	ffma
	dadd	dmul	dfma
	fsub	fdiv	fsqrt
	dsub	ddiv	dsqrt
	d32add	d32mul	d32fma
30	d64add	d64mul	d64fma
	d32sub	d32div	d32sqrt
	d64sub	d64div	d64sqrt

All arguments are generic. If any argument is not real, use of the macro results in undefined behavior. If the macro prefix is **f** or **d**, use of an argument of decimal floating type results in undefined behavior. If the macro prefix is **d32** or **d64**, use of an argument of standard floating type results in undefined behavior. The function invoked is determined as follows:

- If any argument has type **_Decima1128**, or if the macro prefix is **d64**, the function invoked has the name of the macro, with a **d128** suffix.
- 40 — Otherwise, if the macro prefix is **d32**, the function invoked has the name of the macro, with a **d64** suffix.
- Otherwise, if any argument has type **long double**, or if the macro prefix is **d**, the function invoked has the name of the macro, with an **l** suffix.
- Otherwise, the function invoked has the name of the macro (with no suffix).

After 7.25#6a, before 7.25#6b (see Part 1 of Technical Specification 18661), add the paragraph:

[6a+] For each `d64`-suffixed function in `<math.h>`, except `decodedecd64`, `encodedecd64`, `decodebind64`, and `encodebind64`, that does not have an unsuffixed counterpart, the corresponding type-generic macro has the name of the function, but without the suffix. These type-generic macros are:

<code><math.h></code> function	type-generic macro
-----	-----
<code>quantizedN</code>	<code>quantize</code>
<code>samequantumdN</code>	<code>samequantum</code>
<code>quantumdN</code>	<code>quantum</code>
<code>llquantexpdN</code>	<code>llquantexp</code>

Use of the macro with an argument of standard floating or complex type or with only integer type arguments results in undefined behavior.

After 7.25#6b, add the paragraph:

[6c] A type-generic macro `cbirt` that supports decimal floating-point functions and that is affected by constant rounding modes as specified in Part 1 of Technical Specification 18661 could be implemented as follows:

```

20  #ifndef __STDC_WANT_IEC_60559_DFP_EXT__
      #define cbirt(X)  _Generic((X),
                          \
                          _Decimal128: cbrtd128(X), \
                          _Decimal64: cbrtd64(X),   \
                          _Decimal32: cbrtd32(X),   \
25  long double: cbrtl(X), \
                          default: _Roundwise_cbirt(X), \
                          float: cbrtf(X)         \
                          )
      #else
30  #define cbirt(X)  _Generic((X),
                          \
                          long double: cbrtl(X),   \
                          default: _Roundwise_cbirt(X), \
                          float: cbrtf(X)         \
                          )
35  #endif

```

where `_Roundwise_cbirt()` is equivalent to `cbirt()` invoked without macro-replacement suppression.

In 7.25#7, insert at the beginning of the example:

```

40  #define __STDC_WANT_IEC_60559_DFP_EXT__

```

In 7.25#7, append to the declarations:

```

45  #if __STDC_IEC_60559_DFP__ >= 201ymmL
      _Decimal32 d32;
      _Decimal64 d64;
      _Decimal128 d128;
      #endif

```

In 7.25#7, append to the table:

	<code>exp(d64)</code>	<code>expd64(d64);</code>
	<code>sqrt(d32)</code>	<code>sqrtd32(d32);</code>
5	<code>fmax(d64, d128)</code>	<code>fmaxd128(d64, d128);</code>
	<code>pow(d32, n)</code>	<code>powd64(d32, n);</code>
	<code>remainder(d64, d)</code>	<code>undefined behavior</code>
	<code>creal(d64)</code>	<code>undefined behavior</code>
	<code>remquo(d32, d32, &n)</code>	<code>undefined behavior</code>
10	<code>llquantexp(d)</code>	<code>undefined behavior</code>
	<code>quantize(dc)</code>	<code>undefined behavior</code>
	<code>samequantum(n, n)</code>	<code>undefined behavior</code>
	<code>d32sub(d32, d128)</code>	<code>d32subd128(d32, d128)</code>
	<code>d32div(d64, n)</code>	<code>d32divd64(d64, n)</code>
15	<code>d64fma(d32, d64, d128)</code>	<code>d64fmad128(d32, d64, d128)</code>
	<code>d64add(d32, d32)</code>	<code>d64addd128(d32, d32)</code>
	<code>d64sqrt(d)</code>	<code>undefined behavior</code>
	<code>dadd(n, d64)</code>	<code>undefined behavior</code>

Bibliography

- [1] ISO/IEC 9899:2011, *Information technology — Programming languages, their environments and system software interfaces — Programming Language C*
- [2] ISO/IEC 9899:2011/Cor.1:2012, *Technical Corrigendum 1*
- 5 [3] ISO/IEC/IEEE 60559:2011, *Information technology — Microprocessor Systems — Floating-point arithmetic*
- [4] ISO/IEC TR 24732:2009, *Information technology – Programming languages, their environments and system software interfaces – Extension for the programming language C to support decimal floating-point arithmetic*
- 10 [5] IEC 60559:1989, *Binary floating-point arithmetic for microprocessor systems, second edition*
- [6] IEEE 754-2008, *IEEE Standard for Floating-Point Arithmetic*
- [7] IEEE 754-1985, *IEEE Standard for Binary Floating-Point Arithmetic*
- [8] IEEE 854-1987, *IEEE Standard for Radix-Independent Floating-Point Arithmetic*