By: Philippe Le Mouël
Rogue Wave Software Inc.
philippe@roguewave.com

Doc. No.: X3J16/96-0099
WG21/N0917
Date: May 25 1996

Iostreams Issues List
Library Clause 27

Revision History

Pre-Stockholm	X3J16/96-0099 WG21/N0917
Post-Santa-Cruz	X3J16/96-0079 WG21/N0897
Pre-Santa Cruz	X3J16/96-0009 WG21/N0827
Post-Tokyo	X3J16/95-0221 WG21/N0821
Pre-Tokyo	X3J16/95-0194 WG21/N0794
Pre-Monterey	X3J16/95-0089 WG21/N0689
Pre-Austin	X3J16/95-0034 WG21/N0634

Summary of Issues

27.4.2 ios_traits **P. 5**

Active 27-001 Making newline locale aware
Active 27-002 is_whitespace is inconsistent
Active 27-004 example of changing the behavior of is_whitespace is incorrect.
Active 27-005 not_eof specification
Active 27-007 ios_traits typedefs are ‘char’ oriented
Active 27-008 ios_traits::length is missing **Returns:** clause
Active 27-009 ios_traits::get_state should be specified
Active 27-010 ios_traits::get_pos should be specified
Active 27-011 Return type for ios_traits::copy is incorrect

Closed 27-003 Mention of base struct string_char_traits (Tokyo)
Closed 27-006 streamsize should be ***SZ_T*** not ***INT_T*** (Tokyo)

27.4.3 ios_base **P. 10**

Active 27-106 Init class should be an implementation detail
Active 27-107 ios::failure doesn’t have the same functionality
Active 27-108 cin, cout … construction and initialization (Box)

Closed 27-101 ios_base manipulators (Santa-Cruz)
Closed 27-102 ios_base::width semantics are incorrect (Santa-Cruz)
Closed 27-103 proposal for adding ios_base::maxwidth (Santa-Cruz)

Closed 27-104 ios_base unitbuf and nounitbuf manipulators (Santa-Cruz)
Closed 27-105 ios_base storage functions are not exception safe (Santa-Cruz)

27.4.4 basic_ios P. 11

Active 27-203 operator bool( ) needs to be fixed
Active 27-205 imbue should not call rdbuf( )->pubimbue
Active 27-206 clear() should not unconditionally clear the error state
Active 27-207 availability of char_traits in header ios (Box)
Active 27-208 move member functions from basic_ios to ios_base (Box)
Active 27-209 imbueing getloc()::codecvt into the argument stream buffer (Box)

Closed 27-201 remove throw specifications for clear and setstate (Tokyo)
Closed 27-202 tie not required to be associated with an input sequence (Tokyo)
Closed 27-204 replace int_type by char_type in int_type fill( ) and int_type fill(int_type) (Tokyo)

27.5.2 basic_streambuf P. 15

Active 27-301 imbuing on streambufs. When, how often, etc...
Active 27-312 sync does not say what happens to the input sequence (Box)

Closed 27-302 sungetc has an incorrect return type (Tokyo)
Closed 27-303 not_eof needs to be used where appropriate (Santa-Cruz)
Closed 27-304 uflow needs editing (Santa-Cruz)
Closed 27-305 basic_streambuf::showmanyc Incorrect return clause (Santa-Cruz)
Closed 27-306 basic_streambuf::uflow has incorrect default behavior (Santa-Cruz)
Closed 27-307 basic_streambuf::uflow has nonsense returns clause (Santa-Cruz)
Closed 27-308 streambuf inlines (Santa-Cruz)
Closed 27-309 two return clauses for streambuf::underflow (Santa-Cruz)
Closed 27-310 streambuf::pbackfail has incorrect **Notes:** clause (Santa-Cruz)
Closed 27-311 caching results of calls to locale functions (Santa-Cruz)

27.6.1 basic_istream P. 16

Active 27-404 istream functions need to check for NULL streambuf
Active 27-405 confusing English in formatted requirements
Active 27-406 operator>>(char_type *) failure
Active 27-407 operator>>(char_type) failure
Active 27-408 ws manipulator
Active 27-409 unsigned short extractors cannot use unsigned long get function
Active 27-410 putback function has wrong description
Active 27-411 getline should not set failbit when reading no characters
Active 27-412 operator >>(basic_streambuf *sb), should not set badbit if sb is null
Active 27-413 sentence missing (Box)
Active 27-414 readsome, putback and unget need to check for good (Box)
Active 27-415 streampos need to be replaced (Box)

Closed 27-401 isfx what does it do? (Santa-Cruz)
Closed 27-402 ipfx example is incorrect (Santa-Cruz)
Closed 47-403 Clarification of exceptions thrown (Santa-Cruz)

27.6.2 basic_ostream P. 21

Active 27-501 op<<(char) needs to be consistant with the other formatted inserters
Active 27-503 ostream functions need to check for NULL streambuf
Active 27-505 incorrect conversion specifier for operator<<(unsigned long)
Active 27-506 wrong default behavior for padding

Closed 27-502 op<<(void *) should it be const volatile void * (Santa-Cruz)
Closed 27-504 exceptions in ostream (Santa-Cruz)

27.6.1-27.6.2 basic_istream, basic_ostream P. 23

Active 27-601 op[<<|>>](ios_base&) needed for manipulators
Active 27-602 positional typedefs in istream/ostream derived classes are not needed
Active 27-603 read/write should take a void * instead of a char_type *
Active 27-604 Should we require ios::in to be set for istream's and ios::out to be set for ostream's?
Active 27-605 Should get/put use iterators?
Active 27-606 seekg and seekp should have their first parameter passed by value.
Active 27-607 locale getnum needed for void* extractor (Box)

27.6.3 Standard manipulators P. 28

Active 27-651 setfill description is wrong
Active 27-652 smanip is not a single type

27.7 string streams P. 29

Active 27-701 str() needs to clarify return value on else clause
Active 27-702 string stream classes need to have string_char_traits and allocator parameters
Active 27-703 stringbuf postconditions
Active 27-704 stringbuf::stringbuf constructor
Active 27-705 Incorrect calls to setg and setp in Table 14
Active 27-706 Incorrect calls to setg and setp in table 16
Active 27-707 setbuf function is missing

27.8 fstreams P. 34

Active 27-801 filebuf::underflow example is incorrect
Active 27-802 filebuf::is_open is a bit confusing
Active 27-803 ofstream constructor missing trunc as openmode
Active 27-804 ofstream::open missing trunc in openmode
Active 27-805 filebuf::imbue semantics
Active 27-806 filebuf::seekoff **Effects:** clause needs work
Active 27-807 filebuf::underflow performance questions
Active 27-808 Editorial fixes in wording for fstreams
Active 27-809 description of function setbuf is missing
Active 27-810 openmode notation is not consistent in basic_ifstream and basic_ofstream
Active 27-811 description of function sync is missing
Active 27-812 filebuf::overflow example is incorrect
Active 27-813 basic_filebuf::overflow does not specifies its return value on success
Active 27-814 basic_filebuf::imbue has no description
Active 27-815 description of function seekpos is missing

Active 27-816 (i)(o)fstream open functions should not use is_open

Miscellaneous P. 42

Active 27-901 input/output of unsigned char, and signed char
Active 27-904 iosfwd declarations incomplete
Active 27-906 add a typedef to access the traits parameter in each stream class
Active 27-907 Use of “instance of” vs. “version of” in descriptions of class ios
Active 27-908 unnecessary ‘;’ (semicolons) in tables
Active 27-909 Editorial issues (typo’s)
Active 27-910 remove streampos in favor of pos_type
Active 27-911 stdio synchronization
Active 27-912 removing **Notes:** from the text
Active 27-913 Incorporating **Notes:** into the text
Active 27-914 rethrowing exceptions
Active 27-915 The use of specialization
Active 27-916 missing descriptions of specializations
Active 27-917 Editorial changes
Active 27-918 Validity of OFF_T to POS_T conversion
Active 27-919 Question on Table 2 assertions
Active 27-920 destination of clog and wclog
Active 27-921 default locale argument to constructor
Active 27-922 Cleaning the iostreams header synopsis #include of other headers

Closed 27-902 default locale (Santa-Cruz)
Closed 27-903 ipfx/opfx/isfx/osfx not compatible with exceptions (Santa-Cruz)
Closed 27-905 iostream type classes are missing (Santa-Cruz)

Annex D P. 56

Active 27-1001 description of function setbuf is not sufficient
Active 27-1002 strstreambuf Editorial issues
Active 27-1003 istrstream Editorial issues
Active 27-1004 ostrstream Editorial issues

Total remaining active issues: 91

ios_traits issues

Issue Number: 27-001
Title: changing traits::newline to be locale aware
Section: 27.4.2.1 **ios_traits value functions [lib.ios.traits.values]**
Status: **active**
Description:

The problem with traits::newline is that it does not know about the currently imbued locale.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends changing the description of functions *get* and *getline* so there are two variants instead of one with a default argument. Nathan Myers will provide text for the proposal.

Requestor: Nathan Myers (ncm@cantrip.org),
John Hinke (hinke@roguewave.com)

Issue Number: 27-002
Title: traits::is_whitespace() is inconsistent
Section: 27.4.2.2 **ios_traits test functions [lib.ios.traits.tests]**
Status: **active**
Description:

This function is inconsistent throughout the document. For example:

27.4.2 Template struct ios_traits [lib.ios.traits]
static bool is_whitespace(int_type, const ctype<char_type>&);

27.4.2.2 ios_traits test functions [lib.ios.traits.tests]
bool is_whitespace(int_type c, const ctype<char_type>& ct);

Returns: true if *c* represents a white space character. The default definition is as if it returns *ct.*isspace(*c*).

The returns paragraph calls a method of ctype that does not exist.
It should say:

Returns: true if *c* represents a white space character. The default definition is as if it returns *ct.*is(*ct*.space, *c*).

27.6.1.1.2 basic_istream::ipfx [lib.istream.prefix]
Notes: ...uses the function
bool traits::is_whitespace(charT, const ctype<charT>&)

The same paragraph goes on to use ctype<...> in the example.

27.6.1.1.2 Paragraph 4: [lib.istream.prefix]
static bool is_whitespace(char, const ctype<charT>&)

Possible Resolution:

The Santa Cruz meeting, deprecates the is_whitespace function, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). The pre-Stockholm Iostreams WG recommends closing the issue with no action.

Requestor: John Hinke (hinke@roguewave.com)
Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-004
Title: example of changing the behavior of is_whitespace is incorrect.
Section: 27.6.1.1.2 Paragraph 4 **basic_istream prefix and suffix [lib.istream.prefix]**
Status: **active**
Description:

Change from:

```
struct my_char_traits : public ios_traits<char> {
    static bool is_whitespace(char c, const ctype<charT>& ct)
        { ...my own implementation... }
};
```

To:

```
struct my_char_traits : public ios_traits<char> {
    static bool is_whitespace(char c, const ctype<char>& ct)
        { ...my own implementation... }
};
```

Possible Resolution:

The Santa Cruz meeting, deprecates the is_whitespace function, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). The pre-Stockholm Iostreams WG recommends closing the issue with no action.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-005
Title: not_eof specification
Section: 27.4.2.1 ios_traits value functions **[lib.ios.traits.values]**
Status: **active**
Description:

int_type not_eof(int_type c);

Editorial: "**Notes:**" should also mention it is used for sbumpc and sgetc.

Per Bothner writes:
"The **Returns:** is incompatible with the traditional masking function for zapeof. This is because int_type(-2) == -2 while zapeof(-2) == ((-2) & 0xFF). And nowhere else does it say anything that would allow the traditional implementation."

"I don't understand the presentation style well enough to suggest the proper fix. But somewhere it should say or imply that when charT is specialized with char, then not_eof(c) is int_type((unsigned char)(c))."

Possible Resolution:

The pre-Stockholm Iostreams WG recommends changing the specification of function *not_eof*. It has to yield a value which is not equal to *eof*. The value is unspecified. (The current WP requires that *not_eof(e)==e* if *e!=eof()*, and forces a change from existing practice. The recomandation allows existing implementation to remain unchanged.) Tom Plum will provide text for the proposal.

Requestor: Per Bothner (bothner@cygnus.com)

Issue Number: 27-007
Title: ios_traits typedefs are 'char' oriented.
Section: 27
Status: **active**
Description:

We cannot specify int_type, off_type, pos_type, and state_type corresponding to some specialized charT type.

For example, if in order to think about 'char' specialization, we might define

```
template <class charT> struct ios_traits {
    ....
    typedef charT char_type;
    typedef int int_type;
    ....
};
```

we would have to accept it as constant definition in all of the specialized traits, not only ios_traits<char>, but ios_traits<wchar_t>, ios_traits<ultrachar>. This would lead to the restriction upon implementations that all of the charT must be converted in 'int' range. The restriction is too heavy for future wide character types and user-defined character types.

Possible Resolution:

The Santa Cruz meeting, fixes the problem, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). The pre-Stockholm Iostreams WG recommends closing the issue with no action.

Requestor: Norihiro Kumagai (kuma@slab.tnr.sharp.co.jp)

Issue Number: 27-008
Title: `ios_traits::length` is missing **Returns:** clause
Section: 27.4.2.1 **ios_traits value functions [lib.ios.traits.values]**
Status: **active**
Description:

`ios_traits::length` has an **Effects:** clause but no **Returns:** clause. The **Effects:** clause should be reworded as a **Returns:** clause.

Possible Resolution:

The Santa Cruz meeting, fixes the problem, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). The pre-Stockholm Iostreams WG recommends closing the issue with no action.

Requestor: Public Comment

Issue Number: 27-009
Title: definition for `get_state`
Section: 27.4.2.3 **ios_traits conversion functions [lib.ios.traits.convert]**
Status: **active**
Description:

The definition of `ios_traits::get_state` is incomplete. Here is the complete description:

```
state_type get_state(pos_type pos);
```

Returns: A `state_type` value which represents the conversion state in the object *`pos`*.

Possible Resolution:

No consensus was reached on this issue by the pre-Stockholm Iostreams WG. Jerry Schwarz will bring a proposal along these lines:

Add new trait type: char_traits::upos_type
No constraints on this type.
Replace get_pos with: pos_type make_pos(upos_type, state_type)
Add new function: upos_type get_pos(pos_type)

Requestor: Norihiro Kumagai (kuma @ slab.tnr.sharp.co.jp)

Issue Number: 27-010
Title: definition for `get_pos`
Section: 27.4.2.3 **ios_traits conversion functions [lib.ios.traits.convert]**
Status: **active**
Description:

The definition of `ios_traits::get_pos` is incomplete. Here is the complete description:

```
pos_type get_pos(streampos pos, state_type s);
```

Effects: Constructs a `pos_type` value which represents the stream position corresponding to the pair of *`pos`* and *`s`*.

Returns: A `pos_type` value which consists of the values of *`pos`* and *`s`*.

Possible Resolution:

No consensus was reached on this issue by the pre-Stockholm Iostreams WG. Jerry Schwarz will bring a proposal along these lines:

Add new trait type: char_traits::upos_type
No constraints on this type.
Replace get_pos with: pos_type make_pos(upos_type, state_type)
Add new function: upos_type get_pos(pos_type)

Requestor: Norihiro Kumagai (kuma @ slab.tnr.sharp.co.jp)

Issue Number: 27-011
Title: Return type for `ios_traits::copy` is incorrect
Section: 27.4.2.3 **`ios_traits` conversion functions [lib.ios.traits.convert]**
Status: **active**
Description:

The return type for `ios_traits::copy` says to return `dst`. It should return `dest`.

Possible Resolution:

The Santa Cruz meeting, fixes the problem, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). The pre-Stockholm Iostreams WG recommends closing the issue with no action.

Requestor: John Hinke (hinke@roguewave.com)

`ios_base` issues

Issue Number: 27-106
Title: Init class should be an implementation detail
Section: 27.4.3.1.6 **Class ios_base::Init [lib.ios::Init]**
Status: **active**
Description:

I fail to see why the Init class is part of the normative Standard. It is an implementation detail and hence, belongs in the realm of the implementor, not in the Standard.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends no change to the WP. (Jerry Schwarz might add an example showing why Init is needed.)

Requestor: Public Comment

Issue Number: 27-107
Title: ios::failure doesn't have the same functionality
Section: 27.4.3 **Class ios_base [lib.ios.base]**
Status: **active**
Description:

Long ago when I originally proposed *ios::failure* I put the stream into it (as a reference). It now doesn't have that functionality. I don't know if it was removed deliberately or just got dropped inadvertantly. I think it should be there.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends no change to the WP. (Stream lifetime might end before lifetime of the reference.)

Requestor: Jerry Schwarz (jss@a.crl.com)

Issue Number: 27-108
Title: cin, cout … construction and initialization (Box)
Section: 27.3 **Standard iostream objects [lib.iostream.objects]**
Status: **active**
Description:

The standard iostreams objects (cin, cout, cerr, clog, wcin, wcout, wcerr, wclog) need to be constructed and associations established before dynamic initialization of file scope variables is begun.

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

basic_ios issues

Issue Number: 27-203
Title: `operator bool()` needs to be fixed
Section: 27.4.4.3 **basic_ios iostate flags functions [lib.iostate.flags]**
Status: **active**
Description:

Defining ios_base (or, as it appears in my copy of the WP, basic_ios) with a member operator bool() seemed like a good idea at the time, but perhaps the change should be withdrawn.

The reason is: while a conversion to void* is mostly harmless because few functions accept a void* argument, and void* doesn't silently convert to anything else, with an operator bool, the following absurdities are well-defined:

```
1 + cin
sin(cin)
vector<int> v(cin);
```

and (worse) ambiguities like

```
void f(istreambuf_iterator<char>);
void f(double);

f(cin);  // ambiguous
```

have been introduced. In other words, this change broke reasonable code. The problem is that bool is an arithmetic type, and is ill-behaved.

Possible Resolution:

Replace the member `ios_base::operator bool()` with member `ios_base::operator const void*()`, specified to return 0 if fail( ) is true, and non 0 if it is false.

This restores the code we broke, and also prevents frustrating ambiguities in new code.

The pre-Stockholm Iostreams WG recommends to wait for the final resolution of bool properties before taking any action.

Requestor: Nathan Myers (ncm@cantrip.org)

Issue Number: 27-205
Title: imbue should not call rdbuf( )->pubimbue
Section: 27.4.4.2 **Member functions [lib.basic.ios.members]**
Status: **active**
Description:

basic_ios::imbue(const locale&) should call rdbuf( )->pubimbue(loc) only if rdbuf( ) is not a null pointer. Even better, it should not call rdbuf( )->pubimbue(loc) at all. Changing the locale that

controls stream conversions is best separated from changing the locale that affects numeric formatting, etc. Anyone who knows how to imbue a proper pair of codecvt facets in a streambuf won't mind having to make an explicit call.

Possible Resolution:

The first part of the issue has already been resolved, the description of function *locale imbue(const locale& loc)* says:

Effects: Calls ios_base::imbue(loc) (27.4.3.3) and if rdbuf( ) != 0 then rdbuf( )->pubimbue(loc) (27.5.2.2.1).

Concerning the second part you have two possibilities:

If we leave the basic_ios::imbue function unchanged, when users call the imbue function from basic_istream, basic_ostream or the classes derived from them, they are actually changing both the locale of the stream object, and the locale of the stream buffer object attached to the stream object. This is not a real problem, because the stream object is only affected by the ctype, num_get , num_put, and numpunct facets, while the stream buffer object is affected by the codecvt facet. Therefore, even if you want to have several stream pointing to the same stream buffer objects (with a different locale object for each of them), you can easily do it by having all the different stream locale objects having the same codecvt facet. You could also do it by imbuing the stream buffer at last. The advantage of this scheme is that in simple cases you need to imbue just once in the stream object without having to wonder about the stream buffer object attached to it. The drawback is that you need to be more careful when you imbue in a stream object, and make sure that the locale object you are imbuing contains the correct codecvt facet; otherwise, you need to imbue the stream buffer object attached to the stream with another locale.

The other possibility is to remove the call to rdbuf( )->pubimbue(loc), in which case you just imbue the stream object itself. The problem is that in simple cases you need to imbue both the stream object and the stream buffer attached to it. The advantage is you only imbue the object that needs to have a change of locale.

The pre-Stockholm Iostreams WG deferred the issue to Stockholm.

Requestor: Public Comment

Issue Number: 27-206
Title: clear() should not unconditionally clear the error state
Section: 27.4.4.3 **basic_ios iostate flags functions [lib.iostate.flags]**
Status: **active**
Description:

Problem: *clear()* can be used to unconditionally clear the error state, even if *rdbuf()*, returns null. The stream then appears to be in a good state, which is wrong.

Possible Resolution:

The function *clear()* should set badbit (independent of its argument) if *rdbuf()* returns null.

Note: This means *clear()* must not be moved to ios_base; it must remain in basic_ios.
Philippe Le Mouël will provide text for the WP.

Requestor: pre-Stockholm Iostreams WG

Issue Number: 27-207
Title: availability of char_traits in header ios (Box)
Section: 27.4.2 **Template struct ios_traits [lib.ios.traits]**
Status: **active**
Description:

The *ios_traits* was previously defined in header *ios*. Character traits have now been consolidated into *char_traits* defined in the string header. Should they still be available after a *#include<ios>*.

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

Issue Number: 27-208
Title: move member functions from basic_ios to ios_base (Box)
Section: 27.4.3 **Class ios_base [lib.ios.base]**
Status: **active**
Description:

Move the following declarations from basic_ios to ios_base:

// 27.4.4.3 iostate flags:
operator bool() const
bool operator! () const

iostate rdstate() const
void clear (iostate state = goodbit)
void setstate(iostate state)
bool good() const
bool eof() const
bool fail() const
bool bad() const

ios_base& copyfmt (const ios_base& rhs)

Note that there will be a version of copyfmt() specified for basic_ios.

Note: void clear (iostate state = goodbit) and void setstate(iostate state) should not be moved see issue 27-206.

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

Issue Number: 27-209
Title: imbueing getloc()::codecvt into the argument stream buffer (Box)
Section: 27.4.4.2 **Member functions [lib.basic.ios.members]**
Status: **active**
Description:

The first Box of section 27.4.4.2 says:

Note: need to modify so as to describe the occurrence of imbueing getloc()::codecvt into the argument stream buffer.

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

`basic_streambuf` issues

Issue Number: 27-301
Title: imbuing on streambufs: when, how often, etc...
Section: 27.5.2.2.1 **Locales [lib.streambuf.locales]**
Status: **active**
Description:

There needs to be something said as to when a new locale can be imbued into a streambuf or stream. Which operations are considered "atomic" in regards to locale changes.

Possible Resolution:

Nathan wrote:

"The effect of calling `imbue` during activation of any member of a class derived from `basic_ios<>`, or of any operator `<<` or `>>` in which the class is the left argument, is unspecified. In particular (e.g.) any `codeset` conversion occurring in the streambuf may become incompatible with the formats specified by the old locale and still used.

The effect of calling `streambuf::imbue` or `pub_imbue` during activation of any streambuf virtual member is also undefined."

The pre-Stockholm Iostreams WG recommends that no standard function defined in Chapter 27 calls imbue directly, except for the imbue function. If any user code (e.g. if called via a virtual function) calls imbue during the execution of any of these functions, the effect is undefined. Nathan Myers will provide text for the proposal.

Requestor: Nathan Myers (ncm@cantrip.org)

Issue Number: 27-312
Title: sync does not say what happens to the input sequence (Box)
Section: 27.5.2.4.2 **Buffer management and positioning [lib.streambuf.virt.buffer]**
Status: **active**
Description:

The description of function *sync* does not say what happens to the input sequence (if there is one).
Is it possible to synchronize the input sequence in all cases? If not, can we liberalize this specification to accommodate those constraints ?

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

---

basic_istream issues

Issue Number: 27-404
Title: istream functions need to check for NULL streambuf
Section: 27.6.1.1 **Template class basic_istream [lib.istream]**
Status: **active**
Description:

Functions in basic_istream that call members of rdbuf() need to check for a NULL streambuf before calling the function. There are some functions that make sure rdbuf() is not a NULL pointer before calling any functions on the buffer, but some functions don't check for the NULL pointer. This needs to be consistent.

Discussion:

P.J. Plauger wrote: "Any attempt to store a null stream buffer pointer causes badbit to be set in the stored status. Hence, no input or output is ever attempted, using such a pointer, by formatted functions."

Possible Resolution:

As pointed out by P.J. Plauger, we should add a footnote to explain why there is no need to check for a NULL streambuf.

We should also add, in section 27.4.4.2 **Member functions [lib.basic.ios.members],** the following to the description of basic_streambuf<charT,traits>* rdbuf(basic_streambuf<charT,traits>* sb); :

Postcondition: sb == rdbuf() and if sb is a NULL pointer rdstate() == badbit.

Note: This issue has to be discussed with issue 27-503.

The pre-Stockholm Iostreams WG recommends the issue to be treated as editorial. It needs to be pointed out where the check is not necessary. In places where check is required, recommend add the check. Jerry Schwarz will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-405
Title: confusing English in formatted requirements
Section: 27.6.1.2.1 **Common requirements [lib.istream.formatted.reqmts]**
Status: **active**
Description:

27.6.1.2.1 [lib.istream.formatted.reqmts]: Paragraph 5: "In case the converting result is a value of either an integral type ... or a float type ... performing to parse and convert the result depend on the imbued locale object." This is really French converted to English by translation software, right? :->}

Possible Resolution:

The pre-Stockholm Iostreams WG recommends closing the issue since the rewrite of the section fixed this problem.

Requestor: Public Comment

Issue Number: 27-406
Title: operator>>(char_type *) failure
Section: 27.6.1.2.2 **basic_istream::operator>> [lib.istream::extractors]**
Status: **active**
Description:

27.6.1.2.2 [lib.istream::extractors]: Paragraph 2: "If the function stores no characters, it calls setstate(failbit), which may throw ios_base::failure (27.4.4.3). In any case, it then stores a null character ...." How can it store anything if an exception is thrown? C++ does not use the resumption model for exception handling. Different language than "In any case" is needed here.

Possible Resolution:

Change paragraph 2 to:
"If the function stores no characters, it calls setstate(failbit), which may throw ios_base::failure (27.4.4.3)."

Add paragraph 3:
"Before returning or throwing an exception the function stores a null character into the next successive location of the array and calls width(0)."

Jerry Schwarz fixed the problem as editorial with the approval of the pre-Stockholm Iostreams WG. Therefore the issue should be closed.

Requestor: Public Comment

Issue Number: 27-407
Title: operator>>(char_type) failure
Section: 27.6.1.2.2 **basic_istream::operator>> [lib.istream::extractors]**
Status: **active**
Description:

basic_istream<charT,traits>& operator>>(char_type& c);
Effects: Extracts a character, if one is available, and stores it in c. Otherwise, the function calls setstate(failbit).

Not eofbit?

Possible Resolution:

In 27.6.1.2.1 **Common requirements [lib.istream.formatted.reqmts]** paragraph 8 says:

"If the scan fails for any reason, the formatted input function calls setstate(failbit), which may throw ios_base::failure (27.4.4.3)."

This is one of the requirements for all the formatted input functions. Because of this the user can call the ios_base member function fail( ) or the operator bool ( ) to check if the extraction failed. The user can therefore write code like this:

The pre-Stockholm Iostreams WG recommends closing the issue since the definition of “extract” (27.6.1.1) covers setting eof.
Note: footnotes could be added referring to that section. (Editorial)

Requestor: Public Comment

Issue Number: 27-408
Title: ws manipulator
Section: 27.6.1.4 **Standard basic_istream manipulators [lib.istream.manip]**
Status: **active**
Description:

27.6.1.4 [lib.istream.manip]: "... saves a copy of is.fmtflags ...."
Should this not read "... saves a copy of is.flags ...."?

Possible Resolution:

The pre-Stockholm Iostreams WG recommends a rewrite of the explanation. The intent is clear: Extracts any whitespace. Sets eof if eof is reached. Jerry Schwarz will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-409
Title: unsigned short extractors cannot use unsigned long get function
Section: 27.6.1.2.2 basic_istream ::operator>> **[lib.istream::extractors]**
Status: **active**
Description:

Unsigned short (and unsigned int) extractors cannot use unsigned long get function in num_get. It cannot distinguish certain valid inputs from errors.

Possible Resolution:

P.J. Plauger wrote: “num_get should add a get function (and underlying do get) for unsigned short and unsigned int extractions. Otherwise, input values in the range -1 through -USHRT_MAX (or -UINT_MAX) look erroneous, and cannot be distinguished from truly erroneous values.”

The pre-Stockholm Iostreams WG recommends closing the issue. These functions have been added to the WP, see 22.2.2.1 Template class num_get.

Requestor: P.J. Plauger (plauger!pjp@uunet.uu.net)

Issue Number: 27-410
Title: putback function has wrong description
Section: 27.6.1.3 Unformatted input functions **[lib.istream.unformatted]**
Status: **active**
Description:

The description of the putback function is incorrect.

Possible Resolution:

The complete description of the function should be:

basic_istream<charT,traits>& putback(char_type c);
Effects: If rdbuf( ) is not null, calls rdbuf( )->sputbackc(c). If rdbuf( ) is null, or if sputbackc(c) returns traits::eof( ), calls setstate(badbit) (which may throw ios_base::failure (27.4.4.3)).
Returns: *this.

Jerry Schwarz fixed the problem as editorial with the approval of the pre-Stockholm Iostreams WG. Therefore the issue should be closed.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-411
Title: getline should not set failbit when reading no characters
Section: 27.6.1.3 Unformatted input functions **[lib.istream.unformatted]**
Status: **active**
Description:

When the function getline is called and the stream has a line that contains no text, ios_base::failbit is set on the input stream (which may throw ios_base::failure). While consistent with the behavior of the similar function named get, the behavior is quite inconvenient. Furthermore, I tested this behavior on the AT&T Release 3.0 implementation of Iostreams and I did not encounter the problem described above. The same comment also apply to the string's getline function described in section 21.1.1.10.8 Inserters and extractors **[lib.string.io]**.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends changing the WP, if it does not say:
getline fails if no characters are extracted. An empty line is not a failure.
Jerry Schwarz will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-412
Title: operator >>(basic_streambuf *sb), should not set badbit if sb is null
Section: 27.6.1.2.2 basic_istream::operator >> **[lib.istream::extractors]**
Status: **active**
Description:

basic_istream::operator>>(basic_streambuf *sb) now says, ``If sb is null, calls setstate(badbit)." This requirement was added without committee approval. It is also inconsistent with the widespread convention that badbit should report loss of integrity of the stream proper (not some other stream). A null sb should set failbit.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends setting *failbit* not *badbit*.
Jerry Schwarz will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-413
Title: sentence missing (Box)
Section: 27.6.1.1 **Template class basic_istream [lib.istream]**
Status: **active**
Description:

X3J16/95-0149==WG21/N0749 deleted a sentence that prevented the formatted and unformatted input functions from calling other streambuf virtuals (such as seek).

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

Issue Number: 27-414
Title: readsome, putback and unget need to check for good (Box)
Section: 27.6.1.3 **Unformatted input functions [lib.istream.unformatted]**
Status: **active**
Description:

basic_istream::readsome, basic_istream::putback and basic_istream::unget should not call virtual if good() returns false.

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

Issue Number: 27-415
Title: streampos need to be replaced (Box)
Section: 27.6.1.3 **Unformatted input functions [lib.istream.unformatted]**
Status: **active**
Description:

tellg and *tellp* refer to the type *streampos* that has been moved to Annex D as per Monterey resolution 35. That resolution did not say what to do with the functions that use *streampos* as an argument type, so they are left here. (see 27-910)

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

---

basic_ostream issues

Issue Number: 27-501
Title: ostream<<(char) : formatting, padding, width
Section: 27.6.2.4.2 **basic_ostream::operator<< [lib.ostream.inserters]**
Status: active
Description:

For historical reasons, this function has usually ignored padding and formatting. In the WP, it does not mention anything about ignoring padding or formatting. This needs to be clarified.
Reasons for ignoring padding on op<<(char):

1. Historical reasons/compatibility

Reasons for full formatting on op<<(char):

1. put(char) currently does no formatting. But there is no way to insert a char with formatting.
2. Some implementations do formatting.

Since put can insert a character without formatting, there needs to be a way to insert a character with formatting. Currently this does not exist. It would be nice not to introduce an inconsistency with the other formatted inserters, but it would also be nice to provide compatibility. I think that consistency would be much better in this case than compatibility.

Possible Resolution:

At the Tokyo meeting the straw vote gave the following result:
5 for past practice (no padding), 1 for consistency.
The pre-Stockholm Iostreams WG deferred the issue to Stockholm.

Requestor: John Hinke (hinke@roguewave.com),
Bernd Eggink (admin@rrz.uni-hamburg.de)

Issue Number: 27-503
Title: ostream functions need to check for NULL streambuf
Section: 27.6.2.1 **Template class basic_ostream [lib.ostream]**
Status: **active**
Description:

Functions in basic_ostream that call members of rdbuf() need to check for a NULL streambuf before calling the function. There are some functions that make sure rdbuf() is not a NULL pointer before calling any functions on the buffer, but some functions don't check for the NULL pointer. This needs to be consistent.

Discussion:

P.J. Plauger wrote: "Any attempt to store a null stream buffer pointer causes badbit to be set in the stored status. Hence, no input or output is ever attempted, using such a pointer, by formatted functions."

Possible Resolution:

As pointed out by P.J. Plauger we should add a footnote to explain why there is no need to check for a NULL streambuf.
We should also add in section 27.4.4.2 **Member functions [lib.basic.ios.members]** the following to the description of basic_streambuf<charT,traits>* rdbuf(basic_streambuf<charT,traits>* sb); :

Postcondition: sb == rdbuf() and if sb is a NULL pointer rdstate() == badbit.

Note: This issue has to be discussed with issue 27-404.

The pre-Stockholm Iostreams WG recommends the issue to be treated as editorial. It needs to be pointed out where the check is not necessary. In places where check is required, recommend add the check. Jerry Schwarz will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-505
Title: incorrect conversion specifier for operator<<(unsigned long)
Section: 27.6.2.4.2 **basic_ostream::operator<< [lib.ostream.inserters]**
Status: **active**
Description:

basic_ostream<charT,traits>& operator<<(unsigned long n);
Effects: Converts the unsigned long integer n with the integral conversion specified preceded by l. Should this be "... preceded by ul."?

Possible Resolution:

The pre-Stockholm Iostreams WG recommends closing the issue, since the rewrite of this section fixed the problem.

Requestor: Public Comment

Issue Number: 27-506
Title: wrong default behavior for padding
Section: 27.6.2.4.1 Common requirements Table 13 Fill padding **[lib.ostream.formatted.reqmts]**
Status: **active**
Description:

27.6.2.4.1 Table13 Fill padding changes the long-standing default behavior for padding output field. It has always been true that setting none of left, right, and internal called for left padding (pad after text). Now it calls for right padding (pad before text). Since this is the initial state of all ios objects, many simple C++ programs will change behavior.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends closing the issue, since the rewrite and moving discussion of fill padding to chapter 22 (Localization) fixed the problem.

Requestor: P.J. Plauger (plauger!pjp@uunet.uu.net)

---

basic_istream/basic_ostream issues

Issue Number: 27-601
Title: istream::operator>>(ios_base&), ostream::operator<<(ios_base&)
Section: 27.6.1.2.2 **basic_istream::operator>> [lib.istream::extractors],** 27.6.2.4.2 **basic_ostream::operator<< [lib.ostream.inserters]**
Status: active
Description:

The ios_base manipulators 27.4.5.1**[lib.std.ios.manip]** will not work as written. They won't work because there is no conversion from ios_base to basic_ios.

They are currently declared as:
ios_base& boolalpha(ios_base&);

I propose adding a new insertor/extractor for istream and ostream that does insertion/extraction for ios_base.

Possible Resolution:

John wrote:

"Add to basic_istream:

basic_istream<charT, traits>& operator>>(ios_base& (*pf)(ios_base&));

Effects: Calls (*pf)(*this)
Returns: *this.

Add to basic_ostream:

basic_ostream<charT, traits>& operator<<(ios_base& (*pf)(ios_base&));

Effects: Calls (*pf)(*this)
Returns: *this.

Also, several footnotes will need to be changed."

We need to change footnote 9 in 27.4.5.3 **basefield manipulators [lib.basefield.manip]** to:

"The function signature dec(ios_base& str) can be called by the function signature basic_ostream<charT,traits>& basic_ostream<charT,traits>::operator << (ios_base& (*) (ios_base&)) to permit expressions of the form cout << dec to change the format flags stored in cout."

The pre-Stockholm Iostreams WG recommends accepting resolution in issues list.
Philippe Le Mouël will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-602

Title: positional typedefs in istream/ostream derived classes
Section: 27
Status: **active**
Description:

Remove the positional typedefs from the following classes. The positional typedefs are:

typedef traits::pos_type pos_type;
typedef traits::off_type off_type;

They are not used in the following classes:

basic_istringstream
basic_ostringstream
basic_ifstream
basic_ofstream

Possible Resolution:

John wrote:

"Remove them. They are still inherited from the base classes."

The pre-Stockholm Iostreams WG recommends closing the issue with no change to the WP.
It does not harm to leave in the typedefs, and probably they are required by language rules anyway.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-603
Title: istream::read, ostream::write
Section: 27.6.1.3 **Unformatted input functions [lib.istream.unformatted]**,
27.6.2.5 **Unformatted output functions [lib.ostream.unformatted]**
Status: **active**
Description:

basic_istream<charT,traits>& basic_istream<charT,traits>::read(char_type *,streamsize);
basic_ostream<charT,traits>& basic_ostream<charT,traits>::write(const char_type *,streamsize);

These functions are typically used for binary data.

Possible Resolution:

John wrote:

"These functions should take a void * instead of char_type *. If these functions are changed, then perhaps we should add another function that replaces this behavior. basic_istream currently has a get function, which behaves like the read and write functions. It would make sense to add a corresponding put function in basic_ostream that parallels the behavior of get."

The pre-Stockholm Iostreams WG recommends closing the issue with no change to the WP.
If *read/write* take void*, what does it mean to write bytes to a wide stream? Here it is clear that you always write sequences of charT to a stream.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-604
Title: Opening an istream without ios::in set? or an ostream without ios::out set?
Section: 27.6.1.1 **Template class basic_istream [lib.input.streams],**
27.6.2.1 **Template class basic_ostream [lib.output.streams]**
Status: **active**
Description:

Benedikt asks,

"Why can I open an istream without ios::in being set or an ostream without ios::out? I mean, I just did that by mistake with an ofstream and searched for quite a while to find out, why there were no actual writes to the newly created file.

"Or, even worse, why can I open an istream with ios::out (and no ios::in) being set and vice versa?

"Shouldn't the iostreams check whether the given mode flags make any sense, and maybe even add ios::in if you missed to set this in an istream, or ios::out if you used an ostream?"

Possible Resolution:

The pre-Stockholm Iostreams WG recommends that ctors/open for iXstream, oXstream always assumes the "in" or "out" bit. Ctors/open for Xstream (bidirectional) do not assume either "in" or "out" bits. Steve Clamage will provide text for the proposal.

Requestor: Benedikt Erik Heinen (beh@tequila.oche.de)

Issue Number: 27-605
Title: get/put type functions should be able to use iterators.
Section: 27.6.1.3 **Unformatted input functions [lib.istream.unformatted]**
27.6.2.5 **Unformatted output functions [lib.ostream.unformatted]**
Status: **active**
Description:

Several functions in istream and ostream take a pointer and a length and optionally a delimiter. It would be nice to add overloaded functions that take either InputIterators, or OutputIterators. These new functions would look like:

For basic_istream:

```
template<class OutputIterator>
istream& get(OutputIterator begin, OutputIterator end, char_type delim);
```

The *begin* and *end* iterators define where the characters will be written. Characters will be read from the sequence until the *end* iterator is reached, or the next character is *delim*.

For basic_ostream:

```
template<class InputIterator>
ostream& write(InputIterator begin, InputIterator end);
```

The *begin* and *end* iterators define the sequence of characters to be written.

These functions would be added to the current implementation. The current set of functions should not be removed. They are very commonly used. There are several functions which are candidates for these *begin* and *end* iterators. These functions are:

For basic_istream:

```
istream& get(char_type *, streamsize, char_type);
istream& getline(char_type *, streamsize, char_type);
istream& read(char_type *, streamsize);
```

For basic_ostream:

```
ostream& put(char_type *, streamsize);
ostream& write(void *, streamsize);
```

Possible Resolution:

The pre-Stockholm Iostreams WG recommends closing the issue with no change to the WP. This is a proposed extension.

Requestor: Nathan Myers (ncm@cantrip.org)

Issue Number: 27-606
Title: seekg and seekp should have their first parameter passed by value.
Section: 27.6.1.3 **Unformatted input functions [lib.istream.unformatted]**
27.6.2.3 **basic_ostream prefix and suffix functions [lib.ostream.prefix]**
Status: **active**
Description:

The following functions should have their first parameter passed by value as described in 27.6.1.1 **Template class basic_istream [lib.istream]** and 27.6.2.1 **Template class basic_ostream [lib.ostream].**

```
basic_istream<charT,traits>& seekg(off_type& off, ios_base::seekdir dir);
basic_ostream<charT,traits>& seekp(pos_type& pos);
basic_ostream<charT,traits>& seekp(off_type& off, ios_base::seekdir dir);
```

The seekp functions should also be moved in section 27.6.2.5 **Unformatted output functions [lib.ostream.unformatted].**

Possible Resolution:

Change them to:

```
basic_istream<charT,traits>& seekg(off_type off, ios_base::seekdir dir);
basic_ostream<charT,traits>& seekp(pos_type pos);
basic_ostream<charT,traits>& seekp(off_type off, ios_base::seekdir dir);
```

The pre-Stockholm Iostreams WG recommends treating the issue as editorial. Steve Clamage will provide text to make the declaration and definition agree to pass parameter by value.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-607
Title: locale getnum needed for void* extractor (Box)
Section: 27.6.1.2.3 **basic_istream::operator>> [lib.istream::extractors]**
Status: **active**
Description:

The description of void* extractor needs work. Maybe there should be a locale getnum for it. (Using %p conversion specifier).

Possible Resolution:

Requestor: pre-Stockholm Iostreams WG

Standard manipulators issues

Issue Number: 27-651
Title: setfill description is wrong
Section: 27.6.3 Standard manipulators **[lib.std.manip]**
Status: **active**
Description:

P.J. Plauger wrote: "Setfill description is nonsense, since a fill character is now a charT, which cannot necessarily be represented as type int. Nor can it be applied to ios_base, since the fill character now inhabits basic_ios."

Possible Resolution:

The pre-Stockholm Iostreams WG deferred the issue to Stockholm.
The problem is which parameter type(s) should the *setfill* manipulator accept. Certainly charT, but what about char or int? Problem is lack of a correct implicit "widen" from char to charT, because the conversion requires knowledge of the locale.

Requestor: P.J. Plauger (plauger!pjp@uunet.uu.net)
Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-652
Title: smanip is not a single type
Section: 27.6.3 Standard manipulators **[lib.std.manip]**
Status: **active**
Description:

P.J. Plauger wrote: "Description of manipulators strongly suggests that smanip is a single type. It was supposed to make clear that each manipulator can return a different type, as needed. (And more than one type is certainly needed here.)"

Possible Resolution:

The pre-Stockholm Iostreams WG recommends treating the issue as editorial. Jerry Schwarz will provide wording, along the lines of:
Returns: A value of some class lsmanip such that *out* << *resetiosflags(m)* has the effect of *out.setf(0,m).*

Requestor: P.J. Plauger (plauger!pjp@uunet.uu.net)
Philippe Le Mouël (philippe@roguewave.com)

---

string stream issues

Issue Number: 27-701
Title: basic_stringbuf::str() needs to clarify return value on else clause
Section: 27.7.1.2 **Member functions [lib.stringbuf.members]**
Status: **active**
Description:

"Table 15 in [lib.stringbuf.members] describes the return values of basic_stringbuf::str(). What does the "otherwise" mean?. Does it mean neither ios_base::in nor ios_base::out is set? What is the return value supposed to be if _both_ bits are set?"

Possible Resolution:

My understanding is that if both ios_base::in and ios_base::out are set, you should return basic_string<char_type>(eback(),egptr()-eback()). I propose to change the **Returns:** clause to clarify this fact.

Returns: The return values of this function are indicated in Table 15 and the test that determine these values are carried out in the order shown in Table 15.

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: Angelika Langer (langer@roguewave.com)
Bernd Eggink (admin@rrz.uni-hamburg.de)

Issue Number: 27-702
Title: string streams need allocator and string_char_traits parameters
Section: 27.7.1 **Template class basic_stringbuf [lib_stringbuf]**
Status: **active**
Description:

The string streams are currently templatized on the character type (charT) and the traits type (ios_traits). String template parameters need to be added.

Possible Resolution:

The Santa Cruz meeting, fixes the problem, by accepting doc: 96-0036R1=N0854R1 (Unification of Traits Revision1). But we are still left with the problem of taking or returning string arguments using an other allocator than the default one. See *basic_stringbuf* , *basic_istringstream*, *basic_ostringstream* and *basic_stringstream* constructors and *str* functions.

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-703
Title: stringbuf postconditions
Section: 27.7.1.2 **Member functions [lib.stringbuf.members]**
Status: **active**
Description:

basic_stringbuf::str(basic_string s) Postconditions requires that str() == s. This is true only if which had in set at construction time. Condition should be restated.

Possible Resolution:

I think the real problem is in "Table 16 - str get/set areas". Its second line says:

(which & ios_base::out) != 0 setp(str(),str(),str()+str.size())

First, the function setp takes only two parameters. Furthermore it should say:

(which & ios_base::out)!= 0 setp(str(),str()+s.size())
then if: (which & (ios_base::app | ios_base::ate))!=0 pbump(s.size())

Then the postcondition requiring that str() == s in the function void str(const basic_string<char_type>& s) will be valid if "in" or "out" and "app" or "ate" are set at construction time.

Table 16 should be changed to:

Table 16—str get/set areas

Condition	Setting
(which & ios_base::in)!=0	setg(str(), str(), str()+s.size())
(which & ios_base::out)!=0	setp(str(),str()+s.size())
(which & (ios_base::app | ios_base::ate))!=0	pbump(s.size())

The postcondition should be changed to:

Postcondition: if ios_base::in, or ios_base::out and ios_base::app or ios_base::ate are set at construction time, then str()==s. Otherwise str() == basic_string<char_type>(). If s.size() >0, set the get and/or put pointers as indicated in Table 16.

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-704
Title: stringbuf::stringbuf constructor
Section: 27.7.1.1 **basic_stringbuf constructors [lib.stringbuf.cons]**
Status: **active**
Description:

basic_stringbuf::basic_stringbuf(basic_string str, openmode which) Postconditions requires that str() == str. This is true only if which has in set. Condition should be restated.

Possible Resolution:

This is the same problem described in issue 27-703.

The real problem is in "Table 14 - str get/set areas". The second line says:

(which & ios_base::out) != 0 setp(str(),str(),str()+str.size())

First, the function setp takes only two parameters. Furthermore it should say:

(which & ios_base::out)!= 0 setp(str(),str()+str.size())
then if: (which & (ios_base::app | ios_base::ate))!=0 pbump(str.size())

Then the postcondition requiring that str() == str in the function basic_stringbuf:: basic_stringbuf(basic_string str, openmode which) will be valid if "in" or "out" and "app" or "ate" are set.

Table 14 should be changed to:

Table 14—str get/set areas

Condition	Setting
(which & ios_base::in)!=0	setg(str(), str(), str()+str.size())
(which & ios_base::out)!=0	setp(str(),str()+str.size())
(which & (ios_base::app | ios_base::ate))!=0	pbump(str.size())

The postcondition should be changed to:

Postcondition: if ios_base::in, or ios_base::out and ios_base::app or ios_base::ate are set at construction time, then str()==str. Otherwise str() == basic_string<char_type>(). If str.size() >0, set the get and/or put pointers as indicated in Table 14.

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-705
Title: Incorrect calls to setg and setp in Table 14
Section: 27.7.1.1 **basic_stringbuf constructors [lib.stringbuf.cons]**
Status: **active**
Description:

Table 14 describes calls to setg and setp with string arguments, for which no signature exists. Needs to be recast.

Possible Resolution:

Possible Resolution of issue 27-704 solves this problem.

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-706
Title: Incorrect calls to setg and setp in table 16
Section: 27.7.1.2 **Member functions [lib.stringbuf.members]**
Status: **active**
Description:

Table 16 describes calls to setg and setp with string arguments, for which no signature exists. Needs to be recast.

Possible Resolution:

Possible Resolution of issue 27-703 solves this problem

The pre-Stockholm Iostreams WG recommends defining a consistent model for stringstreams. Should stringbufs be more like filebufs or more like strstreams? Probably more like files. The String stream section needs a full review and possibly some rewriting to fit the model. Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-707
Title: setbuf function is missing
Section: 27.7.1 **Template class basic_stringbuf [lib.stringbuf]**
Status: **active**
Description:

Steve Clamage wrote: “Section 27.7.1.3 should have a basic_stringbuf override of the base class setbuf() function, but it is missing.”

Possible Resolution:

Add the following description in 27.7.1 **Template class basic_stringbuf [lib.stringbuf]** and 27.7.1.3 **Overridden virtual functions [lib.stringbuf.virtuals]**:

basic_streambuf<charT,traits>* setbuf(char_type* s, int n);

Effects: If *(mode & ios_base::out)* is true, proceed as follows:
If *s* is not a null pointer, and n > pptr() - pbase(), replace the current buffer (copy its contents and deallocate it) by the buffer of size *n* pointed at by *s*.
In the case where *s* is a null pointer, and n > pptr() - pbase() resize the current buffer to size *n*.
If the function fails, it returns a null pointer.
Returns: (basic_streambuf<charT,traits>*)(this)

I am not qualified enough to decide if the return type should be changed to basic_stringbuf<charT,traits>* as proposed by Steve Clamage in issue 27-809. I tried it with several compilers, and the results were just error messages. Basically, the compilers were complaining about the fact that the base class virtual function and the overridden virtual function should have the same return type.

The pre-Stockholm Iostreams WG recommends the behavior of the *setbuf* function to be implementation-defined, except that setbuf(0,0) has no effect. The return type in the WP is coreect. Steve Clamage will provide text for the proposal.

Requestor: Steve Clamage (stephen.clamage@eng.sun.com)

file stream issues

Issue Number: 27-801
Title: filebuf::underflow example
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

The "as if" example for basic_filebuf::underflow has several "typos". It should say:

```
char    from_buf[FSIZE};
char*   from_end;
char    to_buf[TSIZE};
char*   to_end;
typename traits::state_type st;

codecvt_base::result r =
      getloc().template use<codecvt<char, charT,
      typename traits::state_type> >().convert
      (st, from_buf, from_buf+FSIZE, from_end,
      to_buf, to_buf+TSIZE, to_end);
```

Possible Resolution:

We should correct the example as follows, and not as described above:

```
char    from_buf[FSIZE};
char*   from_end;
charT    to_buf[TSIZE};
charT*   to_end;
typename traits::state_type st;

codecvt_base::result r=
  use_facet<codecvt<char,charT,typename traits::state_type> >(getloc()).
     convert(st,from_buf,from_buf+FSIZE,from_end,to_buf,to_buf+TSIZE,to_end);
```

Should be treated with issue 27-812.

The pre-Stockholm Iostreams WG recommends to treat the issue as editorial. The modifications have already been incorporated to the WP.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-802
Title: filebuf::is_open is a bit confusing
Section: 27.8.1.3 **Member functions [lib.filebuf.members]**
Status: **active**
Description:

It says, "**Returns:** true if the associated file is available and open." What is the meaning of available? This seems a bit confusing.

Possible Resolution:

Change the **Returns:** statement to:

Returns: true after a successful call to the member function open, and before a successful call to member function close, otherwise false.

The pre-Stockholm Iostreams WG recommends accepting the above resolution. Jerry Schwarz will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com),
Bob Kline (bkline@cortex.nlm.nih.gov)

Issue Number: 27-803
Title: ofstream constructor missing trunc as openmode
Section: 27.8.1.9 **basic_ofstream constructors [lib.ofstream.cons]**
Status: **active**
Description:

basic_ofstream::basic_ofstream(const char *s, openmode mode = out) has wrong default second argument. It should be `out | trunc', the same as for basic_ofstream::open (in the definition at least).

Possible Resolution:

In 27.8.1.9 **basic_ofstream constructors [lib.ofstream.cons]** change:

explicit basic_ofstream(const char* s, openmode mode = out);

to:

explicit basic_ofstream(const char* s, ios_base::openmode mode = ios_base::out | ios_base::trunc);

In 27.8.1.10 **Member functions [lib.ofstream.members]** change:

void open(const char* s, openmode mode = out);

to:

void open(const char* s, ios_base::openmode mode = ios_base::out | ios_base::trunc);

The pre-Stockholm Iostreams WG recommends fixing the words and Table 14 to show that “out” by itself is equivalent to “out | trunc”. Then “out | trunc” can be changed to “out” everywhere as editorial. All possible combinations of flags should be considered and given a meaning or declared invalid or undefined. Steve Clamage will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-804
Title: ofstream::open missing trunc in openmode
Section: 27.8.1.10 **Member functions [lib.ofstream.members]**

Status: **active**
Description:

basic_ofstream::open(const char *s, openmode mode = out) has wrong default second argument. It should be `out | trunc', the same as for basic_ofstream::open in the definition.

Possible Resolution:

See issue 27-803.

Requestor: Public Comment

Issue Number: 27-805
Title: filebuf::imbue semantics
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

basic_filebuf::imbue has silly semantics. Whether or not sync() succeeds has little bearing on whether you can safely change the working codecvt facet. The most sensible thing is to establish this facet at construction. (Then pubimbue and imbue can be scrubbed completely.) Next best is while is_open() is false. (Then imbue can be scrubbed, since it has nothing to do.) Next best is to permit any imbue that doesn't change the facet or is at beginning of file. Next best is to permit change of facet any time provided either the current or new facet does not mandate state-dependent conversions. (See comments under seekoff.)

Possible Resolution:

In my current version of the WP, I do not have any description for the virtual filebuf imbue function. See issue 27-814.

The pre-Stockholm Iostreams WG deferred the issue to Stockholm.

Requestor: Public Comment

Issue Number: 27-806
Title: filebuf::seekoff **Effects:** clause needs work
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

basic_filebuf::seekoff Effects is an interesting exercise in creative writing. It should simply state that if the stream is opened as a text file or has state-dependent conversions, the only permissible seeks are with zero offset relative to the beginning or current position of the file. (How to determine that predicate is another matter -- should state for codecvt that even a request to convert zero characters will return noconv.) Otherwise, behavior is largely the same as for basic_stringstream, from whence the words should be cribbed. The problem of saving the stream state in a traits::pos_type object remains unsolved. The primitives described for ios_traits are inadequate.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends accepting in principle the recommendations in the public comment. Eight bit streams behave like stdio FILEs. For wide streams, seeks are allowed provided the external file meets certain criteria to be worked out by Tom Plum, who will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-807
Title: filebuf::underflow performance questions
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

basic_filebuf::underflow is defined unequivocally as the function that calls codecvt, but there are performance advantages to having this conversion actually performed in uflow. If the specification cannot be broadened sufficiently to allow either function to do the translation, then uflow loses its last rationale for being added in the first place. Either the extra latitude should be granted implementors or uflow should be removed from basic_streambuf and all its derivatives.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends that *filebuf* overrides both *uflow* and *underflow*, instead of just *underflow*. Semantic are left as-is. Jerry Schwarz will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-808
Title: Editorial fixes in wording for fstreams
Section: 27.8.1 **File streams [lib.fstreams]**
Status: **active**
Description:

27.8.1 [lib.fstreams], paragraph 2: "... the type name FILE is a synonym for the type FILE." This seems like an odd sort of synonym, doesn't it? Also, the last sentence of this subsection, "Because of necessity of the conversion between the external source/sink streams and wide character sequences." is incomplete.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends to treat the issue as editorial. Make clear that FILE is a typedef in C, but not necessarily in C++. The change as already been incorporated.

Requestor: Public Comment

Issue Number: 27-809
Title: Description of function setbuf is missing
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

Steve Clamage wrote: “basic_filebuf version of setbuf( ) needs a description, and the return type shown in the draft is basic_streambuf*, which is probably wrong. It was correct before covariant return types were added to the draft. Now it should probably return basic_filebuf*.”

Possible Resolution:

Add the following description in 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**:

basic_streambuf<charT,traits>* setbuf(char_type* s, streamsize n);

Effects: If *s* is not a null pointer, flush the buffer by calling *overflow(traits::eof())* and if the return value is not *traits::eof()*, deallocate the current buffer and replace it by the buffer of size *n* pointed at by *s*.
In the case where *s* is a null pointer, resize the current buffer to size *n* (this can result in flushing the buffer).
If the function fails, it returns a null pointer.
Returns: (basic_streambuf<charT,traits>*)(this)

I am not qualified enough to decide if the return type should be changed or not as proposed by Steve Clamage. I tried it with several compilers, and the results were just error messages. Basically, the compilers were complaining about the fact that the base class virtual function and the overridden virtual function should have the same return type.

The pre-Stockholm Iostreams WG recommends the behavior of the *setbuf* function to be implementation-defined, except that setbuf(0,0) if called before any I/O occurs on the stream, makes the stream unbuffered. The return type in the WP is coreect. Steve Clamage will provide text for the proposal.

Requestor: Steve Clamage (stephen.clamage@eng.sun.com)

Issue Number: 27-810
Title: Openmode notation is not consistent in basic_ifstream and basic_ofstream
Section: 27.8.1.5 **Template class basic_ifstream [lib.ifstream]**
27.8.1.8 **Template class basic_ofstream [lib.ofstream]**
Status: **active**
Description:

basic_ifstream, basic_ofstream *constructors* and member functions *open* describe the type ios_base::openmode as openmode and its values as *in* and *out* rather than *ios_base::in* and *ios_base::out* as everywhere else in the library.

Possible Resolution:

In 27.8.1.5 **Template class basic_ifstream [lib.ifstream]** , 27.8.1.6 **basic_ifstream constructors [lib.ifstream.cons]** and 27.8.1.7 **member functions [lib.ifstream.members]** change the following functions:

explicit basic_ifstream(const char* s, openmode mode = in);
to:
explicit basic_ifstream(const char* s, ios_base::openmode mode = ios_base::in);

void open(const char* s, openmode mode = in);
to:
void open(const char* s, ios_base::openmode mode = ios_base::in);

In 27.8.1.8 **Template class basic_ofstream [lib.ofstream]** , 27.8.1.9 **basic_ofstream constructors [lib.ofstream.cons]** and 27.8.1.10 **member functions [lib.ofstream.members]** change the following functions:

explicit basic_ofstream(const char* s, openmode mode = out | trunc);

to:

explicit basic_ofstream(const char* s, ios_base::openmode mode = ios_base::out | ios_base::trunc);

void open(const char* s, openmode mode = out | trunc);

to:

void open(const char* s, ios_base::openmode mode = ios_base::out | ios_base::trunc);

The pre-Stockholm Iostreams WG recommends to treat as editorial. The "trunc" issue is handled by 27-803,804.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-811
Title: Description of function sync is missing
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

Description of the overridden sync( ) function in class basic_filebuf is missing.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends adapting wording from C standard for output. The intent is clear, for in/out files, flush output then really seek to current file position. For input files, implementation-defined. Tom Plum will provide text for the proposal.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-812
Title: filebuf::overflow example is incorrect
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

The "as if" example for basic_filebuf::overflow has several "typos". It should say:

```
charT* b = pbase();
charT* p = pptr();
charT* end;
char      buf[BSIZE];
char*   ebuf;
typename traits::state_type st;

codecvt_base::result r=
  use_facet<codecvt<charT,char,typename traits::state_type> >(getloc()).
    convert(st,b,p,end,buf,buf+BSIZE,ebuf);
```

Possible Resolution:

Should be treated with issue 27-801.

The pre-Stockholm Iostreams WG recommends to treat the issue as editorial. The modifications have already been incorporated to the WP.

Requestor: Public Comment

Issue Number: 27-813
Title: basic_filebuf::overflow does not specifies its return value on success
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

The function basic_filebuf::overflow does not specifies its return value on success.

Possible Resolution:

The **Returns:** clause should be changed to:

Returns: If *traits::eq_int_type(c, traits::eof())* returns false, the function signals success by returning *c*. Otherwise If *traits::eq_int_type(c, traits::eof())* returns true, the function signals success by returning *traits::not_eof(c).* The function returns *traits::eof()* to indicate failure.

The pre-Stockholm Iostreams WG recommends to return not_eof(c) on success. Jerry Schwarz will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-814
Title: basic_filebuf::imbue has no description
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

The virtual function basic_filebuf::imbue has no description.

Possible Resolution:

The pre-Stockholm Iostreams WG deferred the issue to Stockholm.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-815
Title: description of function seekpos is missing
Section: 27.8.1.4 **Overridden virtual functions [lib.filebuf.virtuals]**
Status: **active**
Description:

basic_filebuf::seekpos has no sementics. Needs to be supplied.

Possible Resolution:

The pre-Stockholm Iostreams WG recommends that the function sets the file position to value of its argument, which must have come from seekoff(0). Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-816
Title: (i)(o)fstream open functions should not use is_open
Section: 27.8.1.7 **Member functions [lib.ifstream.members]**
27.8.1.10 **Member functions [lib.ofstream.members]**
Status: **active**
Description:

(i)(o)fstream *open* functions should not use *is_open* to determine if the operation fails (and as a result setting *failbit*). The problem arises if you do not close the (i)(o)fstream and then try to open another file with it. In this case the *filebuf open* function will fail, but *is_open* will still return true.

Possible Resolution:

The Effects: clause for *open* should be changed to:

Effects: Calls *Rdbuf()->open(s,mode).* If that function returns a null pointer, calls *Setstate(failbit)* (which may throw *ios_base::failure).*

Note: What about (i)(o)fstream constructors ? failbit should be set in the case they fail to open the file.

The pre-Stockholm Iostreams WG recommends accepting the above resolution. Philippe Le Mouël will provide text for the proposal.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Miscellaneous issues

Issue Number: 27-901
Title: input/output of unsigned charT
Section: 27
Status: **active**
Description:

NOTE: istream here means basic_istream.
ostream here means basic_ostream.

This issue details all of the issues with inserting or extracting characters.

Currently, IOStreams does not allow the insertion/extraction of unsigned charT or signed charT. There are two types of functions that could insert or extract these character types: formatted IO, and unformatted IO. Formatted IO use overloaded operators. Example:

```
istream& istream::operator>>(charT&);
ostream& ostream::operator<<(charT);
```

Examples of unformatted IO are:

```
istream& istream::get(charT *, streamsize, charT);
int_type ostream::put(charT);
```

This does not allow us to overload on unsigned charT. We can make the formatted operators global, and then overload ("specialize") on char, and wchar_t, but that doesn't solve the unformatted problem.

There is also a problem of inserting or extracting wide-characters from a skinny stream or skinny characters from a wide-stream:

```
char    c;
wchar_t wc;

cout << wc;
wcout << c;
```

Possible Resolution:

The pre-Stockholm Iostreams WG deferred the issue to Stockholm.

See papers: X3J16/96-0100 WG21/N0918 and X3J16/96-0101 WG21/N0919

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-904
Title: iosfwd declarations: incomplete
Section: 27.2 **Forward declarations [lib.iostream.forward]**
Status: **active**
Description:

The list of forward declarations is incomplete. Should it contain all of the forward declarations available? Forward declarations for template classes basic_ios, basic_istream, and basic_ostream should have two class parameters, not one. It is equally dicey to define ios, istream, etc. by writing just one parameter for the defining classes. All should have the second parameter supplied, which suggests the need for a forward reference to template class ios_char_traits as well, or at least the two usual specializations of that class.

Possible Resolution:

Replace "**Header <iosfwd> synopsis"** by:

```
namespace std {
        template<class charT> struct char_traits;
        template<class charT, class traits = char_traits<charT> > class basic_ios;
        template<class charT, class traits = char_traits<charT> > class basic_streambuf;
        template<class charT, class traits = char_traits<charT> > class basic_istream;
        template<class charT, class traits = char_traits<charT> > class basic_ostream;
        template<class charT, class traits = char_traits<charT> > class basic_iostream;
        template<class charT, class traits = char_traits<charT> > class basic_stringbuf;
        template<class charT, class traits = char_traits<charT> > class basic_istringstream;
        template<class charT, class traits = char_traits<charT> > class basic_ostringstream;
        template<class charT, class traits = char_traits<charT> > class basic_stringstream;
        template<class charT, class traits = char_traits<charT> > class basic_filebuf;
        template<class charT, class traits = char_traits<charT> > class basic_ifstream;
        template<class charT, class traits = char_traits<charT> > class basic_ofstream;
        template<class charT, class traits = char_traits<charT> > class basic_fstream;
        template<class charT, class traits= char_traits<charT> >  class ostreambuf_iterator;
        template<class charT, class traits= char_traits<charT> >  class istreambuf_iterator;

        typedef basic_ios<char>                 ios;
        typedef basic_streambuf<char>           streambuf;
        typedef basic_istream<char>             istream;
        typedef basic_ostream<char>             ostream;
        typedef basic_iostream<char>            iostream;
        typedef basic_stringbuf<char>           stringbuf;
        typedef basic_istringstream<char>       istringstream;
        typedef basic_ostringstream<char>       ostringstream;
        typedef basic_stringstream<char>        stringstream;
        typedef basic_filebuf<char>             filebuf;
        typedef basic_ifstream<char>            ifstream;
        typedef basic_ofstream<char>            ofstream;
        typedef basic_fstream<char>             fstream;
        typedef basic_ios<wchar_t>              wios;
        typedef basic_streambuf<wchar_t>        wstreambuf;
        typedef basic_istream<wchar_t>          wistream;
        typedef basic_ostream<wchar_t>          wostream;
        typedef basic_iostream<wchar_t>         wiostream;
        typedef basic_stringbuf<wchar_t>        wstringbuf;
        typedef basic_istringstream<wchar_t>            wistringstream;
        typedef basic_ostringstream<wchar_t>            wostringstream;
        typedef basic_stringstream<wchar_t>     wstringstream;
        typedef basic_filebuf<wchar_t>          wfilebuf;
```

```
typedef basic_ifstream<wchar_t>        wifstream;
typedef basic_ofstream<wchar_t>        wofstream;
typedef basic_fstream<wchar_t>         wfstream;

}
```

The pre-Stockholm Iostreams WG recommends adding decls for streampos (see 27-910). Nathan Myers will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-906
Title: add a typedef to access the traits parameter for a class.
Section: 27
Status: **active**
Description:

Some classes; such as istream don't have access to the traits template parameter. Perhaps each class should provide a typedef for the traits parameter.

You need the traits parameter when you want to say stuff like:

```
cin.ignore(100, traits::newline(use_facet<ctype<cin.char_type> >(cin.getloc()) )
```

There is no way to get the traits type without saying something like: ios_traits<cin.char_type> which is almost reasonable, but it would be nicer to say something like: cin::traits_type. There are some cases where ios_traits is not the traits used to instantiate the stream.

Possible Resolution:

The Tokyo meeting recommends acceptance of the following:

Add "typedef traits traits_type;" to basic_ios and basic_streambuf.

Where traits is the template parameter

The pre-Stockholm Iostreams WG recommends accepting the above resolution. Nathan Myers will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-907
Title: Use of "instance of" vs. "version of" in descriptions of class ios
Section: 27.2 **Forward declarations [lib.iostream.forward]**
Status: **active**
Description:

Paragraph 2 and 3 describe the class ios and the class wios. One is described as "an instance of the template..." the other is described as "a version of the template...".

Possible Resolution:

Change paragraph 3 to:

"The class wios is an instance of the template class basic_ios, specialized by the type wchar_t"

Jerry Schwarz fixed the problem as editorial with the approval of the pre-Stockholm Iostreams WG. Therefore the issue should be closed.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-908
Title: unnecessary ';' (semicolons) in tables
Section: 27
Status: **active**
Description:

There are unnecessary semicolons in tables in chapter 27. These probably should be removed.

Possible Resolution:

The only semicolons I can find are in section 27.1.2.6 **Type POS_T [lib.iostreams.pos.t]** "Table 2-Position type requirements".

Jerry Schwarz fixed the problem as editorial with the approval of the pre-Stockholm Iostreams WG. Therefore the issue should be closed.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-909
Title: Editorial issues (typo's)
Section: 27
Status: **active**
Description:

Here are a list of "typo's" and other possible editorial issues.

Editorial Issue #1

Description:
27.4.4.3 basic_ios iostate flags functions [lib.iostate.flags]
The description of ios_base::exceptions is listed under the basic_ios clause.

Possible Resolution:
This needs to be moved back to the ios_base clause.

Jerry Schwarz fixed the problem as editorial with the approval of the pre-Stockholm Iostreams WG. Therefore the issue should be closed.

Editorial Issue #2

Description:
27.1.2.4 **Type POS_T [lib.iostreams.pos.t]**
Description of type POS_T contains many awkward phrases. Needs rewriting for clarity.

The pre-Stockholm Iostreams WG declared the issue moot.

Editorial Issue #3

Description:
27.1.2.3 **Type OFF_T [lib.iostreams.off.t]**
Footnote 1 should say ``for one of'' instead of ``for one if.'' Also, it should``whose representation has at least'' instead of ``whose representation at least.''

The pre-Stockholm Iostreams WG recommends treating as editorial.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-910
Title: remove streampos in favor of pos_type
Section: 27
Status: **active**
Description:

There are editorial boxes in Chapter 27 that say that streampos was deprecated but no resolution on what to do with functions that use it as an argument type has been offered.

Possible Resolution:

John wrote: “Change all references to streampos as an argument type to pos_type. Each class in Chapter 27 has a typedef for, or access to, pos_type.”

My understanding is that we should add back streampos, has being the pos_type used on streams instantiated on tiny characters. We also need to replace all the references to streampos by references to pos_type throughout the iostreams chapter (when streams are instantiated on char, pos_type == streampos).

The pre-Stockholm Iostreams WG recommends accepting the above resolution, and adding streampos to <iosfwd>. Tom Plum will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-911
Title: stdio synchronization
Section: 27.3.1 Narrow stream objects [**lib.narrow.stream.objects**]
Status: **active**
Description:

Doing measurements on the performance of streambufs attached to stdin on a variety of systems, I found that the performance of a simple loop:

```
while ((c = cin.get()) != EOF) ...
```

was from 5 to 20 times slower than the equivalent

```
while ((c = getc(stdin)) != EOF) ...
```

To my horror, I found that this is a result of a mandate in the WP, that stdin and cin (and also stdout and cout) must be synchronized. As a goal this seems laudable, but if the consequence in many (most) environments is either:

1. an order of magnitude slower input, or

2. breaking link compatibility with C,

maybe we should reconsider this choice, and instead allow-but-not-require that the two be synchronized.

Possible Resolution:

Nathan wrote:

"One possibility would be to reintroduce "sync_with_stdio" but give it a boolean argument. sync_with_stdio(true) would cause syncronization, while sync_with_stdio(false) would cause unsyncronization.

This would be agreeable to me. I take it this would be a static member of ios_base? How would it default? I assume that the call with false could be a no-op."

The pre-Stockholm Iostreams WG recommends that synchronization should be the default (status quo). Nathan Myers will write a proposal about adding in synch/unsynch functions, and will discuss when synch/unsynch can be called.

Requestor: Nathan Myers (ncm@cantrip.org)

Issue Number: 27-912
Title: removing **Notes:** from the text
Section: 27
Status: **active**
Description:

This issue is in response to Mats Meta list. It is an attempt to remove normative text from the WP. This issue removes **Notes:** from the text. Some **Notes:** clauses that need to be incorporated into the text will be handled in another issue.

Remove all **Notes:** clauses from the following:

27.4.2.1 ios_traits value functions [lib.ios.traits.values]
int_type not_eof(char_type c)

27.4.3.4 ios_base storage functions [lib.ios.base.storage]
void * & pword(int idx)

27.5.2.2.3 Get area [lib.streambuf.pub.get]
int_type snextc()

27.5.2.4.3 Get area [lib.streambuf.virt.get]
int showmanyc()

27.5.2.4.3 Get area [lib.streambuf.virt.get]
streamsize xsgetn(char_type *_s_, streamsize _n_)

27.6.1.2.2 basic_istream::operator>> [lib.istream::extractors]
basic_istream<charT, traits>& operator>>(char_type *_s_)

27.7.1.3 Overridden virtual functions [lib.stringbuf.virtuals]

int_type pbackfail(int_type *c*)

27.7.1.3 Overridden virtual functions [lib.stringbuf.virtuals]
int_type overflow(int_type *c*)

27.8.1.4 Overridden virtual functions [lib.filebuf.virtuals]
int showmanyc()

Possible Resolution:

The pre-Stockholm Iostreams WG recommends that Non-normative notes to "[Note:" style, change normative "Notes" to some other heading word. Jerry Schwarz will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-913
Title: Incorporating **Notes:** into the text
Section: 27
Status: **active**
Description:

The following **Notes:** clauses need to be incorporated into the WP text:

27.5.2.1 basic_streambuf constructors [lib.streambuf.cons]
basic_streambuf()

27.5.2.4.1 Locales [lib.streambuf.virt.locales]
void imbue(const locale&)

27.5.2.4.3 Get area [lib.streambuf.virt.get]
int_type underflow()

27.5.2.4.4 Putback [lib.streambuf.virt.pback]
int_type pbackfail(int *c*)

27.5.2.4.5 Put area [lib.streambuf.virt.put]
int_type overflow(int_type *c*)

27.6.1.1.1 basic_istream constructors [lib.basic.istream.cons]
virtual ~basic_istream()

27.6.1.2.2 basic_istream::operator>> [lib.istream::extractors]
basic_istream<charT, traits>& operator>>(bool& *n*)

27.6.1.3 Unformatted input functions [lib.istream.unformatted]
basic_istream<charT, traits>& ignore(int *n*, int_type *delim*)

27.6.2.2 basic_ostream constructors [lib.ostream.cons]
virtual ~basic_ostream()

27.6.2.4.2 basic_ostream::operator<< [lib.ostream.inserters]
basic_ostream<charT, traits>& operator<<(char_type c)

Change this **Notes:** clause to a **Requires:** clause.

27.7.1.1 basic_stringbuf constructors [lib.stringbuf.cons]
explicit basic_stringbuf(ios_base::openmode)

27.8.1.4 Overridden virtual functions [lib.filebuf.virtuals]
int_type pbackfail(int_type *c*)

Possible Resolution:

The pre-Stockholm Iostreams WG recommends that Non-normative notes to "[Note:" style, change normative "Notes" to some other heading word. Jerry Schwarz will provide text for the proposal.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-914
Title: rethrowing exceptions
Section: 27.6.2.4.1 Common requirements **[lib.ostream.formatted.reqmts]**
Status: **active**
Description:

[NOTE: This follows directly with 27-903 --John Hinke]

The typical operator<< looks like this, given current semantics for exceptions:

```
{
 sentry cerberos(*this); if (!cerberos) return;
 iostate save = exceptions(); exceptions(0);

 try {
  if (use_facet< num_put<charT,ostreambuf_iterator<charT,traits> >(
       getloc()).put(*this,*this,fill(),getloc(),val).failed())
    setstate(failbit); // won't throw
 }
 catch (...) { exceptions(save); setstate(badbit); throw; }
 exceptions(save); setstate(rdstate());
}
```

If we change exception semantics so that ios_base::failure just gets rethrown, without setting badbit, we have instead:

```
{
 sentry cerberos(*this);
 if (!cerberos) return;
 try {
  if (use_facet< num_put<charT,ostreambuf_iterator<charT,traits> >(
       getloc()).put(*this,*this,fill(),getloc(),val).failed())
    setstate(failbit);  // might throw
 }
 catch (const ios_base::failure&) { throw; }
 catch (...)                      { setstate(badbit); throw; }
}
```

The examples don't constitute an argument for or against the change, but rather are suggestions for the example code that should appear in **[lib.ostream.formatted.reqmts]** according to what is decided.

For the record, I am in favor of the change.

Possible Resolution:

We do not have any example code in 27.6.2.4.1 **Common requirements [lib.ostream.formatted.reqmts],** but if we want to add one, the ones described above are not correct.

The pre-Stockholm Iostreams WG recommends to add an example (editorial), but details will depend on a pending proposal from Jerry Schwarz about the "sentry" types.

Requestor: Nathan Myers (ncm@cantrip.org)

Issue Number: 27-915
Title: The use of specialization
Section: 27
Status: **active**
Description:

There is wording in Clause 27 such as:

"...iostream classes are the instantiations of the..."
"...class ios is an instance of the..."
"...class wios is a version of the..."

This wording needs to be consistent with the rest of the document.

Possible Resolution:

Make the following changes to be consistent:

27.1.1 Definitions [lib.iostreams.definitions]
Replace: "**-- narrow-oriented iostream classes** ...iostream classes are the instantiations of the..."
With: "**--narrow-oriented iostream classes** ...iostream classes are specializations of the..."

27.1.1 Definitions [lib.iostreams.definitions]
Replace: "**-- wide-oriented iostream classes** ...iostream classes are the instantiations of the..."
With: "**-- wide-oriented iostream classes** ...iostream classes are specializations of the..."

27.2 Forward declarations [lib.iostream.forward] paragraph 2
Replace: "The class ios is an instance of the template..."
With: "The class ios is a specialization of the template..."

27.2 Forward declarations [lib.iostream.forward] paragraph 3
Replace: "The class wios is a version of the template..."
With: "The class wios is a specialization of the template..."

27.4.2 Template struct ios_traits [lib.ios.traits] paragraph 2
Replace: "An implementation shall provide the following two instantiations of ios_traits:"
With: "An implementation shall provide the following two specializations of ios_traits:"

27.5.2 Templates class basic_streambuf<charT, traits> [lib.streambuf] paragraph 2
Replace: "The class streambuf is an instantiation of the template..."
With: "The class streambuf is a specialization of the template..."

27.5.2 Templates class basic_streambuf<charT, traits> [lib.streambuf] paragraph 3
Replace: "The class wstreambuf is an instantiation of the template..."
With: "The class wstreambuf is a specialization of the template..."

The pre-Stockholm Iostreams WG recommends to treat as editorial, but more work is needed to preserve distinction between explicit and implicit specialization.

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-916
Title: missing descriptions of specializations
Section: 27
Status: **active**
Description:

For compatibility, each templatized class has two specializations. One for skinny characters and one for wide characters. For example:

```
template<class charT, class traits>
class basic_ios : public ios_base {
  //...
};
```

Class ios is a specialization of...
Class wios is a specialization of...

These descriptions are missing for some of the classes. This proposal adds these missing descriptions.

Possible Resolution:

Add the following descriptions to the appropriate sections:

For class basic_ios:

27.4.4 Template class basic_ios [lib.ios]
The class ios is a specialization of the template class basic_ios specialized by the type char.

The class wios is a specialization of the template class basic_ios specialized by the type wchar_t.

For class basic_istream:

27.6.1.1 Template class basic_istream [lib.istream]
The class istream is a specialization of the template class basic_istream specialized by the type char.

The class wistream is a specialization of the template class basic_istream specialized by the type wchar_t.

For class basic_ostream:

27.6.2.1 Template class basic_ostream [lib.ostream]

The class ostream is a specialization of the template class basic_ostream specialized by the type char.

The class wostream is a specialization of the template class basic_ostream specialized by the type wchar_t.

For class basic_stringbuf:

27.7.1 Template class basic_stringbuf [lib.stringbuf]

The class stringbuf is a specialization of the template class basic_stringbuf specialized by the type char.

The class wstringbuf is a specialization of the template class basic_stringbuf specialized by the type wchar_t.

For class basic_istringstream:

27.7.2 Template class basic_istringstream [lib.istringstream]

The class istringstream is a specialization of the template class basic_istringstream specialized by the type char.

The class wistringstream is a specialization of the template class basic_istringstream specialized by the type wchar_t.

For class basic_ostringstream:

27.7.2.3 Template class basic_ostringstream [lib.ostringstream]

The class ostringstream is a specialization of the template class basic_ostringstream specialized by the type char.

The class wostringstream is a specialization of the template class basic_ostringstream specialized by the type wchar_t.

For class basic_filebuf:

27.8.1.1 Template class basic_filebuf [lib.filebuf]

The class filebuf is a specialization of the template class basic_filebuf specialized by the type char.

The class wfilebuf is a specialization of the template class basic_filebuf specialized by the type wchar_t.

For class basic_ifstream:

27.8.1.5 Template class basic_ifstream [lib.ifstream]

The class ifstream is a specialization of the template class basic_ifstream specialized by the type char.

The class wifstream is a specialization of the template class basic_ifstream specialized by the type wchar_t.

For class basic_ofstream:

27.8.1.8 Template class basic_ofstream [lib.ofstream]

The class ofstream is a specialization of the template class basic_ofstream specialized by the type char.

The class wofstream is a specialization of the template class basic_ofstream specialized by the type wchar_t.

The pre-Stockholm Iostreams WG recommends closing the issue with no change to the WP, since the proposal is subsumed by proposed change to <iosfwd> (27-904).

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-917
Title: Editorial changes
Section: 27.1.2 Type requirements **[lib.iostreams.type.reqmts]**
Status: **active**
Description:

27.1.2 **[lib.iostreams.type.reqmts]**: Last sentence: "... expects to the character container class." should read "... expects of the character container class."

Possible Resolution:

Requestor: Public Comment

Issue Number: 27-918
Title: Validity of OFF_T to POS_T conversion
Section: 27.1.2.3 Type OFF_T **[lib.iostreams.off.t]**
Status: **active**
Description:

27.1.2.3 **[lib.iostreams.off.t]**: Paragraph 4: "Type OFF_T is convertible to type POS_T. But no validity of the resulting POS_T value is ensured, whether or not the OFF_T value is valid." Of what use is the conversion, then?

Possible Resolution:

The pre-Stockholm Iostreams WG recommends to treat as editorial and added a footnote.

Requestor: Public Comment

Issue Number: 27-919
Title: Question on Table 2 assertions
Section: 27.1.2.4 Table2 Position type requirements **[lib.iostreams.pos.t]**
Status: **active**
Description:

27.1.2.4 **[lib.iostreams.pos.t]**: table 2: first row has assertion "p == P(i)" but p does not appear in the expression for that row; also, that row has the note "a destructor is assumed" -- what does this mean?

Possible Resolution:

The first row of table 2 should be deleted. The second row already specifies the construction and assignment from an integer value.

The pre-Stockholm Iostreams WG recommends accepting the above resolution. A larger issue is the table was voted out of the iostreams chapter as part of traits consolidation, but needs to be somewhere. The discussions of OFF_T and POS_T should be consolidated in iostreams chapter, with a note added to string chapter referring to this chapter. Philippe Le Mouël will provide text for the proposal.

Requestor: Public Comment

Issue Number: 27-920
Title: destination of clog and wclog
Section: 27.3.1 Narrow stream objects **[lib.narrow.stream.objects]**, 27.3.2 Wide stream objects **[lib.wide.stream.objects]**
Status: **active**
Description:

There is currently an editorial box concerning the destination of clog and wclog. I would like to propose the following resolution:

Possible Resolution:

Change **27.3.1 Narrow stream objects [lib.narrow.stream.objects]** paragraph 6 to:
The object clog controls output to an implementation defined stream buffer.

Change **27.3.2 Wide stream objects [lib.wide.stream.objects]** paragraph 6 to:
The object wclog controls output to an implementation defined stream buffer.

The pre-Stockholm Iostreams WG recommends closing with no change to the WP (delete the editorial box).

Requestor: John Hinke (hinke@roguewave.com)

Issue Number: 27-921
Title: default locale argument to constructor
Section: 27
Status: **active**
Description:

Default locale arguments for stream constructors.

istream and ostream constructors (and all derivations) should have a default locale argument, in the manner of

```
obogusstream(const char *name,const locale& l = locale());
```

Possible Resolution:

Add a new argument to the standard stream constructors:

```
const locale& l = locale::global()
```

Add this new argument to the following classes' constructors:

basic_istream,
basic_ostream,
basic_istringstream,
basic_ostringstream,
basic_ifstream,
basic_ofstream
istrstrem
ostrstream

The pre-Stockholm Iostreams WG recommends closing with no change to the WP

Requestor: Nathan Myers (ncm@cantrip.org)
Norihiro Kumagai (kuma@slab.tnr.sharp.co.jp)

Issue Number: 27-922
Title: Cleaning the iostreams header synopsis #include of other headers
Section: Chapter 27 and Annex D
Status: **active**
Description:

Several public comments pointed out that the C++ header synopsis #include of other C++ headers were not correct.

Possible Resolution:

Add to header <iostream> synopsis:	<istream> and <ostream>
Add to header <sstream> synopsis:	<string> (already brought by locale)
Add to header <streambuf> synopsis:	<locale>
Add to header <strstream> synopsis:	<streambuf>

Requestor: Judy Ward

Annex D issues

Issue Number: 27-1001
Title: description of function setbuf is not sufficient
Section: D.6.1.3 **strstreambuf overridden virtual functions [depr.strstreambuf.virtuals]**
Status: **active**
Description:

Description of the overridden setbuf(char* s,streamsize n) function in class strstreambuf is not sufficient.

Possible Resolution:

Change the current description of function setbuf(char* s, streamsize n) in D.6.1.3 **strstreambuf overridden virtual functions [depr.strstreambuf.virtuals]** to:

streambuf* setbuf(char* s, streamsize n);

and not:

streambuf<char>* setbuf(char* s, streamsize n);

Effects: If *s* is not a null pointer, and n > pptr() - pbase(), replace the current buffer (copy its contents and deallocate it) by the buffer of size *n* pointed at by *s*.
In the case where *s* is a null pointer, and n > pptr() - pbase() resize the current buffer to size *n*.
If the function fails, it returns a null pointer.
Returns: (streambuf*)(this)

I am not qualified enough to decide if the return type should be changed to strstreambuf* as proposed by Steve Clamage in issue 27-809. I tried it with several compilers, and the results were just error messages. Basically, the compilers were complaining about the fact that the base class virtual function and the overridden virtual function should have the same return type.

The pre-Stockholm Iostreams WG recommends the behavior of the *setbuf* function to be implementation-defined, except that setbuf(0,0) has no effect. The return type in the WP is coreect. Steve Clamage will provide text for the proposal.

Requestor: philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-1002
Title: strstreambuf Editorial issues
Section: D.6.1 **Class strstreambuf [depr.strstreambuf]**
Status: **active**
Description:

Class strstreambuf contains several typos and is also missing some typedefs.

Possible Resolution:

The following typedefs need to be added to class strstreambuf (D.6.1 **Class strstreambuf [depr.strstreambuf]**) :

- typedef char_traits<char>::int_type int_type;

This typedef is used in the strstreambuf overridden virtual functions *overflow , pbackfail* and *underflow*.

- typedef char_traits<char>::pos_type pos_type;

This typedef is used in the strstreambuf overridden virtual functions *seekoff* and *seekpos.*

- typedef char_traits<char>::off_type off_type;

This typedef is used in the strstreambuf overridden virtual function *seekoff.*

In D.6.1 **Class strstreambuf [depr.strstreambuf]** the notation of the strstreambuf base class is wrong it should say:

class strstreambuf : public basic_streambuf<char>

and not:

class strstreambuf : public streambuf<char> // does not exist

In D.6.1 **Class strstreambuf [depr.strstreambuf]** the declaration of function freeze is missing the argument name. It should say:

void freeze(bool freezefl =1);

and not:

void freeze(bool = 1);

The pre-Stockholm Iostreams WG recommends treating as editorial. The corrections have already been made.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-1003
Title: istrstream Editorial issues (typos)
Section: D.6.2 **Template class istrstream [depr.istrstream]**
Status: **active**
Description:

Class istrstream contents several typos.

Possible Resolution:

In D.6.2 **Template Class istrstream [depr.istrstream]** the previous title should be changed to "D.6.2 Class istrstream", because the class is not a template class.

In D.6.2 **Template Class istrstream [depr.istrstream]** the notation of the istrstream base class is wrong. It should say:

class istrstream : public basic_istream<char>

and not:

class istrstream : public istream<char> // does not exist

The pre-Stockholm Iostreams WG recommends treating as editorial. The corrections have already been made.

Requestor: Philippe Le Mouël (philippe@roguewave.com)

Issue Number: 27-1004
Title: ostrstream Editorial issues (typos)
Section: D.6.3 **Template class ostrstream [depr.ostrstream]**
Status: **active**
Description:

Class ostrstream contents several typos.

Possible Resolution:

In D.6.3 **Template Class ostrstream [depr.ostrstream]** the previous title should be changed to "D.6.3 Class ostrstream", because the class is not a template class.

In D.6.3 **Template Class ostrstream [depr.ostrstream]** the notation of the ostrstream base class is wrong. It should say:

class ostrstream : public basic_ostream<char>

and not:

class ostrstream : public ostream<char> // does not exist

In D.6.3 **Template Class ostrstream [depr.ostrstream]** and D.6.3.2 **Member functions[depr.ostrstream.members]** the declaration of function *void freeze(int freezefl = 1)* is not consistent with the declaration in D.6.1 **Class strstreambuf [depr.strstreambuf],** which is *void freeze(bool freezefl =1).* The argument should be *bool* or *int*, but not *bool* in one and *int* in the other.

The pre-Stockholm Iostreams WG recommends treating as editorial. The corrections have already been made.

Requestor: Philippe Le Mouël (philippe@roguewave.com)